

Niche tiles[®]

United States of America
United States Patent and Trademark Office

Niche tiles

Reg. No. 6,145,274

Niche Tiles & Stone Inc. (GEORGIA CORPORATION)

Niche tiles®

APPENDIX 2020

Declaration of Performance for 4"x4" Resin Metal Insert.....	PAGE 3
Declaration of Performance for 2"x2" Resin Metal Insert.....	PAGE 4
Declaration of Performance for 2"x12" Resin Metal Trim Pieces.....	PAGE 5
Declaration of Performance for 1/2"x12" Resin Metal Trim Pieces.....	PAGE 6
Declaration of Performance for 1 1/5"x12" Resin Metal Trim Pieces.....	PAGE 7
Declaration of Performance for 12"x18" Resin Metal Mural/Plaque.....	PAGE 8
Declaration of Performance for 15 3/4"x 23 2/3" Resin Metal Mural/Plaque.....	PAGE 9
Declaration of Performance for 12"x12" Resin Metal Mosaic (4"x4" loose pieces).....	PAGE 10
Declaration of Performance for 9"x12" Resin Metal Mosaic (3"x9" loose pieces).....	PAGE 11

DECLARATION PERFORMANCE

No.001CPR2020-02-08

- Unique identification code of the product-type:
4"x4" Resin Metal Insert
- Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
In Style Collection 4"x4" Resin Metal Insert
Heritage Collection 4"x4" Resin Metal Insert
- Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

In Style Urban 4"x4" Resin Metal Wall Insert	Heritage Western 4"x4" Resin Metal Wall Insert	} Residential Interior Wall
In Style Mood 4"x4" Resin Metal Wall Insert	Heritage Retro 4"x4" Resin Metal Wall Insert	
In Style Vertical 4"x4" Resin Metal Wall Insert	Heritage Custom 4"x4" Resin Metal Wall Insert	
In Style Reflection 4"x4" Resin Metal Wall Insert	Heritage Vintage 4"x4" Resin Metal Wall Insert	
In Style Focus 4"x4" Resin Metal Wall Insert	Heritage Dot 4"x4" Resin Metal Wall Insert	
In Style Handcraft 4"x4" Resin Metal Wall Insert	Heritage Florance 4"x4" Resin Metal Wall Insert	

- Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
NICHE TILE &STONE Inc
- System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 4**
- In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15285: 2008 (European Norm) – Agglomerated Stone, Modular Tiles for internal walls
- Declared performance

Characteristics	Declared values	Test method
Appearance	Roughly equidimensional grains	Visual
Tacility	Polished finish	Visual
Reaction to fire	A2fl-S1	Euro Classes
Flexural strength	Avr. Value (Mpa) 65.7	EN 14617-2:2008 Part 2
Water absorption	0.02%	EN 14617-1
Internal Slip resistance	NPD	
Apparent density	2.26 g/cm3	EN 14617-1:2005 Part1
Thermal conductivity	Wet 1.6 (W/mk) Dry 1.6 (W/mk)	ASTM E1225-13
Geometric Characteristics	Length 97 mm and Width 97 mm	EN 14617-16:2005 Part16
	deviation - 0.10 % ~ + 0.3 %	
	Thickness 8 mm deviation - 1 % ~ + 1 %	
	Average: 8 mm	
	Straightness 0.0 mm ~ + 0.1mm	
	Rectangularity -0.1mm ~ + 0.2mm	
	Centre curvature -0.1% ~ - 0.05%	
	Flatness Edge curvature +0.05% ~ + 0.1 % Warping -0.25% ~ 0.1 %	
Surface quality	No defects	
Shade Variation	V3	While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly.

DECLARATION PERFORMANCE

No.001CPR2020-02-23

- Unique identification code of the product-type:
2"x2" Resin Metal Insert
- Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
In Style Collection 2"x2" Resin Metal Insert
Heritage Collection 2"x2" Resin Metal Insert
- Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

In Style Urban 2"x2"Resin Metal Wall Insert	Heritage Western 2"x2"Resin Metal Wall Insert	} Residential Interior Wall
In Style Mood 2"x2"Resin Metal Wall Insert	Heritage Retro 2"x2"Resin Metal Wall Insert	
In Style Vertical 2"x2"Resin Metal Wall Insert	Heritage Custom 2"x2"Resin Metal Wall Insert	
In Style Reflection 2"x2"Resin Metal Wall Insert	Heritage Vintage 2"x2"Resin Metal Wall Insert	
In Style Focus 2"x2"Resin Metal Wall Insert	Heritage Dot 2"x2"Resin Metal Wall Insert	
In Style Handcraft 2"x2"Resin Metal Wall Insert	Heritage Florance 2"x2"Resin Metal Wall Insert	

- Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
NICHE TILES & STONE INC
- System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 4**
- In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15285: 2008 (European Norm) – Agglomerated Stone, Modular Tiles for internal walls
- Declared performance

Characteristics	Declared values		Test method	
Appearance	Roughly equidimensional grains		Visual	
Tacility	Polished finish		Visual	
Reaction to fire	A2fl-S1		Euro Classes	
Flexural strength	Avr. Value (Mpa) 65.7		EN 14617-2:2008 Part 2	
Water absorption	0.02%		EN 14617-1	
Internal Slip resistance	NPD			
Apparent density	2.24 g/cm3		EN 14617-1:2005 Part1	
Thermal conductivity	Wet	1.6 (W/mk)	ASTM E1225-13	
	Dry	1.6 (W/mk)		
Geometric Characteristics	Length	48 mm	EN 14617-16:2005 Part16	
	and	48 mm		
	Width	deviation		- 0.10 % ~ + 0.3 %
	Thickness	8 mm		Average: 8 mm
		deviation		- 1 % ~+ 1 %
	Straightness	0.0 mm ~ + 0.1mm		
	Rectangularity	-0.1mm ~ + 0.2mm		
	Flatness	Centre curvature		-0.1% ~ - 0.05%
Edge curvature		+0.05% ~ + 0.1 %		
Warping		-0.25% ~0.1 %		
Surface quality	No defects			
Shade Variation	V3	While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly.		

DECLARATION PERFORMANCE

No.001CPR2020-03-15

1. Unique identification code of the product-type:

2"x12" Resin Metal Trim Pieces

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

In Style Collection 2"x12" Resin Metal Liner

Heritage Collection 2"x12" Resin Metal Liner

In Style Collection 2"x12" Resin Metal Chair Rail

Heritage Collection 2"x12" Resin Metal Chair Rail

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

In Style 2"x12" Resin Metal Chair Rail

In Style 2"x12" Resin Metal Focus Liner

Heritage 2"x12" Resin Metal Chair Rail

In Style 2"x12" Resin Metal Handcraft Liner

Residential Interior Wall

In Style 2"x12" Resin Metal Chic Liner

Heritage 2"x12" Resin Metal Mixed Liner

In Style 2"x12" Resin Metal Linear Liner

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

NICHE TILES & STONE INC

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 4**

6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 15285: 2008 (European Norm) – Agglomerated Stone, Modular Tiles for internal walls

7. Declared performance

Characteristics	Declared values	Test method	
Appearance	Roughly equidimensional grains	Visual	
Tacility	Polished finish	Visual	
Reaction to fire	A2fl-S1	Euro Classes	
Flexural strength	Avr. Value (Mpa) 65.7	EN 14617-2:2008 Part 2	
Water absorption	0.02%	EN 14617-1	
Internal Slip resistance	NPD		
Apparent density	2.42 g/cm3	EN 14617-1:2005 Part1	
Thermal conductivity	Wet 1.6 (W/mk) Dry 1.6 (W/mk)	ASTM E1225-13	
Geometric Characteristics	Length and Width	EN 14617-16:2005 Part16	
	305 mm 48 mm		
	deviation		- 0.10 % ~ + 0.3 %
	Thickness		Average: 8 mm
	deviation		- 1 % ~+ 1 %
	Straightness		0.0 mm ~ + 0.1mm
	Rectangularity		-0.1mm ~ + 0.2mm
	Flatness		Centre curvature -0.1% ~- 0.05% Edge curvature +0.05% ~ + 0.1 % Warping -0.25% ~0.1 %
Surface quality	No defects		
Shade Variation	V3	While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly.	

DECLARATION PERFORMANCE

No.001CPR2020-04-04

1. Unique identification code of the product-type:
1/2"X12" Resin Metal Trim Pieces
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
In Style Collection 1/2"X12" Resin Metal Pencil Liner
Heritage Collection 1/2"X12" Resin Metal Pencil Liner
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
In Style 1/2"X12" Resin Metal Pencil Liner }
Heritage 1/2"X12" Resin Metal Pencil Liner } **Residential Interior Wall**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
NICHE TILES & STONE INC
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 4**
6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15285: 2008 (European Norm) – Agglomerated Stone, Modular Tiles for internal walls
7. Declared performance

Characteristics	Declared values		Test method	
Appearance	Roughly equidimensional grains		Visual	
Tacility	Polished finish		Visual	
Reaction to fire	A2fl-S1		Euro Classes	
Flexural strength	Avr. Value (Mpa) 65.7		EN 14617-2:2008 Part 2	
Water absorption	0.02%		EN 14617-1	
Internal Slip resistance	NPD			
Apparent density	2.32 g/cm3		EN 14617-1:2005 Part1	
Thermal conductivity	Wet	1.6 (W/mk)	ASTM E1225-13	
	Dry	1.6 (W/mk)		
Geometric Characteristics	Length	305 mm	EN 14617-16:2005 Part16	
	and	12 mm		
	Width	deviation - 0.10 % ~ + 0.3 %		
	Thickness	8 mm		Average: 8 mm
		deviation		- 1 % ~+ 1 %
	Straightness	0.0 mm ~ + 0.1mm		
	Rectangularity	-0.1mm ~ + 0.2mm		
	Flatness	Centre curvature		-0.1% ~ - 0.05%
Edge curvature		+0.05% ~ + 0.1 %		
	Warping	-0.25% ~0.1 %		
Surface quality	No defects			
Shade Variation	V3	While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly.		

**DECLARATION
PERFORMANCE**

No.001CPR2020-04-19

1. Unique identification code of the product-type:
1 1/5"X12" Resin Metal Trim Pieces
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
Heritage Collection 1 1/5"X12" Resin Metal Liner
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
Heritage 1 1/5"X12" Resin Metal Dot Liner : Residential Interior Wall
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
NICHE TILES & STONE INC
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 4**
6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15285: 2008 (European Norm) – Agglomerated Stone, Modular Tiles for internal walls
7. Declared performance

Characteristics	Declared values		Test method	
Appearance	Roughly equidimensional grains		Visual	
Tacility	Polished finish		Visual	
Reaction to fire	A2fl-S1		Euro Classes	
Flexural strength	Avr. Value (Mpa) 65.7		EN 14617-2:2008 Part 2	
Water absorption	0.02%		EN 14617-1	
Internal Slip resistance	NPD			
Apparent density	2.51 g/cm ³		EN 14617-1:2005 Part1	
Thermal conductivity	Wet	1.6 (W/mk)	ASTM E1225-13	
	Dry	1.6 (W/mk)		
Geometric Characteristics	Length and Width	305 mm 30 mm deviation - 0.10 % ~ + 0.3 %	EN 14617-16:2005 Part16	
	Thickness	8 mm deviation - 1 % ~ + 1 % Average: 8 mm		
	Straightness	0.0 mm ~ + 0.1mm		
	Rectangularity	-0.1mm ~ + 0.2mm		
	Flatness	Centre curvature		-0.1% ~ - 0.05%
		Edge curvature		+0.05% ~ + 0.1 %
		Warping		-0.25% ~ 0.1 %
	Surface quality	No defects		
Shade Variation	V3	While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly.		

**DECLARATION
PERFORMANCE**

No.001CPR2020-04-24

1. Unique identification code of the product-type:
12"X18" Resin Metal Mural / Plaque
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
Viola 12"x18" Resin Metal Mural
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
Viola 12"x18" Resin Metal Mural : Residential Interior Wall
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
NICHE TILES & STONE INC
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 4**
6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15285: 2008 (European Norm) – Agglomerated Stone, Modular Tiles for internal walls
7. Declared performance

Characteristics	Declared values		Test method	
Appearance	Roughly equidimensional grains		Visual	
Tacility	Polished finish		Visual	
Reaction to fire	A2fl-S1		Euro Classes	
Flexural strength	Avr. Value (Mpa) 65.7		EN 14617-2:2008 Part 2	
Water absorption	0.02%		EN 14617-1	
Internal Slip resistance	NPD			
Apparent density	2.27 g/cm3		EN 14617-1:2005 Part1	
Thermal conductivity	Wet Dry	1.6 (W/mk) 1.6 (W/mk)	ASTM E1225-13	
Geometric Characteristics	Length and Width	457 mm 305 mm deviation - 0.10 % ~ + 0.3 %	EN 14617-16:2005 Part16	
	Thickness	10 mm deviation - 1 % ~+ 1 % Average: 10 mm		
	Straightness	0.0 mm ~ + 0.1mm		
	Rectangularity	-0.1mm ~ + 0.2mm		
	Flatness	Centre curvature		-0.1% ~ - 0.05%
		Edge curvature		+0.05% ~ + 0.1 %
		Warping		-0.25% ~0.1 %
	Surface quality	No defects		
Shade Variation	V3	While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly.		

DECLARATION PERFORMANCE

No.001CPR2020-04-27

1. Unique identification code of the product-type:
15 3/4"X23 2/3" Resin Metal Mural / Plaque
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
Cypress 15 3/4"X23 2/3" Resin Metal Mural
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
Cypress 15 3/4"X23 2/3" Resin Metal Mural : Residential Interior Wall
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
NICHE TILES & STONE INC
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 4**
6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15285: 2008 (European Norm) – Agglomerated Stone, Modular Tiles for internal walls

7. Declared performance

Characteristics	Declared values		Test method	
Appearance	Roughly equidimensional grains		Visual	
Facility	Polished finish		Visual	
Reaction to fire	A2fl-S1		Euro Classes	
Flexural strength	Avr. Value (Mpa) 65.7		EN 14617-2:2008 Part 2	
Water absorption	0.02%		EN 14617-1	
Internal Slip resistance	NPD			
Apparent density	2.27 g/cm ³		EN 14617-1:2005 Part1	
Thermal conductivity	Wet	1.6 (W/mk)	ASTM E1225-13	
	Dry	1.6 (W/mk)		
Geometric Characteristics	Length and Width	600 mm and 400 mm deviation	EN 14617-16:2005 Part16	
	Thickness	10 mm deviation		
	Straightness	Average: 10 mm deviation		
	Rectangularity	- 0.10 % ~ + 0.3 %		
	Flatness	Centre curvature		- 1 % ~ + 1 %
		Edge curvature		0.0 mm ~ + 0.1mm
	Warping	Warping		-0.1mm ~ + 0.2mm
		Surface quality		-0.1% ~ - 0.05% +0.05% ~ + 0.1 % -0.25% ~ 0.1 %
Shade Variation	V3	While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly.		

DECLARATION PERFORMANCE

No.001CPR2020-05-09

1. Unique identification code of the product-type:
12"x12" Resin Metal Mosaic (4"x4" loose pieces)
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
Inherent 12"x12" Resin Metal Mosaic (4"x4" loose pieces)
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
Inherent 12"x12" Resin Metal Mosaic (4"x4" loose pieces) : Residential Interior Wall
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
NICHE TILES & STONE INC
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 4**
6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15285: 2008 (European Norm) – Agglomerated Stone, Modular Tiles for internal walls

7. Declared performance

Characteristics	Declared values		Test method	
Appearance	Roughly equidimensional grains		Visual	
Facility	Fine ground matte finish		Visual	
Reaction to fire	A2fl-S1		Euro Classes	
Flexural strength	Avr. Value (Mpa) 65.7		EN 14617-2:2008 Part 2	
Water absorption	0.02%		EN 14617-1	
Internal Slip resistance	NPD			
Apparent density	2.26 g/cm ³		EN 14617-1:2005 Part1	
Thermal conductivity	Wet	1.6 (W/mk)	ASTM E1225-13	
	Dry	1.6 (W/mk)		
Geometric Characteristics	Length	99 mm	EN 14617-16:2005 Part16	
	and	99 mm		
	Width	deviation - 0.10 % ~ + 0.3 %		
	Thickness	6 mm		Average: 6 mm
		deviation		- 1 % ~+ 1 %
	Straightness	0.0 mm ~ + 0.1mm		
	Rectangularity	-0.1mm ~ + 0.2mm		
	Flatness	Centre curvature		-0.1% ~- 0.05%
Edge curvature		+0.05% ~ + 0.1 %		
Warping		-0.25% ~0.1 %		
Surface quality	No defects			
Shade Variation	V3	While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly.		

DECLARATION PERFORMANCE

No.001CPR2020-05-17

1. Unique identification code of the product-type:
9"x12" Resin Metal Mosaic (3"x9" loose pieces)
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
Majestic 9"x12" Resin Metal Mosaic (3"x9" loose pieces)
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
Majestic 9"x12" Resin Metal Mosaic (3"x9" loose pieces) : Residential Interior Wall
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
NICHE TILES & STONE INC
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 4**
6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15285: 2008 (European Norm) – Agglomerated Stone, Modular Tiles for internal walls
7. Declared performance

Characteristics	Declared values		Test method	
Appearance	Roughly equidimensional grains		Visual	
Tacility	Fine ground matte finish		Visual	
Reaction to fire	A2fl-S1		Euro Classes	
Flexural strength	Avr. Value (Mpa) 65.7		EN 14617-2:2008 Part 2	
Water absorption	0.02%		EN 14617-1	
Internal Slip resistance	NPD			
Apparent density	2.64 g/cm3		EN 14617-1:2005 Part1	
Thermal conductivity	Wet	1.6 (W/mk)	ASTM E1225-13	
	Dry	1.6 (W/mk)		
Geometric Characteristics	Length	225 mm	EN 14617-16:2005 Part16	
	and	75 mm		
	Width	deviation		- 0.10 % ~ + 0.3 %
	Thickness	6 mm		Average: 6 mm
		deviation		- 1 % ~ + 1 %
	Straightness	0.0 mm ~ + 0.1mm		
	Rectangularity	-0.1mm ~ + 0.2mm		
	Flatness	Centre curvature		-0.1% ~ - 0.05%
Edge curvature		+0.05% ~ + 0.1 %		
Warping		-0.25% ~ 0.1 %		
Surface quality	No defects			
Shade Variation	V3	While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly.		