

	SAFETY DATA SHEET	Version: R0001.0001
		Date of issue: 2019-07-05
	INR18650M26	Revision date: Not applicable
		Change List:

Copyright 2017. LG Chem, Ltd. all rights reserved.

1. IDENTIFICATION

A. Product name

- 18650 M26

B. Recommended use and restriction on use

- General use : Not available
 - Restriction on use : Not available

C. Manufacturer / Supplier / Distributor information

o Manufacturer information

- Company name : LG Chem I & E Materials Co. Ltd.
 - Address : Hengyi Road, Nanjing Economic & Technological Development Zone, Nanjing, Jiangsu, China
 - Dept. : --
 - Telephone number : --
 - Emergency telephone number : --
 - Fax number : --
 - E-mail address : --

o Supplier/Distributor information

- Company name : LG Chem I & E Materials Co. Ltd.
 - Address : Hengyi Road, Nanjing Economic & Technological Development Zone, Nanjing, Jiangsu, China
 - Dept. : --
 - Telephone number : --
 - Emergency telephone number : --
 - Fax number : --
 - E-mail address : --

2. HAZARD IDENTIFICATION

A. GHS Classification

- Carcinogenicity : Category1A
 - Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)
 - Specific target organ toxicity(Repeated exposure) : Category2
 - Acute aquatic toxicity : Category1
 - Chronic aquatic toxicity : Category1

B. GHS label elements

o Hazard symbols



o Signal words

- Danger

o Hazard statements

- H335 May cause respiratory irritation.
 - H350 May cause cancer
 - H373 May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)
 - H400 Very toxic to aquatic life
 - H410 Very toxic to aquatic life with long lasting effects

○ **Precautionary statements**

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P281 Use personal protective equipment as required.

2) Response

- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P391 Collect spillage.

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

○ **NFPA grade (0 ~ 4 level)**

- Health : 2, Flammability : 0, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Cobalt lithium manganese nickel oxide	-	182442-95-1	34
Carbon	Acetylene Black ; Graphite (synthetic) ;	7440-44-0	20
Lithium hexafluorophosphate(1-)	Lithium hexafluorophosphate ; Phosphate(1-), hexafluoro-, lithium (1:1) ; Phosphate(1-), hexafluoro-, lithium ; lithium hexafluorophosphate(1-) ; LITHIUM PHOSPHOHEXAFLUORIDE ; Lithium fluophosphate ; Lithium hexafluoro phosphate ; Lithium hexafluorophosphate ; Lithium hexafluorophosphate (LiPF6) ; Lithium phosphorus fluoride (LiPF6) ;	21324-40-3	20
Copper	Copper concentrate ; Copper element ; Copper powder ; Copper metal ;	7440-50-8	10
Aluminium	Allbri aluminum paste and powder ; Aluminium bronze ; Aluminium flake ; Aluminum dehydrated ; Aluminum powder ; Metana ; Metana aluminum paste ; Noral aluminium ;	7429-90-5	10
1,1-Difluoroethene homopolymer	-	24937-79-9	5
Ethenylbenzene polymer with 1,3-butadiene	-	9003-55-8	1

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.
- Remove contaminated clothing, shoes and isolate.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES**A. Suitable (Unsuitable) extinguishing media**

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Do not access if the tank on fire.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES**A. Personal precautions, protective equipment and emergency procedures**

- Wear proper personal protective apparatus as indicated in Section 8 and avoid skin contact and inhalation.
- Must work against the wind, let the upwind people to evacuate.
- Move container to safe area from the leak area.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Avoid entering to sewers or water system.
- Prevent the influx to waterways, sewers, basements or confined spaces.
- Spilled material should be treated as a potential risk of waste collected.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Since emptied containers retain product residue(vapor, liquid, solid) follow all MSDS and label warnings even after container is emptied.
- Get the manual before use.
- Refer to Engineering controls and personal protective equipment.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Do not use damaged containers.
- Do not apply direct heat.
- Avoid direct sunlight.
- Keep in the original container.
- Keep sealed when not in use.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- **ACGIH TLV**
 - [Cobalt lithium manganese nickel oxide] : TWA 0.1 mg/m³, Nickel Soluble inorganic compounds
 - [Aluminium] : TWA, 1 mg/m³, Respirable Particulate Matter
 - [Copper] : TWA, 0.2 mg/m³ (Fume, as Cu), TWA, 1 mg/m³ (Dusts and Mists, as Cu)
- **OSHA PEL**
 - [Aluminium]: 15 mg/m³ (Total dust), 5 mg/m³ (Respirable fraction)
 - [Cobalt lithium manganese nickel oxide]: 1mg/m³
 - [Copper]: 0.1 mg/m³ (Fume), 1 mg/m³ (Dusts and mists)

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

- **Respiratory protection**
 - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
 - Respiratory protection is ranked in order from minimum to maximum.
 - Consider warning properties before use.
- **Eye protection**
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
- **Hand protection**
 - Wear appropriate glove.
- **Skin protection**
 - Wear appropriate clothing.
- **Others**
 - Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Other
- Color	Not available
B. Odor	Not available
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	Not available
G. Flash point	Not available
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity(Relative density)	Not available
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY**A. Chemical Stability**

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
 - Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION**A. Information on the likely routes of exposure**

- (Respiratory tracts)
 - May cause respiratory irritation.
- (Oral)
 - Not available
- (Eye·Skin)
 - Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- Acute toxicity
 - * Oral
 - Product (ATEmix) : 2000mg/kg < ATEmix <= 5000mg/kg
 - [Cobalt lithium manganese nickel oxide] : LD50 >2000 mg/kg Rat (NICNAS)
 - [Carbon] : LD50 > 10000 mg/kg Rat (IUCLID, HSDB)

- [Copper] : LD50 481 mg/kg Rat (OECD TG 401, GLP)
- [Aluminium] : LD50 > 15900 mg/kg Rat (OECD TG 401)
- * **Dermal**
 - Product (ATEmix) : >5000mg/kg
 - [Copper] : LD50 > 2000 mg/kg Rat (OECD TG 402, GLP)
- * **Inhalation**
 - Product (ATEmix) : Not available
 - [Cobalt lithium manganese nickel oxide] : 0.05 < LC50 <= 0.5 mg/L/4hr
 - [Carbon] : Vapor LC50 > 64.4 mg/l Rat
 - [Copper] : LC50 > 5.11 mg/l 4 hr Rat (OECD TG 436, GLP)
 - [Aluminium] : Dust LC50 > 0.888 mg/l 4 hr Rat (OECD TG 403, GLP)
- o **Skin corrosion/irritation**
 - Not available
- o **Serious eye damage/irritation**
 - Not available
- o **Respiratory sensitization**
 - Not available
- o **Skin sensitization**
 - Not available
- o **Carcinogenicity**
 - * **IARC**
 - [Ethenylbenzene polymer with 1,3-butadiene] : Group 3
 - * **OSHA**
 - Not available
 - * **ACGIH**
 - [Lithium hexafluorophosphate(1-)] : A4 (Fluorides)
 - [1,1-Difluoroethene homopolymer] : A4 (Fluorides)
 - [Aluminium] : A4
 - * **NTP**
 - Not available
 - * **EU CLP**
 - Not available
- o **Germ cell mutagenicity**
 - Not available
- o **Reproductive toxicity**
 - Not available
- o **STOT-single exposure**
 - May cause respiratory irritation.
- o **STOT-repeated exposure**
 - May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)
- o **Aspiration hazard**
 - Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- o **Fish**
 - [Cobalt lithium manganese nickel oxide] : LL50 >100 mg/l 96 hr Pimephales promelas (NICNAS)
 - [Copper] : LC50 0.286 mg/l 96 hr Oncorhynchus mykiss (LC50 0.28640% sewage treatment plant effluent, 0.164river water mg/l 96hr)
- o **Crustaceans**
 - [Cobalt lithium manganese nickel oxide] : EL50 >100 mg/l 48 hr Daphnia magna (NICNAS)
 - [Aluminium] : IUCLID NOEC > 100 mg/l 48 hr Daphnia magna
 - [Copper] : LC50 0.0338 mg/l ~ 0.792 mg/l 48 hr Daphnia magna (OECD TG 202)
- o **Algae**
 - [Cobalt lithium manganese nickel oxide] : ErC50 >100 mg/l 72 hr (Pseudokirchneriella subcapitata) (NICNAS)
 - [Aluminium] : NOEC ≥ 0.052 mg/l 72 hr Selenastrum capricornutum (OECD TG 201, GLP)
 - [Copper] : NOEC 0.708 mg/l ~ 0.0376 mg/l 72 hr (Phaeodactylum tricorutum: NOEC = 0.0376 - 0.708 mg/l 72hr, OECD TG 201 Phaeodactylum tricorutum: NOEC = 5.7 µg/l, IOS 10253, GLP)

B. Persistence and degradability

- **Persistence**
 - [Carbon] : log Kow = 0.78 (Estimate)
 - [Copper] : log Kow = -0.57 (Estimate)
- **Degradability**
 - [Carbon] : BOD = 5 ca. 2mgO₂/l , COD = 2000mg/g

C. Bioaccumulative potential

- **Bioaccumulative potential**
 - [Carbon] : BCF = 1.378 (Estimate)
 - [Copper] : BCF = 5830
- **Biodegradation**
 - Not available

D. Mobility in soil

- Not available

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS**A. Disposal methods**

- Since more than two kinds of designated waste is mixed, it is difficult to treat separately, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.

B. Special precautions for disposal

- The user of this product must dispose by oneself or entrust it to a waste disposer, a person who recycles other's waste or establishes and operates waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION**A. UN No. (IMDG)**

- Not applicable

B. Proper shipping name

- Not applicable

C. Hazard Class

- Not applicable

D. IMDG Packing group

- Not applicable

E. Marine pollutant

- Applicable
- Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- Air transport(IATA): Not subject to IATA regulations.

15. REGULATORY INFORMATION**A. National and/or international regulatory information**

- **POPs Management Law**
 - Not applicable
- **Information of EU Classification**
 - * **Classification**
 - [Aluminium] : H261,H250
 - [Aluminium] : H261,H228
- **U.S. Federal regulations**
 - * **OSHA PROCESS SAFETY (29CFR1910.119)**
 - Not applicable
 - * **CERCLA Section 103 (40CFR302.4)**
 - [Copper] : 2267.995 kg 5000 lb
 - * **EPCRA Section 302 (40CFR355.30)**
 - Not applicable
 - * **EPCRA Section 304 (40CFR355.40)**
 - Not applicable
 - * **EPCRA Section 313 (40CFR372.65)**
 - [Aluminium] : Applicable
 - [Copper] : Applicable
- **Rotterdam Convention listed ingredients**
 - Not applicable
- **Stockholm Convention listed ingredients**
 - Not applicable
- **Montreal Protocol listed ingredients**
 - Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2019-07-05

C. Revision number and Last date revised

- Not applicable

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).