Olympic Maximum Clear Waterproofing Sealer

GENERAL DESCRIPTION

Olympic Maximum Clear Sealer provides exceptional protection for wood. Its unique, penetrating formula enhances the natural look of wood while it strengthens, protects, and conditions wood fibers. Recommended for use on exterior wood decks, fences, siding, railings, outdoor furniture and other wood surfaces. Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant or semi-transparent stain.

RECOMMENDED SUBSTRATES

Wood	Siding
Pressure-treated wood	Railings
Decks	Plywood
Fences	Outdoor Furniture

FEATURES / BENEFITS

Penetrating Formula for Strong Protection
Advanced SUNBLOCK® U.V. Protection
Exclusive SCUFF GUARD® Formula
Provides a Mildew Resistant Coating
Enhanced Waterproofing Protection

PRODUCT INFORMATION

57500 Clear Waterproofing Sealant

Do Not Tint.

PACKAGING

Quart (946 mL)
1-Gallon (3.78 L)
5-Gallon (18.9 L)

PRODUCT DATA

PRODUCT TYPE:	Oil Resin
VOLUME SOLIDS:	31% +/- 2%
WEIGHT SOLIDS:	37% +/- 2%
WEIGHT/GALLON:	7.1 lbs. (3.2 kg) +/- 0.2 lbs. (91 g)
VOC:	< 550 g/L (4.6 lbs./gal.)

COVERAGE: Approximately 250 to 350 sq. ft. (23 to 33 sq. meters) per gallon (3.78 L) depending on application, wood texture, and porosity. One coat application is recommended.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries in 24 hours when applied in temperatures of 50ºF (10ºC) to 85ºF (29ºC).High humidity or low temperature application may prolong drying time.

Drying times listed may vary depending on temperature, humidity, film build, and air movement.

CLEANUP: Clean brushes and tools with mineral spirits.
DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH *OLYMPIC MAXIMUM* CLEAR WATERPROOFING SEALANT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

DISPOSAL: Contact your local environmental agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: 108ºF (42ºC)

LIMITATIONS OF USE

FOR EXTERIOR USE ONLY. FOR WOOD SUBSTRATES ONLY.

Apply when no precipitation is expected for 24 hours, and when air and surface temperatures are 50°F (10°C) to 90°F (32°C) and will remain above 50°F (10°C) for the next 24 hours. Caution: Avoid direct skin contact with hot surfaces. Avoid staining in direct sunlight or on hot surfaces.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Not recommended for recently painted or sealed surfaces.

DO NOT use on plastic, rubber, asphalt, tile, vinyl, concrete or any non-porous surface.

Olympic Maximum Clear Waterproofing Sealer

GENERAL SURFACE PREPARATION

Surface must be clean. Remove all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Previous coatings must be completely removed. To ensure proper penetration, weathered, dirty, or mildewed surfaces should be cleaned with a wood cleaner prior to applying stain. After rinsing, ensure surface is free of standing water. Sand all cleaned wood using 80-120 grit sandpaper for vertical surfaces and 60-80 grit sandpaper for horizontal surfaces. Always sand in direction of the wood grain and remove sanding dust. Test wood for absorbency by sprinkling water on the surface—if water is absorbed within 30 sec. to 2 min., depending on climate, the surface is ready for staining.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

FENCES, SIDING OR DECKS: Clean weathered, dirty or mildewed surfaces with *Olympic* Deck Cleaner prior to applying product. Before use, be sure to read and follow the instructions and warnings on the label.

PRETEST: Test a small hidden area prior to application to ensure acceptable appearance and penetration.

EXTRACTIVE BLEEDING: Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to “bleed” or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

APPLICATION INFORMATION

Stir thoroughly and often during use. When using more than one container of the same color, intermix to ensure color uniformity. Apply to a small area and allow stain to dry to ensure acceptable appearance and penetration. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our website or by calling 1-800-441-9695.

Application Method: Apply one thin coat. To help avoid lap marks, apply to only a few boards at a time, and maintain a wet edge. Do not saturate or puddle on horizontal surfaces.

Application Equipment: Apply with a high-quality brush, paint/stain-pad, or with spray equipment. When applying by roller or spray, always back-brush for best results.

Spray equipment must be handled with due care and in accordance with manufacturer’s recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

Thinning: Do not thin.

Permissible temperatures during application:
Material: 50 to 90ºF (10 to 32ºC) Ambient: 50 to 90ºF (10 to 32ºC) Substrate: 50 to 90º (10 to 32ºC)

PRECAUTIONS

For warning information, please refer to the product label and SDS available at the online listing for this product at www.pittsburghpaintsco.com. Keep container tightly closed and sealed until ready for use. SDS, spill, and emergency information are available by calling 1-833-477-1553.

© 2026 The Pittsburgh Paints Co. All Rights Reserved. *Olympic, Olympic and Design, Paintbrush Design, Maximum, Scuff Guard,* and *Sunblock* are registered trademarks, and the *P Logo & Pittsburgh Paints* are trademarks of The Pittsburgh Paints Co.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.

PITTSBURGH PAINTS CO.

The Pittsburgh Paints Company
500 Cranberry Woods Drive
Cranberry Township, PA 16066
www.olympic.com

Technical Services
1-800-441-9695