

- Ready To Use • Applies Smooth
- Rock-Hard After Dry • Easy Water Clean Up

WARNING: Contains 1-Chloro-4-(Trifluoromethyl) Benzene and Petroleum Distillates. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes nose, throat, eye and skin irritation. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.** First aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

MAX VOC 50 g/L

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 888-855-1774 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061
888-855-1774 rustoleum.com

Made in USA | Hecho en E.U.A.
©2019 Rust-Oleum Corporation 353310 0519

KEEP FROM FREEZING

MH READY PATCH®

PROFESSIONAL FORMULA
SPACKLING AND
PATCHING COMPOUND

INTERIOR/EXTERIOR

- SHRINK & CRACK RESISTANT
- EASY TO SAND • EASY TO APPLY
- OUTPERFORMS VINYL SPACKLING COMPOUNDS
- LOW VOC

WARNING! Combustible liquid and vapor.
ONE QUART — (32 oz.) (946.35mL)

Product No.
352305

Ready Patch Is America's
Finest Professional Quality
Spackling Paste.

FILLS AND SMOOTHS plaster and drywall splits, cracks and holes – nail holes and splits in woodwork – cracks and seams around window frames and moldings.

READY PATCH STICKS FIRMLY to all clean, dry surfaces – plaster, wood, drywall, wallboard, brick, concrete, stucco, paint.

READY PATCH IS EASY TO WORK WITH

- No pre-mixing, no need to add water, no need to water-dip finishing blade to smooth
- Does not shrink, crack, crater, or sag on normal applications
- Sands easily to a smooth, rock-hard finish ready for priming or painting
- Dries quickly on both interior and exterior surfaces.

DIRECTIONS:

1. Remove grease, wax, dust, loose paint, loose particles, etc.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead.


2. Prime nail and screw-heads, which may rust, with a ZINSSER® stain-blocking primer/sealer.

3. Pack tightly with putty knife, trowel, or fingers. Deep cracks or large holes should be filled with two (2) applications.

4. Smooth and allow to dry. May be primed or painted when dry to touch (normally less than 30 minutes).

5. For best professional results, and to prevent "Flashing", full surface prime with ZINSSER® primer prior to finish coat. Spot priming (patched area only), or no priming at all, can result in "Flashing" or reverse "Flashing" (shiners).

6. Close container tightly after each use. Keep from freezing. Clean-up with soap and water.



353310