

Safety Data Sheet

Printing date 03/28/2017

Revised On 03/28/2017

1 Identification of the substance and manufacturer

Trade name: 0316-GA RUBBER FLEXX SPRAY
Product code: GG00200146
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: Gardner-Gibson, Inc.
 P.O. Box 5449
 Tampa, FL 33675
 phone: 813-248-2101
 www.gardner-gibson.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification**Classification of the substance or mixture**

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Skin Irrit. 2 H315 Causes skin irritation.
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.
 STOT SE 3 H335 May cause respiratory irritation.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word**Hazard statements**

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.
 Suspected of damaging fertility or the unborn child.
 May cause respiratory irritation.
 May cause damage to organs through prolonged or repeated exposure.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Do not handle until all safety precautions have been read and understood.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER/doctor if you feel unwell.
 If skin irritation occurs: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of water.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Protect from sunlight. Store in a well-ventilated place.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Precautionary statements**3 Composition/information on ingredients****Chemical characterization: Mixtures**

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

1317-65-3	Calcium Carbonate	25.2%
8052-42-4	Asphalt	18.9%
108-88-3	Toluene	16.2%
64742-89-8	VM&P Naphtha	13.5%
1332-58-7	Aluminum Silicate	8.1%
14807-96-6	Talc	8.1%
74-98-6	propane	6.3%
106-97-8	n-butane	3.7%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. on page 2)

Safety Data Sheet

Printing date 03/28/2017

Revised On 03/28/2017

Trade name: 0316-GA RUBBER FLEXX SPRAY

Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****8052-42-4 Asphalt**

REL (USA) Ceiling limit value: 5* mg/m³
 *15-min; See Pocket Guide App. A
 TLV (USA) Long-term value: 0.5* mg/m³
 *inh. fraction; as benzene-soluble aerosol; BEIp

1332-58-7 Aluminum Silicate

PEL (USA) Long-term value: 15* 5** mg/m³
 *total dust **respirable fraction
 REL (USA) Long-term value: 10* 5** mg/m³
 *total dust **respirable fraction
 TLV (USA) Long-term value: 2* mg/m³
 E; as respirable fraction

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm
 REL (USA) Long-term value: 1800 mg/m³, 1000 ppm
 TLV (USA) refer to Appendix F in TLVs&BEIs book; NIC-EX

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm
 TLV (USA) Short-term value: (2370) mg/m³, (1000) ppm
 NIC-EX

Ingredients with biological limit values:**8052-42-4 Asphalt**

BEI (USA) -
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

Hygienic protection: Immediately remove all soiled and contaminated clothing.
 Wash hands after use.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
 Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves.
 Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.
pH-value: Not determined.
Melting point/Melting range: Undetermined.
Boiling point: -44 °C (-47 °F)
Flash point: -19 °C (-2 °F)
Flammability (solid, gas): Extremely flammable.
Decomposition temperature: Not determined.
Auto igniting: Product is not self-igniting.
Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: Not determined.

(Contd. on page 3)

Safety Data Sheet

Printing date 03/28/2017

Revised On 03/28/2017

Trade name: 0316-GA RUBBER FLEXX SPRAY

(Contd. of page 2)

Upper Explosion Limit:	Not determined.
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density:	Not determined.
Evaporation rate:	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
Solids content:	64.8 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative LC50/4 h 658 mg/l (rat)

Information on toxicological effects:	No data available.
Skin effects:	Irritant to skin and mucous membranes.
Eye effects:	No irritating effect.
Sensitization:	No sensitizing effects known.

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Other adverse effects:	No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number	UN1950
DOT	N/A
DOT	Consumer Commodity
ADR	Aerosols, flammable
Transport hazard class(es):	1950 Aerosols
Class	2.1
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

ADR	
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

IMDG

Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

Packaging Group:	--
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

(Contd. on page 4)

Safety Data Sheet

Printing date 03/28/2017

Revised On 03/28/2017

Trade name: 0316-GA RUBBER FLEXX SPRAY

(Contd. of page 3)

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

Toxic Substances Control Act (TSCA):

All ingredients for this product are found on the inventory list of substances.

Consumer Product Safety Commission (CPSC):

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

CANADIAN ENVIRONMENTAL PROTECTION ACT:**WHMIS Symbols for Canada:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

A - Compressed gas

D2A - Very toxic material causing other toxic effects

**EPA:**

None of the ingredients is listed.

16 Other information**Contact:**

Regulatory Affairs

Date of preparation / last revision

03/28/2017 / -