



## INSTALLATION GUIDE

The following are suggested instructions for installing tile. Please note, each installation will vary depending on the materials being used, desired design and other factors.

1. Measure coverage area. Add at least 10% extra material to account for breakage or miscuts during installation or to replace any tile element in the future.
2. Blending tiles from several boxes during installation is recommended to create a uniform look.
3. Plan the placement of the tiles on your wall/floor prior to installation. If you need to cut a mosaic sheet, cut from the back using a utility knife between tiles along the grout joints. Should you need to cut across tiles in a fashion that is not possible with a utility knife, use a wet saw with a diamond blade to cut through the tiles.
4. Apply setting materials using the notched side of a notched trowel. Using the flat side of the trowel, smooth out all ridges to achieve consistent even coverage.
5. Apply mosaic sheets (mesh side down). Pressing firmly into freshly laid setting material. Using a rubber grout float gently press the tile into the adhesive to ensure complete contact. For best results mix and match from assorted boxes to achieve consistent variation.
6. Natural stone should be sealed prior to grouting. A premium penetrating sealer is recommended for a natural look. Please refer to sealer manufacturer's recommendations for application instructions.
7. After 24 hours, mix and apply nonsanded tile grout. Please refer to grout manufacturer's recommendations for application instructions.
8. Clean all excess grout immediately with a damp sponge. After 12 hours polish off any remaining haze with a dry, clean, soft cloth.

Recommended tools and materials:

- |   |                                       |
|---|---------------------------------------|
| <input type="checkbox"/> White latex, modified thinset    | <input type="checkbox"/> Tape measure |
| <input type="checkbox"/> Rubber grout float. Stone sealer | <input type="checkbox"/> Sponge       |
| <input type="checkbox"/> Nonsanded tile grout             | <input type="checkbox"/> Bucket       |
| <input type="checkbox"/> Notched trowel                   | <input type="checkbox"/> Tile spacers |
| <input type="checkbox"/> Wet saw with diamond blade       | <input type="checkbox"/> Level        |
| <input type="checkbox"/> Utility knife                    |                                       |

### ATTENTION

Do not dry cut using motorized equipment due to the potential for exposure to harmful silica dust. Use a wet saw or a score and snap tool when cutting is necessary during the installation process.



 620 Parkridge Ave  
Norco, CA 92860



 [www.JeffreyCourtHD.com](http://www.JeffreyCourtHD.com)  
 @JeffreyCourtHD

