Thank you for your purchase!

We pride ourselves on creating the best screen doors in America and greatly appreciate being a part of your home. If we can answer any questions or if you experience any issues, please contact us directly at ScreenTight.com. We hope you enjoy your new door!

Quick & Easy Installation

Gather Tools & Supplies

You will need measuring tape, a drill with a Phillips Head bit. Shims, wedges or the like to assist with holding the door in place during installation. You may also need a circular saw if you need to trim your door.

Determine the Size of Your Door Opening

Measure the width and height of your existing opening inside the door frame to determine if you need to trim your door. Allow a 1/8" space on each side around the door.

Trim Your Door As Needed

You can trim your door up to 3/8" from each side and top and 1" off the bottom. A standard circular saw will do the job. If you trim more than these amounts you will compromise the integrity of the door an void the warranty.

Install Hardware

This door is compatible with most types of hardware. If you have purchased Screen Tight hardware separately, please watch our installation video to ensure proper mounting of the hinges.

ScreenTight.com/Hardware

FAST FACTS

This door is **American made** from weather-resistant PVC.

The exterior grade vinyl includes UV inhibitors that resist fading, yellowing or other damage from the sun's rays.

PVC materials are paintable. However, the nature and application of this product is not favorable for painting and will adversely effect its weather resistance and void the warranty.



NEED A SCREEN PORCH TO GO WITH THAT DOOR?

TRY ONE OF OUR INNOVATIVE PORCH SCREENING SYSTEMS



MeshGuard
Guardrail infill.
No more pickets!

Screen Wall
Extremely tough
PVC components.

Screen Block
Simple screen porch
winterization.

FASTtrack
Versatile
mating channels

MINItrack

Low-profile
2-part system.