

Retain this label in place • Do not paint over label

CARE AND MAINTENANCE

Painting: Bilco Basement doors are supplied in either a red oxide primer or powder coat paint finish. If your door has a powder coat finish, no additional finishing is required.


IMPORTANT: Doors supplied with a primer finish must be painted within forty-five (45) days of installation. Bilco recommends using Sherwin-Williams All Surface Enamel A11 Series in a white or light color. For best results, carefully follow the directions on the Sherwin Williams label and apply one thin coat of paint followed by a second coat on both the exterior and interior primered steel surfaces of the door. Two quarts should be sufficient to coat the entire door.

Finish maintenance: If the door becomes scratched during the construction process or worn by long exposure, clean damaged areas as required with steel wool, sandpaper, or a wire brush. Doors supplied with a primer finish: Apply a coat of alkyd primer containing zinc oxide, iron oxide or similar rust inhibiting pigments before applying finish coat. Doors supplied with a pow-

CAUTION

When the doors are open for access, the area should be personally guarded to prevent anyone from falling down the stairs. Doors should be closed and locked when not in use. **KEEP OFF DOORS TO AVOID INJURY** Surface may be slippery. In extreme conditions steel in the summer sun can become hot and cause injury.

KEEP OFF DOORS



Keyed Basement Door Lock Kit Available from Bilco

Easy to install, lock kit provides the convenience of keyed exterior access. Purchase on-line at www.bilco.com