

Specifications:

Model(s):	Shutter Size	Approx. Area Coverage	CFM (airflow)	Spd	Sones @ 5ft	Cord Plug End	Cord Length	Rough-In Height	Rough-In Width
**8SFV-H	8"	150 sq/ft	300	1	5.4	115 volt	9 Ft	8.5"	8.5"
**10SFV-H	10"	200 sq/ft	650	1	6.2	115 volt	9 Ft	10.5"	10.5"
12SF3-H	12"	300 sq/ft	1100	3	6	115 volt	9 Ft	12.5"	12.5"
**12SFV-H	12"	250 sq/ft	900	1	6	115 volt	9 Ft	12.5"	12.5"
**14SFV-H	14"	325 sq/ft	1350	1	7.3	115 volt	9 Ft	14.5"	14.5"
16SF3-H	16"	325 sq/ft	1325	3	6.3	115 volt	9 Ft	16.5"	16.5"
**16SFV-H	16"	350 sq/ft	1400	1	6.4	115 volt	9 Ft	16.5"	16.5"
**18SFV-H	18"	400 sq/ft	1785	1	7.4	115 volt	9 Ft	18.5"	18.5"
**18SF-H	18"	800 sq/ft	3130	1	7.3	115 volt	9 Ft	18.5"	18.5"
20SF3-H	20"	775 sq/ft	2860	3	6.8	115 volt	9 Ft	20.5"	20.5"
**20SFV-H	20"	900 sq/ft	3340	1	7	115 volt	9 Ft	20.5"	20.5"
24SF2-H	24"	1300 sq/ft	4450	2	7.4	115 volt	9 Ft	24.5"	24.5"
**24SFV-H	24"	1300 sq/ft	4450	1	7.4	115 volt	9 Ft	24.5"	24.5"
30SF8N240	30"	1750 sq/ft	5895	1	7	N/A	No Cord	30.5"	30.5"
36SF8N370	36"	2200 sq/ft	8860	1	8.3	N/A	No Cord	36.5"	36.5"

Models run at full speed only when plugged in. If variable speed is desired, **controls are sold separately.

Models 30SF8N240 & 36SF8N370 are single speed only and will run on high speed only when plugged in.

Models 12SF3-H, 16SF3-H, 20SF3-H, 24SF2-H feature pull chain speed selector build in to fan. See table above for number of speeds available with each unit.