



ALL WEATHER PROTECTION

TOUGH HYDROPHOBIC SURFACE

- Repels water absorption for 100% weatherproof seal
- Resists dirt & dust build up

LONG LASTING DURABILITY

- Powerful UV protection prevents fading & yellowing
- · No cracking, chalking or crumbling
- Lifetime mold, mildew & algae resistance
- Strong & durable multi-surface adhesion
- Permanently flexible; meets ASTM Spec C920, Class 35*

BETTER PRODUCTIVITY

- 1 hour rain†& paint ready to save time
- Easy gunning for less fatigue
- . Smooth tooling for better finish
- Easy water clean-up & low odor
- * Clear meets ASTM Spec C920, Class 25 † Clear is rain ready in 2 hours



ULTRA TOUGH. ULTRA EASY.
THE ULTRA DIFFERENCE.

POWERFUL UV PROTECTION RESISTS FADING & CRACKING

- Powered by WEATHER MAX[™] Technology for exceptional UV protection against color fading, yellowing, discoloration and damage from harsh weather.
- No cracking, crumbling or chalking.
- Sealant surface remains smooth and flexible without any surface degradation, bubbling, separation, hardening or softening.



Competitive Sealant



1 HOUR RAIN'& PAINT READY FOR BETTER PRODUCTIVITY

NO WASH OUT OR RAIN MARKS

- Early 1 hour rain resistance without the sealant washing out or getting damaged with permanent rain marks.
- Eliminates the worry of a ruined caulk job and having to reapply.
- Ideal for areas with extended rainy seasons.

EXCEPTIONAL PAINT PROPERTIES

- Paint ready in just 1 hour so you can finish the job faster.
- Sealant is firm and smooth at one hour with no brush drag or marks.
- Excellent paint coverage with latex and oil-based paints and all sheens: flat, satin & semi-gloss.
- No paint glossing ("shiners"), dulling or paint film cracking.
- * Clear is rain ready in 2 hours





TOUGH HYDROPHOBIC SURFACE RESISTS DIRT BUILD UP & WATER ABSORPTION

- The technologically advanced DAP®DYNAFLEX ULTRA™ formula forms a tough sealant surface that resists dirt and dust pick up so the sealant stays looking clean and new.
- The tough hydrophobic surface also prevents water absorption for an ultra waterproof seal that won't swell, blister or break down.



LIFETME MOLD, MILDEW & ALGAE RESISTANCE GUARANTEE

- Once cured, **DAP®DYNAFLEX ULTRA™** resists the growth of mold, mildew and algae for the life of the sealant.
- Perfect for areas that don't get much sunlight or rainy, damp climates.



SUPERIOR FLEXIBILITY & STRONG **MULTI-MATERIAL ADHESION**

- Stays permanently flexible to endure expansion and contraction caused by sun, heat, cold, wind and rain for long lasting, all weather protection.
- Provides a strong, durable seal that won't crack or lose adhesion.
- Meets ASTM Spec C920, Class 35.



* Clear meets ASTM Spec C920, Class 25

COLOR MATCHED TO TOP SIDING & TRIM COLORS

COLOR NAME:





WT093







Dark Bronze RR104



▶ Use the DAP® Spec Line Color Match program to find color matches with other manufacturers. Go to dapspecline.com/dapmatch, and select the DAP color number.

PRODUCT SPECIFICATIONS

Color	Size	Case Pack	Case Code	Product Code	GTIN 14	Case Weight (lbs.)	Case Dimensions (LxWxH)	Case Volume (cu. ft.)	Cases Per Pallet
WHITE	10.1 FL. OZ.	12	18211	0 70798 18211 0	100 70798 18211 7	12	8" x 6" x 12"	0.33	108
BEIGE	10.1 FL. OZ.	12	18213	0 70798 18213 4	100 70798 18213 1	13	8" x 6" x 12"	0.33	108
CLAY	10.1 FL. OZ.	12	18214	0 70798 18214 1	100 70798 18214 8	13	8" x 6" x 12"	0.33	108
IRON GRAY	10.1 FL. OZ.	12	18215	0 70798 18215 8	100 70798 18215 5	13	8" x 6" x 12"	0.33	108
DARK BRONZE	10.1 FL. 0Z.	12	18216	0 70798 18216 5	100 70798 18216 2	13	8" x 6" x 12"	0.33	108
CLEAR	10.1 FL. 0Z.	12	18212	0 70798 18212 7	100 70798 18212 4	10	8" x 6" x 12"	0.33	108