



# PREMIUM PAINTERS LATEX TECHNICAL DATA SHEET

WHITE - 99PAIT3027

## PRODUCT DESCRIPTION

GREAT STUFF™ Premium Painters Latex High Performance Siliconized Acrylic Caulk is single-component, acrylic dispersion based sealant which is reinforced with silicone emulsion. It is paintable and can be used for all porous surfaces. Water, wind and moisture resistant on aluminum, wood and PVC frames and windows.

## PROPERTIES

- Water, wind, and moisture resistant when cured
- Non sag
- Resistant to UV
- Good adhesion, bonds to most common building materials
- Easy to use, water clean up
- Paintable
- Dry to the touch in less than 1 hour (Excludes Clear)
- Forms permanently water repellent layer after curing
- Remains elastic and flexible, after curing
- Does not stain or damage the bonding surface
- It has bright, glossy appearance
- Lifetime Product Warranty

## TECHNICAL INFORMATION

Chemical Base:

Acrylic

Specific gravity:

1.52 ± 0.03 g/cm<sup>3</sup>

Tack free time (77°F/25°C and 50% R.H.):

15 - 45 Minutes



Paintable



18 Month Shelf Life



UV Resistant



For Interior & Exterior Use

NATIONAL ADHESIVE INC.

8280 WILLOW OAKS CORPORATE DRIVE, SUITE 600, FAIRFAX, VA 22031, U.S.A

+1 (855) 674-4583 | [greatstuff@nationaladhesive.com](mailto:greatstuff@nationaladhesive.com) | [www.nationaladhesive.com](http://www.nationaladhesive.com)



## CAULKS & SEALANTS

GREAT STUFF™ is a trademark or registered trademark of affiliates of DuPont de Nemours, Inc. used under license by National Adhesive Inc.



For more information scan the QR Code  
[www.greatstuff.com](http://www.greatstuff.com)

## PREMIUM PAINTERS LATEX

# TECHNICAL DATA SHEET

|                                             |               |
|---------------------------------------------|---------------|
| Cure Rate (1 day) (77°F/25°C and 50% R.H.): | 0.08 inch/2mm |
| Tensile Strength at Break:                  | ≥ 0.1 Mpa     |
| Elongation at Break:                        | ≥ 200 %       |
| Modulus 100 % Elongation:                   | > 0.2 Mpa     |

### APPLICATION DETAILS

|                          |                               |
|--------------------------|-------------------------------|
| Application Temperature: | 41°F to 95°F (5°C to 35°C)    |
| Temperature Resistance:  | 14°F to 176°F (-10°C to 80°C) |

- For best results, the surface must be clean, dry and free of dust, oil and grease, to ensure a clean and strong adherence between the sealant and the surface.
- Cut off the cartridge tip, screw on the removable nozzle and cut tip to your desired bead size.
- Insert cartridge into caulking dispenser.
- Hold at a 45° angle and apply ahead of nozzle to achieve a smooth seal.
- Sealant normally dries to touch in 45 minutes and cures & bonds on average 24 hours.
- Uncured product can be cleaned with water.
- Once cured, the product can be removed mechanically.
- Not suitable for joints exposed to continuous water immersion or joints which are totally closed.
- Do not use on oil leaking materials such as bituminous substrates, natural and synthetic rubber.

### PACKAGING

Cartridge

### COLOR

White

### SHELF LIFE

- Store the product in a cool and dry place.
- Do not store in extreme cold, direct sunlight, and temperatures above 122°F/50°C.

NATIONAL ADHESIVE INC.

8280 WILLOW OAKS CORPORATE DRIVE, SUITE 600, FAIRFAX, VA 22031, U.S.A  
+1 (855) 674-4583 | [greatstuff@nationaladhesive.com](mailto:greatstuff@nationaladhesive.com) | [www.nationaladhesive.com](http://www.nationaladhesive.com)





GREAT STUFF™ is a trademark or registered trademark of affiliates of DuPont de Nemours, Inc. used under license by National Adhesive Inc.



For more information scan the QR Code  
[www.greatstuff.com](http://www.greatstuff.com)

## PREMIUM PAINTERS LATEX

# TECHNICAL DATA SHEET

### CAUTION

Avoid contact with eyes and skin. Do not breathe vapors. Do not take internally. In case of eye contact, flush thoroughly with water. In case of skin contact, flush thoroughly with water. If breathed in, move person into fresh air. If swallowed, do not induce vomiting. Call a physician immediately.

### HEALTH AND SAFETY

For more information, please refer to the most recent Safety Data Sheet found at [www.greatstuff.com](http://www.greatstuff.com).

NATIONAL ADHESIVE INC.

8280 WILLOW OAKS CORPORATE DRIVE, SUITE 600, FAIRFAX, VA 22031, U.S.A  
+1 (855) 674-4583 | [greatstuff@nationaladhesive.com](mailto:greatstuff@nationaladhesive.com) | [www.nationaladhesive.com](http://www.nationaladhesive.com)

