

Instructions for Use

215 Brushing Paint

General application instructions

Undercoat: As DayGlo 215 Brushing Paints are semi-transparent, they're brightest when applied over a clean white surface. White semi-gloss enamels, white enamel undercoats, primer-sealers and bulletin block-out whites are all ideal for this.

Over old finishes, apply a white undercoat or primer that offers good adhesion to both the old finish and new DayGlo paint. For best performance, remove old finishes and start with a freshly primed surface.

DayGlo 215 Brushing Paint Color Coat:

1. Mix well before using.
2. Apply one heavy coat of DayGlo 215 Brushing Paint with a soft varnish brush using short strokes. Cover completely and smooth out as you go to produce a uniform deep layer (approximately 1.5 mils thick dry). Keep in mind that thin spots or streaks will fade prematurely. Allow to set-up or "top dry" at least two hours (@ 70°F).
3. Apply the second coat the same way. Allow 24 hours to dry before applying DayGlo Filteray Type D overcoat. NOTE: Ambient temperature and relative humidity will affect the drying time. Applying the Filteray Type D before the 215 Brushing Paint is fully cured can impact performance.
4. For sign applications, the DayGlo paint can simply be roughed in, slightly overlapping the copy line, but the copy line will not be hidden as DayGlo 215 is semi-transparent. Do not try to work the paint exactly to a line. An opaque background should be used to cut in accurately to the copy line for sharp detail after the DayGlo has top dried.

Filteray Type D Overcoat:

1. Apply one heavy coat of DayGlo Filteray Type D overcoat (1.5 mil. dry). This product works best when applied by brush.

Available Colors

Product Code	Color
215-11	Aurora Pink
215-13	Rocket Red
215-14	Fire Orange
215-15	Blaze Orange
215-16	Arc Yellow
215-17	Saturn Yellow
215-18	Signal Green
215-19	Horizon Blue
215-46	Lightning Yellow
215-08A	Filteray® D Top Coat

Packaging:

1 Quart Cans
1 Gallon Cans

Storage & shelf life:

24 months when kept in closed original packaging in a dry place at ambient temperature.

Safety & regulatory:

Safety Data Sheet available on request.

2. Allow surface to dry for 24 hours before putting into service. Do not wax for approximately two weeks.
3. Clean brushes should always be used.

Coverage:

As a guideline for ordering paint, coverage should be estimated at 250 square feet per gallon. As always, 10-25% extra should be ordered to cover waste, spillage and variations in applied paint film thickness.