



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 3/19/15

DAP® KWIK SEAL ULTRA™ Premium Siliconized Sealant – White & Biscuit

- Easy clean
- Repels water, stains & dirt
- Lifetime mold & mildew guarantee
- Sealant stays looking fresh & new
- 100% waterproof
- Crack & stain proof
- Safe for granite & marble
- Water ready in 4 hours
- Easy water clean up & low odor
- Interior

Packaging: 5.5 fluid ounces (162 mL) and 10.1 fluid ounces (300 mL)
Color: White, Biscuit
UPC Numbers:

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on “Ask the Expert”
Order Information: 800-327-3339
Fax Number: 410-558-1068
Also, visit the DAP website at www.dap.com

Product Description:

DAP® KWIK SEAL ULTRA™ is a high performance siliconized kitchen and bath sealant that repels water, stains and dirt. It has a lifetime mold and mildew guarantee so the sealant stays looking fresh and new. **KWIK SEAL ULTRA™** is 100% waterproof and crack proof. It can be exposed to water in as little as 4 hours after application without washing out. It is safe for granite and marble, cleans up easily with water and is low in odor. Interior use.

Suggested Uses:

Ideal for sealing:

- *Tubs*
- *Sinks*
- *Backsplashes*
- *Showers*
- *Countertops*
- *Toilets*
- *Fixtures*
- *Loose Tile Repair*
- *Cracks and Joints*

Adheres To:

- Ceramic/Porcelain
- Glass
- Most Plastics
- Granite, Cultured Marble & Natural Stone
- Wood
- Metal
- Drywall
- Fiberglass
- Painted Surfaces

Performance Characteristics:

- Repels water, stains and dirt
- Lifetime mold & mildew guarantee
- Sealant stays looking fresh & new
- Water ready in 4 hours
- 100% waterproof
- Crack & stain proof
- Safe for granite & marble
- Easy water clean up and low odor
- Not paintable

For Best Results:

- Apply in temperatures above 40°F.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint size should not exceed 3/8" wide by 3/8" deep. For joints deeper than 3/8", use backer rod.
- Store product away from extreme heat or cold.

Surface Preparation & Application:

1. Surface must be clean, dry and free of all old sealant, dirt, dust, debris and grease. Rubbing alcohol is recommended for removing soap film and soil.
2. Remove cap (from tube). Cut nozzle at a 45° angle to desired bead size. If using the cartridge, puncture inner foil seal and load into caulk gun.
3. Fill gap with sealant, pushing sealant ahead of nozzle.
4. For a neat finish, smooth bead of sealant with a finishing tool.
5. Allow sealant to dry for at least 4 hours before exposing to water. Sealant reaches full performance in 24 hours.
6. Clean up excess uncured sealant with damp sponge before it skins over. Scrape or cut away excess cured sealant.
7. Regular cleaning of surrounding areas is suggested.
8. Reseal tube/cartridge for future use.

Physical & Chemical Characteristics:

Tooling Time:	3-5 minutes
Tack Free Time:	8-10 minutes
Paintable:	No
Odor:	Very Mild
Consistency:	Smooth and Creamy
Vehicle:	Acrylic Polymer
Volatile:	Water
Flash Point:	None
Filler:	Titanium Oxide
Density:	1.04
Solids:	58.2% by weight
Weight per Gallon:	8.70 lbs/gallon

Temperature Service Range: 0° F to 150°F
Temperature Application Range: 40°F to 100°F
Freeze Thaw Stability: Passes 5 Cycles
Applications: Interior
Shelf Life: 12 Months
Coverage: 5.5 fluid ounces: 30 linear feet at a 3/16" diameter bead or two average size bathtubs.
10.1 fluid ounces: 56 linear feet or four average size bathtubs.
SDS No: 00079957001

Clean Up & Storage:

Remove excess uncured sealant with a damp cloth/sponge before it dries. After sealant has dried, excess sealant must be cut or scraped away. Store in a cool, dry place away from extreme heat or cold.

Safety:

For additional safety information, see product label or Safety Data Sheet. You can obtain an SDS sheet by going to www.dap.com and clicking on the SDS link next to the product or by calling 1-888-DAP-TIPS.

Lifetime Mold & Mildew Guarantee:

DAP guarantees that the product when properly applied will remain free of mold and mildew during the lifetime of your home. If mold and/or mildew appear when used as directed, provide evidence of mold and mildew and sales receipt to DAP Products Inc., 2400 Boston Street, Suite 200, Baltimore, MD 21224 for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.