

Non-Metallic Liquid Tight **Conduit Connectors**

FEATURES & BENEFITS

- No threading of conduit or tubing required
- SUPERIOR LIQUID TIGHT SEAL AND PULL OUT STRENGTH
- SUITABLE FOR INDOOR OR OUTDOOR USE
- INCLUDED STEEL LOCK NUT AND RUBBER SEAL GASKET
- PROTECTS FROM RAIN, LIQUID AND OILS
- SIMPLE, QUICK AND EASY ASSEMBLY



APPLICATIONS

- HVAC EQUIPMENT
- MACHINE TOOLS
- MARINE EQUIPMENT
- MOTORS & CONTROLS
- PUMPS
- REFRIGERATION EQUIPMENT
- ASSEMBLIES
- WIRE HOOK-UP





Non-Metallic Liquid Tight Conduit Connectors

FEATURES & BENEFITS

- ALL NYLON CONSTRUCTION RESISTS SALT, WATER, WEAK ACIDS, GASOLINE, ALCOHOL, OIL, GREASE & COMMON SOLVENTS
- SIMPLE, EASY INSTALLATION.
 NO DISASSEMBLY REQUIRED.
- No threading of the conduit or tubing required. Reduces the possibility of cutting the conduit & creating leak paths.
- REUSABLE, CONDUIT WILL NOT WIND TIGHT ONTO THE CONNECTOR DURING ASSEMBLY & CAN BE EASILY REMOVED BY PULLING WHILE TURNING IN A CLOCKWISE DIRECTION
- Molded of type Nylon 6. Flammability classification 94V-2; Temperature index 125° C
- SMOOTH INTERNAL SURFACES PERMITS EASY SMOOTH WIRE INSTALLATION AROUND CORNER ANGLES
- O-RING AND STEEL LOCKNUT INCLUDED



NM STRAIGHT CONNECTORS

Stock	Trade	Unit Carton	Master Carton	WT/100
Number	Size	Quantity	Quantity	
58133657	1/2	20	100	7.08
58133757	3/4	20	100	10.10
58308157	1	10	60	14.52
58616257	1.25	5	20	20.60
58616357	1.50	5	20	29.30
58616457	2.00	1	4	45.40
*58617057 * 5 Piece Contractor Pack	1/2	5	50	7.08

NM 90° CONNECTORS

Stock Number	Trade Size	Unit Carton Quantity	Master Carton Quantity	WT/100
58133857	1/2	20	100	8.29
58133957	3/4	20	100	11.92
58308257	1	10	60	22.00
58616557	1.25	5	20	33.40
58616657	1.50	5	20	45.20
58616757	2.00	1	4	68.70
*58617157 * 5 Piece Contractor Pack	1/2	5	50	8.29

NM Coupling Connectors

Stock Number	Trade Size	Unit Carton Quantity	Master Carton Quantity	WT/100
58616857	1/2	20	100	6.50
58616957	3/4	20	100	6.75

