



# Tremco Sealants - Basic Uses and Classifications

Description	ASTM C920	TYPE- Single/Multi-component	GRADE- Pourable or NonSag	CLASS- Cyclic Movement +/-	USE: NT, M, A, O	USE: T, I, G	ASTM C834	ASTM C1248	ASTM C1382	ASTM E84	Federal Spec TT-S-001543A	Federal Spec TT-S-00230C	Federal Spec TT-S-00227E	TYPE I Self-Leveling	TYPE II Non-Sag	CLASS A 50%max, B 25%max	MCG-1-25-B-N	MCG-2-40-B-N	CAN/CGSD-19.13-M87	CAN/CGSD 19GP16a	CAN/CGSD 19GP17M	AAMA VCL Listed	COLA Approval, City of LA	ULC Registered	EIMA Test 300.01	USDA	CFIA Approved	SWRI Validated Product	
<b>Vulkem 116 ▲</b> Polyurethane, for vertical/horizontal & traffic /non-traffic	●	S	NS	25	●	T,I					●		●	B								●				●	●		
<b>Vulkem Gold ◆</b> Polyurethane, for vertical/horizontal & traffic /non-traffic	●	S	NS	35	●	T,I					●		●	A												●	●		
<b>Vulkem 45 SSL ◆</b> Polyurethane, semi-self-leveling (up to 6% slope)	●	S	P	35	●	T,I					●	●				●													
<b>Vulkem 45 ▲</b> Polyurethane, self-leveling for traffic & non-traffic areas	●	S	P	25	●	T,I					●	●		A					●										
<b>Vulkem 921</b> Polyurethane, for vertical & non-traffic horizontal	●	S	NS	100/50	●						●		●	A		●	●					●				●	●		
<b>Dymonic FC</b> Polyurethane Hybrid, for vertical & non-traffic horizontal	●	S	NS	35	●		●				●		●	A								●				●	●		
<b>Dymonic</b> Polyurethane, for vertical & non-traffic horizontal	●	S	NS	25	●						●		●	A									●			●	●	●	
<b>Dymeric 240*</b> Epoxidized Polyurethane, vertical/horizontal & traffic/non-traffic	●	M	NS	50	●	T					●		●	A							●					●	●	●	
<b>Dymeric 240FC</b> Epoxidized Polyurethane fast cure, vertical /horizontal & traffic/non-traffic	●	M	NS	50	●	T,I					●		●	A							●					●	●		
<b>THC 900</b> Polyurethane, self-leveling for traffic & non-traffic areas	●	M	P	25	●	T					●	●		A												●	●		
<b>THC 901</b> Polyurethane, semi-self-leveling (up to 10% slope)	●	M	P	25	●	T					●	●		A												●	●		
<b>Spectrem 1</b> Silicone neutral cure, low modulus for vertical	●	S	NS	100/50	●	G	●	●	●		●		●	A		●	●									●	●	●	●
<b>Spectrem 2</b> Silicone neutral cure, for vertical, structural glazing	●	S	NS	50	●	G	●				●	●		A		●	●				●					●	●		
<b>Spectrem 3</b> Silicone neutral cure, low modulus for vertical	●	S	NS	50	●	G	●	●			●	●		A							●					●		●	
<b>Spectrem 4-TS</b> Silicone neutral cure, low modulus for vertical	●	M	NS	50	●	G	●	●			●	●		A							●					●		●	
<b>Spectrem 800</b> Silicone neutral cure, low modulus, vertical/horizontal & highway	●	S	NS	100/50	●	T					●	●		A							●								
<b>Spectrem 900 SL</b> Silicone neutral cure, low modulus for horizontal & highway	●	S	P	100/50	●	T					●	●		A							●								
<b>Simple Seal</b> Silicone, preformed low modulus tape for bridge joints																													
<b>Tremsil 200</b> Silicone acetoxy cure, for vertical	●	S	NS	25	●	G					●	●		A							●								
<b>Tremsil 600</b> Silicone neutral cure, for vertical	●	S	NS	25	●	G					●	●		A							●					●	●	●	
<b>Proglaze SSG</b> Silicone, neutral cure, high modulus, fast cure, structural	●	S	NS	25	NT,A,O	G					●	●		A							●								
<b>Proglaze II</b> Silicone, high modulus, 2-part structural glazing	●	M	NS	25	NT,A	G						●		A															
<b>Proglaze</b> Silicone acetoxy cure, for vertical	●	S	NS	25	NT,A,O	G					●	●		A															
<b>MONO 555</b> Acrylic Terpolymer, glazing/flaming sealant		S	NS	12.5							●		●																
<b>Tremflex 834</b> Acrylic Latex, ideal for interior applications		S	NS	12.5			●		●																				
<b>Butyl Sealant</b> Butyl, curtainwall, bedding joints, secondary glazing seals		S	NS	10																									
<b>Curtainwall Sealant</b> Butyl, non-curing/non-skinning for bedding joints		S	NS																										
<b>Acoustical Sealant</b> Butyl, non-curing/non-skinning, sound dampening sealant		S	NS																										
<b>Tremco 830</b> Thermoplastic, exterior grade, non-structural glazing/sliding		S	NS	12.5									●																
<b>illmod 600</b> Polyurethane, preformed, pre-compressed, impregnated foam tape																													

▲ These materials are also available with quick-cure catalyst. ◆ These materials can be water catalyzed. Please contact Technical Services for more info. \* Product not for use in the United States.

## Tremco Commercial Sealants & Waterproofing

3735 Green Road, Beachwood, OH 44122 // Phone: 216.292.5000 // 800.321.7906 • 220 Wicksteed Avenue, Toronto, ON M4H 1G7 // Phone: 416.421.3300 // 800.363.3213 • 1451 Jacobson Avenue, Ashland OH 44805 // Phone: 419.289.2050 // 800.321.6357

