

Additional Information

FINISH: Satin, for a non-skid finish, add pumice stone, sand or marble dust to paint as needed to achieve the desired appearance.

COVERAGE: Theoretical coverage at two mills dry is 400 square feet per gallon and recommended thickness of 4 mills dry would require 2 full coats. Expect 50% less coverage on bare, rough or sand basted surface.

RECOMMENDED REDUCER: Water. Thinning is not recommended.

CLEAN UP: Water & Soap.

SHELF LIFE: 12 months.

LIMITATIONS: Do not apply if material is below 50°F or above 95°F. Not for vinyl lined or metal pools.

MIXING: Mechanically mix well for 10 minutes, apply as it comes from the container.

Method of Application

Spray apply: Use a conventional air 50-70 PSI, tip size .55-.070.

Use an airless equipment, 2200-2500 PSI, tip size .019-.023.

Wait 3 days after final coat before filling pool with water.

Buy enough paint to complete the entire job and intermix all gallons of the same color to insure color uniformity. Stir gently. Apply liberally, in area patterns, no more than a 2ft. by 2ft.. Resists light foot traffic to apply more coats in 12 hours. Do not apply when surface or air temperature is below 50 °F or if rain is expected within 5 hours.

Apply product with sprayer. Apply generously and avoid excessive thickness or spreading too thinly.

Mixing and Thinning: Mix always thoroughly before application. Thinning is not recommended, if necessary use only 8oz. of water per gallon of this product.

LIMITED WARRANTY: The manufacturer's liability in connection with the sale of this product extends only to replacement price if it should fail to comply with quality standards or specifications.

CAUTION: Harmful if swallowed. Contains Acrylic Resin. In case of eye contact, flush thoroughly with water. Do not rub eyes. In case of skin contact, flush area immediately with clean water. If swallowed, do not induce vomiting. CONSULT A PHYSICIAN IMMEDIATELY. USE ONLY WITH ADEQUATE VENTILATION. Adequate ventilation required when sanding or abrading the dried film. Always use NIOSH/MSHA TC21C or equivalent. Goggles are recommended while handling the product. KEEP OUT OF REACH OF CHILDREN.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



Blanco Group

• **NORTH AMERICA** • 600 Mid Florida Drive Airport Industrial Park of Orlando, Florida 32824 • Tel. (407) 240-4000 Fax (407) 240-4046
• **CARIBBEAN & SOUTH AMERICA** • Urb. Aponte #5, San Lorenzo, Puerto Rico USA 00754 • Tel. (787) 736-4221 Fax (787) 736-5313
• **CENTRAL AMERICA** • Zona Industrial Bes, lote #4, El Coyol de Alajuela, Costa Rica • Tel. (506) 2438-2257 Fax (506) 2438-2162