



SAFETY DATA SHEET

1. Identification

Product identifier BEHR® PREMIUM Interior/Exterior Low-Lustre Enamel Porch & Patio Floor Paint - Deep Base

Other means of identification

Product code 6300

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process LLC
1801 E. St. Andrew Place
Santa Ana, CA 92705

Telephone 714-545-7101

Emergency telephone +1 760 476 3962
+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Hazards for the product as sold

Physical hazards Not classified.

Hazards for the product as sold

Health hazards Sensitization, skin Category 1

Hazards for the product as sold

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction.

Precautionary statement

Prevention Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.

Storage Not assigned.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

No additional hazards are known to be associated with the expected conditions of use at the time of publication. This document does not address hazards that may arise from uses not reasonably anticipated by the manufacturer.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
2-Butoxyethyl benzoate	5451-76-3	0.5 - 1.5
Ammonium hydroxide	1336-21-6	0.1 - 1
Zinc oxide	1314-13-2	0.1 - 1
2-Methyl-2H-isothiazol-3-one	2682-20-4	0 - 0.1



Chemical name	CAS number	%
5-Chloro-2-methyl-2H-isothiazol-3-one	26172-55-4	0 - 0.1

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Zinc oxide (CAS 1314-13-2)	PEL	5 mg/m3	Fume.
		5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Ammonium hydroxide (CAS 1336-21-6)	IDLH	300 ppm
Zinc oxide (CAS 1314-13-2)	IDLH	500 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Zinc oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.
	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.
		5 mg/m3	Dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Use of an impervious apron is recommended.

Respiratory protection

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Color	Opaque.
Odor	Slight.
Melting point/freezing point	Property has not been measured.
Boiling point or initial boiling point and boiling range	> 99 °F (> 37.22 °C)
Flammability	Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Flash point Property has not been measured.

Auto-ignition temperature Property has not been measured.

Decomposition temperature Property has not been measured.

pH 7 - 10

pH concentration Property has not been measured.

Kinematic viscosity Property has not been measured.

Kinematic viscosity temp Property has not been measured.

Solubility

Solubility (water) Soluble

**Partition coefficient
(n-octanol/water)** Property has not been measured.

Vapor pressure Property has not been measured.

Vapor pressure temp. Property has not been measured.

Density and/or relative density

Density 9.65 lb/gal

Relative density Property has not been measured.

**Relative density
temperature** Property has not been measured.

Vapor density Property has not been measured.

Vapor density temp. Property has not been measured.

Particle characteristics Not available.

Other information

Dynamic viscosity Property has not been measured.

Dynamic viscosity temp Property has not been measured.

Viscosity 50 - 140 ku

VOC 49 g/l (excluding water) (Coating)
17 g/l (including water) (Material)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

**Possibility of hazardous
reactions** No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition
products** No hazardous decomposition products are known.

11. Toxicological information**Information on likely routes of exposure**

Inhalation Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

**Symptoms related to the
physical, chemical and
toxicological characteristics** May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Product	Species	Test Results
BEHR® PREMIUM Interior/Exterior Low-Lustre Enamel Porch & Patio Floor Paint - Deep Base (CAS Mixture)		
<u>Acute</u>		
Oral		
ATEmix		31660 mg/kg bw
Components	Species	Test Results
Zinc oxide (CAS 1314-13-2)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	> 5.7 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
NTP Report on Carcinogens		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	
Further information	None known.	

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No data available.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to IMO instruments Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA) All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4)	1.0 % Subject to One-Time Reporting Requirements (Per Country)
5-Chloro-2-methyl-2H-isothiazol-3-one (CAS 26172-55-4)	1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethyl benzoate (CAS 5451-76-3)
Ammonium hydroxide (CAS 1336-21-6)
Zinc oxide (CAS 1314-13-2)

SARA 304 Emergency release notification

Ammonium hydroxide (CAS 1336-21-6) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Ammonium hydroxide	1336-21-6	100	500		

SARA 311/312 Hazardous chemical

Classified hazard categories Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-Butoxyethyl benzoate (CAS 5451-76-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ammonium hydroxide (CAS 1336-21-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Ammonium hydroxide (CAS 1336-21-6)
Zinc oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethyl benzoate (CAS 5451-76-3)
Ammonium hydroxide (CAS 1336-21-6)
Zinc oxide (CAS 1314-13-2)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethyl benzoate (CAS 5451-76-3)
Ammonium hydroxide (CAS 1336-21-6)

Zinc oxide (CAS 1314-13-2)

US. Rhode Island RTK

Ammonium hydroxide (CAS 1336-21-6)

Zinc oxide (CAS 1314-13-2)

16. Other information, including date of preparation or last revision

Issue date 13-December-2019

Revision date 20-January-2026

Version # 04

HMIS® ratings Health: 2
Flammability: 0
Physical hazard: 0

References IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer Behr Process LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.