SAFETY DATA SHEET



1. Identification

Product identifier BEHR® PREMIUM Solid Color Waterproofing Stain & Sealer - Tintable White

Other means of identification

Product number 5011

Recommended use **Architectural Coating**

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process Corp.

> 1801 E. St. Andrew Place Santa Ana. CA 92705

714-545-7101 **Telephone Emergency telephone** +1 760 476 3962

+1 866 519 4752

335213 Access code

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1

> Germ cell mutagenicity Category 1B Carcinogenicity Category 2 Reproductive toxicity Category 1B

Specific target organ toxicity, repeated Category 2 (kidney)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word

Hazard statement May cause an allergic skin reaction. May cause genetic defects. Suspected of causing cancer.

May damage fertility. May damage the unborn child. May cause damage to organs (kidney)

through prolonged or repeated exposure.

Precautionary statement

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

and understood. Do not breathe mist/vapors. Contaminated work clothing must not be allowed out

of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If Response

skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and

wash it before reuse.

Store locked up. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

BEHR® PREMIUM Solid Color Waterproofing Stain & Sealer - Tintable White SDS US 952479 Version #: 02 Revision date: 16-June-2020 Issue date: 26-December-2019

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	7 - 13
Ethylene glycol	107-21-1	0.5 - 1.5
Carbendazim	10605-21-7	0.1 - 1
Diphenyl ketone	119-61-9	0.1 - 1
Diuron	330-54-1	0.1 - 1
Hindered amine light stabilizer	41556-26-7	0.1 - 1
Hindered amine light stabilizer	82919-37-7	0.1 - 1

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Symptoms may be delayed.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

May cause an allergic skin reaction. Dermatitis. Rash. Edema. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Indication of immediate medical attention and special

General information

treatment needed

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s)

involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910	0.1000)		
Components	Туре	Value	Form
Diatomaceous earth (CAS 61790-53-2)	TWA	0.8 mg/m3	
		20 mppcf	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Cher	mical Hazards		
Components	Туре	Value	
Diatomaceous earth (CAS 61790-53-2)	TWA	6 mg/m3	
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
US. Workplace Environmental Ex	posure Level (WEEL) Guides		
Components	Type	Value	
Diphenyl ketone (CAS 119-61-9)	TWA	0.5 mg/m3	

SDS US

952479 Version #: 02 Revision date: 16-June-2020 Issue date: 26-December-2019 **Biological limit values**

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an

uncontrolled release, exposure levels are not known, or any other circumstances where

air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. White. Color Odor Slight.

Odor threshold Not available.

7 - 10

Not available. Melting point/freezing point Initial boiling point and boiling

range

> 99 °F (> 37.2 °C)

Flash point Not applicable **Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Not available. Vapor pressure Not available. Vapor density

Relative density 1.24

Solubility(ies)

Soluble. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature**

Viscosity 50 - 140 KU (25 °C)

Other information

Density 10.35 lbs/gal **Explosive properties** Not explosive. Oxidizing properties Not oxidizing.

VOC 28 g/l (including water) (Material) 69 g/l (excluding water) (Coating)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. **Eye contact** Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash. Edema. Prolonged exposure may cause

chronic effects.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results

Diphenyl ketone (CAS 119-61-9)

Acute Dermal

LD50 Rabbit 3535 mg/kg

Ethylene glycol (CAS 107-21-1)

Acute Dermal

LD50 Rabbit 9530 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute

Inhalation

LC50 Rat 3.43 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityMay cause genetic defects.CarcinogenicitySuspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Diatomaceous earth (CAS 61790-53-2) 3 Not classifiable as to carcinogenicity to humans.

Diphenyl ketone (CAS 119-61-9)

2B Possibly carcinogenic to humans.

Titanium dioxide (CAS 13463-67-7)

2B Possibly carcinogenic to humans.

BEHR® PREMIUM Solid Color Waterproofing Stain & Sealer - Tintable White
952479 Version #: 02 Revision date: 16-June-2020 Issue date: 26-December-2019

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity May damage fertility. May damage the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number UN3082

UN proper shipping name

Transport hazard class(es)

Environmentally hazardous substance, liquid, n.o.s. (Diuron, Hindered amine light stabilizer)

Class 9
Subsidiary risk Packing group III
Environmental hazards Yes
ERG Code 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diuron, Hindered amine

light stabilizer)

Transport hazard class(es)

Class 9
Subsidiary risk Packing group III
Environmental hazards

Marine pollutant Yes
S F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

BEHR® PREMIUM Solid Color Waterproofing Stain & Sealer - Tintable White

952479 Version #: 02 Revision date: 16-June-2020 Issue date: 26-December-2019

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations**

Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not applicable.

Diphenyl ketone (CAS 119-61-9) 0.1 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ammonium hydroxide (CAS 1336-21-6) Listed. Carbendazim (CAS 10605-21-7) Listed. Diuron (CAS 330-54-1) Listed. Ethylene glycol (CAS 107-21-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Respiratory or skin sensitization

categories Germ cell mutagenicity

Carcinogenicity Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Ethylene glycol 107-21-1 0.5 - 1.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylene glycol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Ammonium hydroxide (CAS 1336-21-6)

Diatomaceous earth (CAS 61790-53-2)

Diuron (CAS 330-54-1)

Ethylene glycol (CAS 107-21-1)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Ammonium hydroxide (CAS 1336-21-6)

Carbendazim (CAS 10605-21-7)

Diatomaceous earth (CAS 61790-53-2)

Diuron (CAS 330-54-1)

Ethylene glycol (CAS 107-21-1)

Mildewcide (CAS 55406-53-6)

Titanium dioxide (CAS 13463-67-7)

BEHR® PREMIUM Solid Color Waterproofing Stain & Sealer - Tintable White 952479 Version #: 02 Revision date: 16-June-2020 Issue date: 26-December-2019

US. Pennsylvania Worker and Community Right-to-Know Law

Ammonium hydroxide (CAS 1336-21-6) Diatomaceous earth (CAS 61790-53-2)

Diuron (CAS 330-54-1)

Ethylene glycol (CAS 107-21-1) Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Diatomaceous earth (CAS 61790-53-2)

Diuron (CAS 330-54-1) Ethylene glycol (CAS 107-21-1) Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date 26-December-2019 **Revision date** 16-June-2020

Version # 02

Further information HMIS® is a registered trade and service mark of the ACA.

G - Safety Glasses, Gloves, Vapor Respirator

HMIS® ratings Health: 2*

Flammability: 0 Physical hazard: 0 Personal protection: G

List of abbreviations DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PEL: Permissible Exposure Limit. STEL: Short-Term Exposure Limit. TWA: Time Weighted Average Value.

References HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer Behr Process Corp cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

 ${\tt BEHR} \hbox{@ PREMIUM Solid Color Waterproofing Stain \& Sealer - Tintable White} \\$

952479 Version #: 02 Revision date: 16-June-2020 Issue date: 26-December-2019