

Repairs cracks, gouges & holes Shrink & crack resistant Strong nail & screw anchoring Dries hard/Smooth finish

## INTERIOR/EXTERIOR

**WARNING!** 

Read bottom panel carefully for cautions.

**APPLICATION:** Surface should be clean & dry. De-gloss if necessary. Surface, wood filler & air temp. should be above 40°F. Press filler into place w/putty knife. Overfill slightly to allow for sanding. For large/deep holes, apply 1/8" layers, allowing each layer to dry before applying next layer.

**SANDING:** Allow to dry approx. 2 to 6 hours for shallow fills & 36 hours for deeper fills. Wood filler will change color to natural when surface is ready to be sanded. Sand w/medium sandpaper.

**FINISHING:** May be painted w/latex-based paint immediately after sanding, or after 12 hours if using an oil-based paint. If staining, test wood filler with desired stain on scrap wood before filling to ensure desired stain color. Exterior applications and applications subject to water exposure must be sealed with a waterproof coating.

**CLEAN-UP:** Wipe off excess with a damp cloth before material dries. Reseal tightly with lid after each use.

Contains: Crystalline silica. Dry sanding of this product may generate dust. Inhalation of dust may cause lung damage. May cause eye, skin, and respiratory tract irritation. Use only with adequate ventilation. IEnsure fresh air entry during application and drying. Avoid breathing I idust or vapors. Avoid contact with eyes and skin. Do not ingest. Wear gloves and safety glasses. FIRST AID: SKIN: Wash thoroughly. EYE: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get Imedical attention if complications arise from any exposure. For lemergencies, call your poison control center at 800-222-1222. See1 ISDS for additional information. For an SDS, contact your supplier or visit dap.com. KEEP OUT OF REACH OF CHILDREN.

▲ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov VOC Less Exempt Less Water 4 g/L (<1.5 wt/wt%)

LIMITED WARRANTY: If product fails to perform when used as directed, within one year from the date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.

QUESTIONS?/¿PREGUNTAS? Call/llame al 888-DAP-TIPS or visit/ o visite dap.com & click on/y pulse en "Ask the Expert."

Para obtener las instrucciones y garantiá en español, llame al 888-DAP-TIPS.

© DAP Products Inc., Baltimore, MD 21224. Made in the USA with U.S. and globally sourced materials. dap.com