

FOGATTI
WATER HEATING EXPERT

Versatile & Compatible

Rapid Temperature Recovery

No more waiting for consistent hot water, continuously provide endless hot water

Precise control farewell to cold water sandwich



Etank 25 / 40 / 80



Product Features

- **EXCELLENT PERFORMANCE**
Quick recovery rate of 10-20 minutes, adjustable temperature range between 90F and 140F.
- **WIDE ADAPTABILITY**
May be used alone for smaller water volumes or installed in-line with a central heater.
- **CONVENIENT**
Fast recovery rate, no need to wait long-term for hot water.
- **EASY INSTALLATION**
Can be wall or floor mounted, provide hot water right where you need it.
- **ENERGY SAVING**
Thick CFC-free foam insulation maximizes energy efficiency.

Technical Data

Model No.	FDES-ET25	FDES-ET40	FDES-ET80
Series No.	Etank 25	Etank 40	Etank 80
Capacity	US 2.5 gallons	US 4.0 gallons	US 8.0 gallons
Installation	Vertical wall mounted	Vertical wall mounted	Vertical wall mounted
Control Type	Manual control	Manual control	Manual control
Heating Element	310S	310S	310S
Rated Power	1440W	1440W	1440W
Rated Voltage	120V~	120V~	120V~
Rated Frequency	60Hz	60Hz	60Hz
Rated Current	12A	12A	12A
Thermostat	Capillary	Capillary	Capillary
Temperature Range	13-63°C / 55-145°F	13-63°C / 55-145°F	13-63°C / 55-145°F
Thermal Cut-off	Snap action	Snap action	Snap action
Wire Type	Plug in	Plug in	Hard wired
Water Connections	½" NPT	½" NPT	¾" NPT
Protection Against Humidity	IPX4	IPX4	IPX4
Working Pressure	150 PSI	150 PSI	150 PSI
Product Size (inch)	H 13.39" × W 13.39" × D 11.42"	H 14.96" × W 14.96" × D 12.8"	H 17.32" × W 17.32" × D 15.35"