

**SAFETY DATA SHEET**

**SECTION 1 : IDENTIFICATION**

Product Name: **BEHR PRO i300 Flat Interior Paint - White Base**  
 Product Code: PR310  
 SDS Manufacturer Number: PR310  
 Manufacturer Name: BEHR Process Corporation  
 Address: 1801 E. St. Andrew Place  
 Santa Ana, CA 92705  
 (714) 545-7101  
 (800) 854-0133 ext. 2  
 General Phone Number:  
 Customer Service Phone  
 Number:  
 Emergency Phone Number: For emergencies in the US & Canada, call Verisk 3E: (866) 519-4752  
 Access Code: 335213  
 SDS Creation Date: January 21, 2015  
 SDS Revision Date: October 20, 2017

**SECTION 2 : HAZARD(S) IDENTIFICATION**

GHS Pictograms:



Signal Word: Warning.

GHS Class: Eye Irritant, Category 2B.  
 Skin Irritant, Category 2.

Hazard Statements: Causes eye irritation.  
 Causes skin irritation.

Precautionary Statements: Wear protective clothing, gloves, eye, and face protection.  
 Do not eat, drink or smoke when using this product.  
 Wash hands thoroughly after handling.  
 Take off contaminated clothing and wash it before reuse.  
 Dispose of unused contents, container, and other contaminated wastes in accordance with local, state, federal, and provincial regulations.  
**If in eyes:** Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists.  
**If on skin:** Wash with plenty of soap and water.  
**If swallowed:** Rinse mouth and get medical attention if you feel unwell.

Emergency Overview: Irritant.

Potential Health Effects:

Eye: May cause irritation.

Skin: May cause irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.

Signs/Symptoms: Overexposure may cause headaches and dizziness.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing Conditions: None generally recognized.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Ingredient Percent	EC Num.
Titanium dioxide	13463-67-7	10 - 30 by weight	236-675-5
Clay (kaolin)	1332-58-7	5 - 10 by weight	310-194-1
Nepheline Syenite	37244-96-5	1 - 5 by weight	
Calcium carbonate (limestone)	1317-65-3	1 - 5 by weight	215-279-6

Silica, crystalline - cristobalite	14464-46-1	1 - 5 by weight	238-455-4
Carbonic acid calcium salt	471-34-1	1 - 5 by weight	207-439-9
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5 by weight	
Flux Calcined Diatomaceous Earth (DE)	68855-54-9	0.1 - 1 by weight	272-489-0

**Note:** The remaining components of this product are non-hazardous or are in a small enough quantity as to not meet regulatory thresholds for disclosure.

## SECTION 4 : FIRST AID MEASURES

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

**Skin Contact:** Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

## SECTION 5 : FIRE FIGHTING MEASURES

**Flash Point:** None.

**Lower Flammable/Explosive Limit:** Not applicable.

**Upper Flammable/Explosive Limit:** Not applicable.

**Extinguishing Media:** Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.

**Protective Equipment:** As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

**NFPA Ratings:**

NFPA Health: 1

NFPA Flammability: 1

NFPA Reactivity: 0

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in Section 8.

**Environmental Precautions:** Avoid runoff into storm sewers, ditches, and waterways.

**Methods for containment:** Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, diking or other means. Provide ventilation.

**Methods for cleanup:** Clean up spills immediately observing precautions in the protective equipment section. Place into a suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water to remove trace residue.

## SECTION 7 : HANDLING and STORAGE

**Handling:** Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

**Storage:** Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.

**Hygiene Practices:** Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

## SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

**Engineering Controls:** Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

**Eye/Face Protection:** Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.

**Skin Protection Description:** Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.

**Respiratory Protection:** A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**Other Protective:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**PPE Pictograms:**



#### EXPOSURE GUIDELINES

**Titanium dioxide :**

Guideline ACGIH: TLV-TWA: 10 mg/m3

**Clay (kaolin) :**

Guideline ACGIH: TLV-TWA: 2 mg/m3 (E,R)

Guideline OSHA: PEL-TWA: 5 mg/m3 Respirable fraction (R)

PEL-TWA: 15 mg/m3 Total particulate/dust (T)

**Carbonic acid calcium salt :**

Guideline OSHA: PEL-TWA: 5 mg/m3 Respirable fraction (R)

PEL-TWA: 15 mg/m3 Total particulate/dust (T)

**Silica, amorphous, precipitated and gel :**

Guideline OSHA: PEL-TWA: 20 mppcf

### SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State:	Liquid.
Color:	White
Odor:	Slight.
Odor Threshold:	None.
Boiling Point:	>99°F (>37°C)
Melting Point:	None.
Density:	11.672 Lbs/gal
Solubility:	None.
Vapor Density:	None.
Vapor Pressure:	None.
Evaporation Rate:	None.
pH:	7-10
Viscosity:	50 - 140 krebs units
Coefficient of Water/Oil Distribution:	None.
Flammability:	None.
Flash Point:	None.
VOC Content:	Material VOC: 0 gm/L(Includes Water) Coating VOC.:0 gm/L(Excludes Water)

### SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.
Incompatible Materials:	Oxidizing agents. Strong acids and alkalis.

### SECTION 11 : TOXICOLOGICAL INFORMATION

Eye:	No relevant toxicological data for classification were found.
Skin:	No relevant toxicological data for classification were found.
Inhalation:	No relevant toxicological data for classification were found.
Ingestion:	No relevant toxicological data for classification were found.
<b>Carbonic acid calcium salt :</b>	
Eye:	Administration into the eye - Rabbit Standard Draize test: 750 ug/24H [Severe] (RTECS)
Ingestion:	Oral - Rat LD50 - Lethal dose, 50 percent kill: 6450 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

## SECTION 12 : ECOLOGICAL INFORMATION

**Ecotoxicity:** No ecotoxicity data was found for the product.  
**Environmental Fate:** No environmental information found for this product.

## SECTION 13 : DISPOSAL CONSIDERATIONS

**Waste Disposal:** Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

## SECTION 14 : TRANSPORT INFORMATION

**DOT Shipping Name:** Not restricted as a dangerous good.  
**DOT UN Number:** Not restricted as a dangerous good.  
**IATA Shipping Name:** Not restricted as a dangerous good.  
**IATA UN Number:** Not restricted as a dangerous good.  
**Canadian Shipping Name:** Not restricted as a dangerous good.  
**Canadian UN Number:** Not restricted as a dangerous good.  
**IMDG UN Number :** Not restricted as a dangerous good.  
**IMDG Shipping Name :** Not restricted as a dangerous good.  
**ADR UN Number:** Not restricted as a dangerous good.  
**ADR Shipping Name :** Not restricted as a dangerous good.

## SECTION 15 : REGULATORY INFORMATION

### Titanium dioxide :

**TSCA Inventory Status:** Listed  
**Canada DSL:** Listed  
**EC Number:** 236-675-5

### Clay (kaolin) :

**TSCA Inventory Status:** Listed  
**Canada DSL:** Listed  
**EC Number:** 310-194-1

### Nepheline Syenite :

**Canada DSL:** Listed

### Calcium carbonate (limestone) :

**TSCA Inventory Status:** Listed  
**EC Number:** 215-279-6

### Silica, crystalline - cristobalite :

**TSCA Inventory Status:** Listed  
**Canada DSL:** Listed  
**EC Number:** 238-455-4

### Carbonic acid calcium salt :

**TSCA Inventory Status:** Listed  
**Canada DSL:** Listed  
**EC Number:** 207-439-9

### Silica, amorphous, precipitated and gel :

**Canada DSL:** Listed

### Flux Calcined Diatomaceous Earth (DE) :

**TSCA Inventory Status:** Listed  
**Canada DSL:** Listed  
**EC Number:** 272-489-0

HMIS Ratings:

HMIS Health Hazard: 1

HMIS Fire Hazard: 1

HMIS Reactivity: 0

SDS Creation Date: January 21, 2015

SDS Revision Date: October 20, 2017