

Simple Installation Instructions

Included In Box:

- •2 3' Puppy Guard Panels (if purchased)
- •2 3' Puppy Guard Strips (if purchased)
- •#8 x ½" Self-Taping Screws

Needed For Installation:

- •Power Drill w/ #1 Phillips Screw Bit
- •(Optional) Jigsaw for Trimming



Flush Bottom Panel Style



Picket Bottom **Panel Style**

Step 1

Step 2

Insert 3' section of Puppy Guard to yard side of your installed fence section as shown in Figure 1. Bottom pickets on Puppy Guard should rest on bottom horizontal rail of installed fence section. Horizontal rail ends on Puppy Guard should meet at center of center vertical picket on installed fence section. Attach using 4 - #8 x ½" self tapping screws.




Figure 1

opposite installed section of Puppy Guard as shown in Figure 2. Bottom pickets on Puppy Guard should also rest on bottom horizontal rail of installed fence section as instructed in step 1. Make sure horizontal rails ends on both sections of Puppy Guard meet on center of vertical picket on

Insert second 3' section of Puppy Guard

Attach using 4 - #8 x ½" self tapping screws.

installed fence section before attaching.



Figure 2

Screw Placement



Simple Installation Instructions

Step 3

This step is only required when Picket Bottom Style Fence is installed in your yard. Install Puppy Guard Strip (sold separately) at bottom of extended pickets of installed fence as shown in Figure 3. Strip should be located between bottom of horizontal rail and bottom of pickets of your installed fence section as shown.

Attach using 2 - $\#8 \times \frac{1}{2}$ " self tapping screws.



Screw Placement

Figure 3

Step 4

Install second Puppy Guard Strip opposite first installed Puppy Guard Strip as shown in Figure 4. Make sure ends of Puppy Guard Strips meet on center of vertical picket on installed fence section. Attach using 2 - #8 x ½" self tapping screws.

Figure 5 Below shows how Puppy Guard can rack to installed fence by adjusting rails.







