MATERIAL SAFETY DATA SHEET

Date : Jan/23/2012 File No.: PH-W5-878

Identification of the substance/preparation and of the company/undertaking 1.

Identification of the product	
Product name :	Lithium Ion Cell
Chemical System:	LiFePO4/C
Model:	Cylindrical and Prismatic Type Cells_
Designated for RECHARGE?	\underline{X} Yes No
Manufacturer/supplier identification	
Company :	Guangzhou Great Power Energy & Technology Co., Ltd.
Contact for information :	922 Xicun Section, Shiliang Road, Shawan, Panyu,
	Guangzhou, GD, PRC
Emergency telephone No. :	0086-20-61920399

2. Composition/information on ingredients

Ingredient	Percent	CAS Index No./EC No.	Molar mass	Molecular formula	Symbol
Lithium iron phosphate	23%	N/A		LiFePO4	
Graphite	11.5%	7782-42-5		С	
Organic Electrolyte	13.2%	N/A			
Polypropylene	2%	N/A			
Iron	38.1%	7439-89-6		Fe	
Copper	6.7%	7440-50-8		Cu	
Aluminum	5.5%	7429-90-5		Al	

Weight of metallic lithium per cell: 0g. There is no metallic lithium in the lithium ion battery.

3. Hazards identification

Health Hazards (Acute and Chronic):

For the battery cell, chemical materials are stored in a hermetically sealed can, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

However, if exposed to a fire, added mechanical shocks, decomposed, or added electric stress by misuse the cell case will be breached and hazardous materials may be released. Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted.

Carcinogenicity: NTP: None IARC Monograph: None OSHA Regulated: None

Medical Conditions Generally Aggravated by Exposure: An acute exposure will not generally aggravate any medical condition. Human health effects:

Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract. Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and the stimulation on the skin.

Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and the stimulation on the eye. Inflammation of the eyes may occur.

Environmental effects:

Since a battery cell remains in the environment, do not throw out it into the environment.

Specific hazards:

If the electrolyte contacts with water, it may generate detrimental hydrogen fluoride. Since the leaked electrolyte is inflammable liquid, do not bring close to fire.

4. First aid measures	
After inhalation contact:	Make the victim blow his/her nose, gargle. Seek medical attention if necessary.
After skin contact:	Remove contaminated clothes and shoes immediately. Immediately wash extraneous matter or contact region with soap and plenty of water.
After eye contact:	Do not rub eyes. Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention.
After ingestion contact:	Make the victim vomit. Immediately seek medical attention.

5. Fire-fighting measures

Extinguishing Media:	Plenty of water, CO_2 gas, nitrogen gas, chemical powder fire extinguishing medium and fire foam.
Specific methods of	When the battery burns with other combustibles simultaneously, take fire
fire-fighting:	extinguishing method which corresponds to the combustibles. Extinguish a fire from the windward as much as possible.
Flammable Limits:	Not available

6. Accidental release measures

The preferred response is to leave the area and allow the batteries to cool and the vapors to dissipate. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

7. Handling and storage

Avoid mechanical or electrical abuse. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. Exposure controls/personal protection

Specific control parameter :Personal protective equipment :Respiratory protection (Specify Type) :Ventilation:Protective Gloves:Eye protection:Other ProtectiveOther Protective(Clothing or Equipment):

9. Physical and chemical properties

Appearance	
Physical state:	Solid
Form:	Cylindrical
Color:	Metallic color
Odor:	No odor
PH	N/A
Specific temperatures	Temperature ranges changes in physical state occur.
Flash point	N/A
Explosion properties	N/A
Density	N/A
Solubility	with indication of the solvent(s): Insoluble in water

10. Stability and reactivity

Stability: Conditions to Avoid:	Stable When cell is exposed to an external short-circuit, crushes, deformation, high
	temperature above 100 degree C, it will cause heat generation and ignition. Avoid direct sunlight and high humidity.
Hazardous Decomposition or By-products:	Acrid or harmful gas is emitted during fire.
Materials to avoid:	Conductive materials, water, seawater, strong oxidizers and strong acids.

Hazardous polymerization will not occur.

11. Toxicological information	
Acute toxicity :	
Copper	60-100mg sized coarse particulate causes a gastrointestinal disturbance with nausea and inflammation. TDLo, hypodermic - Rabbit 375mg/kg
Organic electrolyte	LD50, oral - Rat 2,000mg/kg or more
Further toxicological information :	
Aluminum	By the long-term inhalation of coarse particulate or fume, it is possible to cause lung damage (aluminum lungs).
Graphite	Long-term inhalation of high levels of graphite coarse particulate may cause lung disease or a tracheal disease.

12. Ecological information

Ecotoxic effects : N/A Further ecological data : N/A

13. Disposal considerations

Great Power encourages battery recycling. Our Li-ion batteries are recyclable through the Rechargeable Battery Recycling Corporation's (RBRC) *Charge Up to Recycle! Program*. For information call 1-800-8-BATTERY or see their website at www.rbrc.org. Li-ion batteries must be handled in accordance with all applicable state and

federal laws and regulations.

DO NOT INCINERATE or subject battery cells to temperatures in excess of 212° F. Such treatment can vaporize the liquid electrolyte causing cell rupture. Do not use in combination with fresh and used lithium batteries neither with other type of battery.

14. Transport information	
International transport regulations	1. International Air Transport Association (IATA 52 nd edition) pursuant to PI 965 Section II.
	2. International Maritime Dangerous Goods Code (IMDG) pursuant to
	Special Provisions 188 and 230.
	4. U.S. hazardous materials regulations pursuant to 49 CFR 173.185 and
	Special Provision 188.
UN-No.:	3480
IATA Packaging Instruction	Section II of PI 965

Great Power Li-ion cells contain no metallic lithium and pass the tests defined in UN model regulation section 38.3.

If Great Power Li-ion cells are used to construct battery packs, the assembler of that pack is responsible to ensure the battery has been tested in accordance with the requirements contained in the UN Model Regulations, Manual of Test and Criteria. Part III, subsection 38.3.

15. Regulatory information

N/A

16. Other information	tion	
Make people :	Professional post : R&D Engineer	Name(sign) : James Lee
Make unit :	Name:R&D Department Address:R&D Dept., Panyu Plant.,	Phone : 0086-20-61920399
Date of issue: 2012/	01/23	
DISCLAIMER :	The information and recomme good faith and believed to be a preparation. Guangzhou Great Co. makes no warranty, expres this information and disclaims it.	accurate as of the date of Power Energy & Technology ssed or implied, with respect to