



DECKPLUS® SOLID COLOR WATERPROOFING WOOD STAIN
NO. 211 WHITE BASE



PRODUCT INFORMATION

BEHR® DECKPLUS® SOLID COLOR WATERPROOFING WOOD STAIN provides protection from water and the sun's harmful rays for up to 5 years on decks and 15 years on fences and siding. Available in over 1,600 custom colors and formulated for color matching, this stain will hide imperfections while allowing the wood texture to show through. The 100% acrylic formula resists cracking, peeling and blistering. This product is also great for composite decks.

RECOMMENDED USES:

Ideal for properly prepared exterior vertical and horizontal surfaces such as:

- Wood
- Engineered (Synthetic) Wood
- Wood Composite

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

- No. 211 Tintable White 124 oz / 4 oz
- No. 213 Deep Base 116 oz / 12 oz

Resin Type: 100% Acrylic

Weight per Gallon: 10.4 lb

% Solids by Volume: 38% ± 2%

% Solids by Weight: 50% ± 2%

VOC: <100 g/L

Flash Point: N/A

Viscosity: 68-77 KU

Recommended Film Thickness:

- 1st Coat:** Wet: 5.4 mils / Dry: 2.0 mils @ 300 sq ft/gal
- 2nd Coat:** Wet: 2.7 mils / Dry: 1.0 mils @ 600 sq ft/gal

Coverage: 200-400 sq ft/gal, depending on application method and substrate porosity.

APPLICATION:

Brush: Nylon/polyester

Roller: 3/8"-1/2" nap roller cover, depending on surface texture

Airless Spray:

Tip: .015" - .019"

Filter: 60 mesh

Fluid Pressure: 1,400 – 2,400 psi

Follow spraying immediately with back brushing or back rolling for a uniform appearance

Thinning: If thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

Dry Time: @ 77°F & 50% RH

To Recoat: 1-2 hours

Light Foot Traffic: 24-48 hours

Full Cure: 72 hours

Dry times are temperature, humidity, and film thickness dependent.

SURFACE PREPARATION:

The following steps and products are recommended for best results:

If you use a product such as BEHR PREMIUM® Wood Stain & Finish Stripper No. 64 to remove loose wood fibers, latex, oil-based and 100% acrylic coating on new or weathered wood, then you must use a product such as BEHR PREMIUM® All-In-One Wood Cleaner No. 63 to clean, brighten & neutralize wood. If you do not use BEHR PREMIUM Wood Stain & Finish Stripper No. 64, then use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to clean and brighten the wood surface and to remove light to medium exterior stains caused by mold, mildew, algae & fungus. Rinse thoroughly and allow to dry before coating. On new wood, use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to remove mill glaze and open the pores of the wood. Lightly sand to remove remaining wood fibers/fuzz.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

SYSTEM RECOMMENDATIONS:

Wood:

- BEHR PREMIUM PLUS® Exterior Multi-Surface Primer & Sealer No. 436

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers,

COMPLIES WITH THE BELOW AS OF 1/1/2020			
SCAQMD	YES	OTC	YES
CARB SCM 2007	YES	LADCO	YES
CARB	YES	AIM	YES
OTC Phase II	YES	MPI	16

unused product and soiled rags, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing
- For best results, apply when air, material and surface temperatures are between 40°F and 90°F. Avoid applying stain in direct sunlight or to hot surfaces. Temperatures above 90°F can cause the paint to dry too fast. Do not apply if rain is expected within 24 hours of product application.
- Test product for color on a small hidden area before proceeding.
- No primer needed on most woods. However, Redwood, Cedar, Cypress and other "bleeding" woods contain water soluble extractive that may cause discoloration of white and pastel colors; therefore, prime the above type woods with one coat of a product such as BEHR PREMIUM PLUS Exterior Multi-Surface Primer & Sealer No. 436.
- Avoid applying stain too heavily. Over-application of DECKPLUS SOLID COLOR WATERPROOFING WOOD STAIN results in film forming on the wood surface and therefore subject to peeling and flaking.
- Stained surfaces may become slippery when wet.
- Shelf life under normal conditions is 2 years (unopened containers).

GENERAL INFORMATION:

WARNING IRRITANT HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer



**DECKPLUS® SOLID COLOR WATERPROOFING WOOD STAIN****NO. 211 WHITE BASE**

additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.