EVERBILT™

FAUCET BIBB SEAT REPAIR KIT INSTALLATION INSTRUCTIONS

1006965250

Tools Required:

Screwdriver (to remove Handle)
Bibb Seat Wrench

Installation Instructions:

1. Turn off water supply to the faucet. Once the water supply is shut off, turn the faucet on to release water pressure, then turn the faucet off.
2. Remove the faucet valve components: Handle, Stem, and any Washers or O–Rings.
3. Remove old Seat: Insert Bibb Seat Wrench into the Seat and turn it counterclockwise. (Use spray lubricant if the Seat is difficult to remove.)
4. Install new Seat: Find the exact match Seat in the Bibb Seat Repair Kit. (See Kit contents below.) Place new Seat in the faucet valve. Secure by using the Bibb Seat Wrench, and turning clockwise. Before reassembling the faucet, remove any debris from the valve.
5. Reinstall the faucet valve components: Stem, any Washers or O–Rings, and Handle.
6. Turn on water supply and check for leaks.

1006 965 250

FAUCET BIBB SEAT REPAIR KIT

For Pfister Height: 3/8 Thread Pitch: 21/32 x 18	For Central Brass Height: 21/32 Thread Pitch: 5/8 x 24
For Kohler Height: 5/16 Thread Pitch: 1/2 x 27	
For Sterling Height: 3/8 Thread Pitch: 1/2 x 24	
For Sayco Height: 5/16 Thread Pitch: 1/2 x 20	For Pfister Height: 3/8 Thread Pitch: 1/2 x 20
For American Standard Height: 11/32 Thread Pitch: 7/16 x 24	For American Standard Height: 11/32 Thread Pitch: 7/16 x 24
For Central Brass Height: 3/8 Thread Pitch: 1/2 x 24	
For Gerber Height: 7/16 Thread Pitch: 5/8 x 20	

NOT MANUFACTURED BY OR CONNECTED WITH THE PRODUCER OF GERBER®, CENTRAL BRASS®, SAYCO®, STERLING®, KOHLER®, AMERICAN STANDARD® OR PFISTER® BATHROOM AND KITCHEN FIXTURES.