

## 1. Identification

**Product identifier** BEHR Water-Based Wood Stain Dark Walnut

**Other means of identification**

**Product code** B4502

**Recommended use** Architectural Coating

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Supplier** Behr Process Corp.  
1801 E. St. Andrew Place  
Santa Ana, CA 92705

**Telephone** 714-545-7101

**Emergency telephone number** (800)-424-9300 CHEMTREC®

## 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Sensitization, skin Category 1A  
Specific target organ toxicity, repeated exposure Category 2 (kidney)

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Warning

**Hazard statement** May cause an allergic skin reaction. May cause damage to organs (kidney) through prolonged or repeated exposure.

**Precautionary statement**

**Prevention** Do not breathe mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves.

**Response** If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** None.

## 3. Composition/information on ingredients

**Mixtures**

Chemical name	CAS number	%
Ethylene glycol	107-21-1	1 - 3
Carbon black	1333-86-4	0.1 - 1
Biocide	55965-84-9	0 - 0.1

**Composition comments** The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

#### 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

**Most important symptoms/effects, acute and delayed** May cause an allergic skin reaction. Dermatitis. Rash. Edema. Prolonged exposure may cause chronic effects.

**Indication of immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

**Suitable extinguishing media** Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical** During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire fighting equipment/instructions** Move containers from fire area if you can do so without risk.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

**Precautions for safe handling** Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities** Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

##### Occupational exposure limits

##### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m <sup>3</sup>

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m <sup>3</sup>	Inhalable fraction.
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m <sup>3</sup>	Aerosol, inhalable.
	TWA	50 ppm	Vapor fraction
		25 ppm	Vapor fraction

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m <sup>3</sup>

<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).
<b>Appropriate engineering controls</b>	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves.
<b>Skin protection</b>	
<b>Other</b>	Wear appropriate chemical resistant clothing.
<b>Respiratory protection</b>	If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. In case of insufficient ventilation, wear suitable respiratory equipment. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Dark brown.

**Odor** Slight.

**Odor threshold** Not available.

**pH** 7 - 10

**Melting point/freezing point** Not available.

**Initial boiling point and boiling range** > 99 °F (> 37.2 °C)

**Flash point** Not applicable.

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not applicable.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** Not available.

**Flammability limit - upper (%)** Not available.

**Vapor pressure** Not available.

**Vapor density** Not available.

Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	40 - 80 ku
Other information	
Density	8.65 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	31 g/l (including water)(Material) 212 g/l (excluding water)(Coating)

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** May cause an allergic skin reaction. Dermatitis. Rash. Edema. Prolonged exposure may cause chronic effects.

### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components	Species	Test Results
Carbon black (CAS 1333-86-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 3000 mg/kg
<b>Oral</b>		
LD50	Rat	> 8000 mg/kg
Ethylene glycol (CAS 107-21-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	9530 mg/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

### Respiratory or skin sensitization

Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Inhalation of carbon black dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Carbon black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

**NTP Report on Carcinogens**

Carbon black (CAS 1333-86-4) Known To Be Human Carcinogen.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** May cause damage to organs (kidney) through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

**12. Ecological information**

**Ecotoxicity** The product is not classified as environmentally hazardous.

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential** No data available.

**Mobility in soil** No data available.

**Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information**

**DOT**  
Not regulated as dangerous goods.

**IATA**  
Not regulated as dangerous goods.

**IMDG**  
Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Ethylene glycol (CAS 107-21-1) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**Toxic Substances Control Act (TSCA)****Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes**Classified hazard categories** Respiratory or skin sensitization  
Specific target organ toxicity (single or repeated exposure)**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Ethylene glycol	107-21-1	1 - 3

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethylene glycol (CAS 107-21-1)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Contains component(s) regulated under the Safe Drinking Water Act.**US state regulations****US. Massachusetts RTK - Substance List**

Carbon black (CAS 1333-86-4)

Ethylene glycol (CAS 107-21-1)

**US. New Jersey Worker and Community Right-to-Know Act**

Carbon black (CAS 1333-86-4)

Ethylene glycol (CAS 107-21-1)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Carbon black (CAS 1333-86-4)

Ethylene glycol (CAS 107-21-1)

**US. Rhode Island RTK**

Carbon black (CAS 1333-86-4)

Ethylene glycol (CAS 107-21-1)

**16. Other information, including date of preparation or last revision**

**Issue date** 10/17/19  
**Revision date** 10/17/19  
**Version #** Initial  
**HMIS® ratings** Health: 2\*  
 Flammability: 0  
 Physical hazard: 0

**List of abbreviations** LD50: Lethal Dose, 50%.  
 IATA: International Air Transport Association.  
 IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.  
 IMDG Code: International Maritime Dangerous Goods Code.  
 MARPOL: International Convention for the Prevention of Pollution from Ships.  
 TWA: Time Weighted Average Value.

**References** HSDB® - Hazardous Substances Data Bank**Disclaimer** Behr Process Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.