

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

- Product Name: LevelLite Self-Leveling Underlayment
- Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Floor underlayment

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

| Name/Address: | Custom Building Products 13001 Seal Beach Blvd. Seal Beach, CA 90740 |
|-------------------|--|
| Telephone Number: | (562)-598-8808 |

1.4 EMERGENCY TELEPHONE NUMBER

| Emergency Telephone | INFOTRAC 1-800-535-5053 (US and Canada) |
|---------------------|---|
| Number: | INTERNATIONAL + 1-352-323-3500 |

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR

1910.1200 (OSHA HAZCOM2012)

| Skin Irritation | Category 2 |
|-----------------------|-------------|
| Serious Eye Damage | Category 1 |
| STOT-SE | Category 3 |
| Carcinogenicity | Category 1A |
| Reproductive Toxicity | Category 1A |

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

- 2.2a SIGNAL WORD: DANGER!
- 2.2b HAZARD STATEMENTS Causes skin irritation
 - Causes serious eye damage May cause respiratory irritation May cause cancer May damage fertility or the unborn child



2.2c HAZARD PICTOGRAMS



2.2d PRECAUTIONARY STATEMENTS

| i. | PREVENTION | Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/ vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. |
|------|------------|---|
| ii. | RESPONSE | If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. |
| iii. | STORAGE | Store in a well-ventilated place. Keep container tightly closed. Store locked up. |
| iv. | DISPOSAL | Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations. |

2.3 ADDITIONAL INFORMATION

- 2.3a HNOC HAZARDS NOT OTHERWISE CLASSIFIED Not applicable
- 2.3b UNKNOWN ACUTE TOXICITY

25% of the mixture consists of ingredient(s) of unknown acute toxicity.

2.3c WHMIS CLASSIFICATION

Class D2B – Skin/Eye Irritant Class D2A – Reproductive Toxicity Class D2A - Carcinogenicity

2.3d LABEL ELEMENTS ACCORDING TO WHMIS

i. WHMIS HAZARD SYMBOLS





ii. WHMIS SIGNAL WORD WARNING!

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

| Chemical Name | CAS Number | Weight % |
|------------------------------|---------------------|----------|
| Cement, Alumina, Chemicals | 65997-16-2 | 15 – 40% |
| Glass, oxide | 65997-17-3 | 10 – 30% |
| Portland cement | 65997-15-1 | 1 – 30% |
| Calcium carbonate | 1317-65-3 | 10 – 30% |
| Calcium sulfate (Anhydrite)* | 10101-41-4/7778-18- | 10 – 30% |
| | 9/14798-04-0** | |
| Mullite | 1302-93-8 | 3 – 7% |
| Crystalline Silica, Quartz | 14808-60-7 | 1 – 5% |
| Lithium carbonate | 554-13-2 | 0.1 – 1% |

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

*A form of calcium sulfate which includes and is not limited to anhydrite calcium sulfate. **Signifies that the chemical may be one or a combination of two of the following CAS#'s provided.

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST-AID MEASURES

| ROUTES OF EXPOSURE | DESCRIPTION |
|--------------------|--|
| Eye Contact: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately. |
| Skin Contact: | In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. |
| Inhalation: | If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. |
| Ingestion: | If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention. |



4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

| ROUTES OF EXPOSURE | DESCRIPTION |
|--------------------|---|
| Eye Contact: | Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Skin Contact: | Causes skin irritation. Handling can cause dry skin. |
| Inhalation: | May cause respiratory tract irritation. |
| Ingestion: | May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting. |

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

| Note to Physicians: | Symptoms may not appear immediately. |
|---------------------|--|
| Special Treatments: | In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible). |

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability:

Not Flammable by WHMIS/OSHA HAZCOM2012 Criteria

5.2 EXTINGUISHING MEDIA

- **5.2a.** Suitable Extinguishing Media: Treat for surrounding material.
- 5.2b. Unsuitable Extinguishing Media: Not available.

5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

- **5.3a. Products of Combustion:** May include, and are not limited to: oxides of carbon
- 5.3b. Explosion Data
 - i. Sensitivity to Mechanical Impact: Not available.
 - ii. Sensitivity to Static Discharge: Not available.



5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

| Methods for Containment: | Recover all usable material. Pick up large pieces, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). |
|--------------------------|--|
| Methods for Cleaning-Up: | Vacuum or sweep material and place in a disposal container. Dispose of unwanted material properly in accordance with all local, regional, national and international regulations. |

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

| Handling: | Use in well-ventilated areas. Wear chemical resistant gloves and eye protection. Do not mix with other chemical products. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Do not take internally. Good housekeeping is important to prevent accumulation of dust. |
|-------------------------|---|
| General Hygiene Advice: | Use good industrial hygiene practices and wear recommended personal protection. Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. |

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage:

Keep out of the reach of children. Keep container tightly closed. Store at room temperature and keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.



Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

| Occupational Exposure Limits | | |
|------------------------------|-------------------------------------|------------------------------|
| Chemical Name | OSHA-PEL | ACGIH-TLV |
| Cement, Alumina, Chemicals | Not available | Not available |
| Glass, oxide | 15 mg/m³ (total) | 10 mg/m ³ (Total) |
| Portland cement | 5 mg/m³ (Resp.) 15 mg/m³ (Total) | 10 mg/m³ (Resp.) |
| Calcium carbonate | 5 mg/m³ (Resp.) 15 mg/m³ (Total | 2 mg/m³ (Resp.) |
| Calcium sulfate (Anhydrite) | 5 mg/m³ (Resp.) 15 mg/m³ (Total | 0.025 mg/m ³ |
| Mullite | Not available | Not available |
| Crystalline Silica, Quartz | 0.1 mg/m ³ | 0.025 mg/m ³ |
| Lithium carbonate | Not available | Not available |

8.2 EXPOSURE CONTROLS

Engineering Controls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTION MEASURES

- 8.3a. Personal Protective Equipment:
 - i. **Eye/Face Protection:** Wear approved eye [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)] protection
 - ii. Skin Protection:
 - 1. Hand Protection: Wear chemical resistant gloves.
 - 2. Body Protection: Wear suitable protective clothing
 - iii. Respiratory Protection: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
 - iv. General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.



Section 9: PHYSICAL AND CHEMICAL PROPERTIES

| Appearance (physical state, color, etc.): | Solid Powder |
|---|----------------------------------|
| Odor: | Characteristic |
| Odor Threshold: | Not available |
| pH: | Not available |
| Melting point/Freezing point: | Not available |
| Initial boiling point and boiling range: | Not available |
| Flash point: | > 212°F |
| Evaporation rate (Water=1): | Not available |
| Flammability: | Not flammable |
| Upper Flammability/Explosive Limit: | Not available |
| Lower Flammability/Explosive Limit: | Not available |
| Vapor Pressure | Not available |
| Vapor Density: | Not available |
| Relative Density: | Not available |
| Solubility in Water: | Moderately Soluble |
| Partition coefficient: n-octanol/water: | Not available |
| Auto-ignition temperature: | Not available |
| Decomposition Temperature: | Not available |
| Viscosity (cps): | 1,500 – 2,500 spindle#3 @ 20 rpm |
| VOC Content: | 0 g/L (0%) |

Section 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2. CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

- **10.3. POSSIBILITY OF HAZARDOUS REACTION** No dangerous reaction known under conditions of normal use.
- **10.4. CONDITIONS TO AVOID** Heat. Incompatible materials.
- **10.5. INCOMPATIBLE MATERIALS** None known.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

Page 7 of 12



11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

- **Eye Contact:** Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Skin Contact: Causes skin irritation. Handling can cause dry skin.
 - Inhalation: May cause respiratory tract irritation.
 - **Ingestion:** May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

| Acute Toxicity | | | |
|-----------------------------|---------------|--|--|
| Chemical Name | LC50 | LD50 | |
| Cement, Alumina, Chemicals | Not available | Dermal: Not Toxic Oral: >2,000 mg/kg (Practically non-toxic) | |
| Glass, oxide | Not available | Not Toxic | |
| Portland cement | Not available | Not available | |
| Calcium carbonate | Not available | Not Toxic | |
| Calcium sulfate (Anhydrite) | Not available | Not Toxic | |
| Mullite | Not available | Not available | |
| Crystalline Silica, Quartz | Not available | Not Toxic | |
| Lithium carbonate | >2 mg/L/4hrs | Dermal: >2,000 mg/kg Oral: 640 mg/kg | |

| Chemical Name | Chemical Listed as Carcinogens or Potential Carcinogen (NTP,IARC,OSHA,ACGIH,CP65)* |
|-----------------------------|--|
| Cement, Alumina, Chemicals | Not Listed |
| Glass, oxide | N-2, I-2B, CP65 |
| Portland cement | Not Listed |
| Calcium carbonate | Not Listed |
| Calcium sulfate (Anhydrite) | Not Listed |
| Mullite | Not Listed |
| Crystalline Silica, Quartz | N-A2, I-1, O-1, CP65 |
| Lithium carbonate | CP65 |

11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

| SHORT-TERM | |
|--------------------------------|--------------------------|
| Skin Corrosion/Irritation: | Causes skin irritation |
| Serious Eye Damage/Irritation: | Causes severe eye damage |
| Respiratory Sensitization: | Not available |



| Skin Sensitization: | Not available |
|-----------------------------------|--|
| STOT-Single Exposure: | May cause respiratory irritation |
| Aspiration Hazard: | Not available |
| LONG-TERM | |
| Carcinogenicity: | May cause cancer |
| Germ Cell Mutagenicity: | Not available |
| Reproductive Toxicity: | May damage fertility or the unborn child |
| STOT-Repeated Exposure: | Not available |
| Synergistic/Antagonistic Effects: | Not available |

Section 12: ECOLOGICAL INFORMATION

12.1. ECOTOXICITY

In large amounts, this substance may be potentially dangerous or hazardous to the aquatic environment. Keep from entry into sewers and waterways.

| Ecotoxicity | | | | |
|-----------------------------|--------------------------|------------------------|--|--|
| Chemical Name | EC50/NOEC-48 Hours | LC50/NOEC-96 Hours | | |
| Cement, Alumina, Chemicals | Not available | Not available | | |
| Glass, oxide | Not available | >1,000 mg/L Zebra fish | | |
| Portland cement | Not available | Not available | | |
| Calcium carbonate | Not available | Not available | | |
| Calcium sulfate (Anhydrite) | Not available | Not available | | |
| Mullite | Not available | Not available | | |
| Crystalline Silica, Quartz | Not available | Not available | | |
| Lithium carbonate | EC50 - 33.2 mg/L Daphnia | LC50 - 30.3 mg/L | | |
| | Magna (No mortality) | NOEC - 19.1 mg/L | | |

12.2. PERSISTENCE AND DEGRADABILITY Not available

12.3. BIOACCUMULATIVE POTENTIAL Not available

12.4. MOBILITY IN SOIL Not available

12.5. OTHER ADVERSE EFFECTS Not available

Section 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations **13.2. OTHER DISPOSAL CONSIDERATIONS**

Not available



Section 14: TRANSPORT INFORMATION

| TDG (CANADA) |
|--------------------------------|
| UN NUMBER: |
| |
| Not regulated |
| UN PROPER SHIPPING NAME: |
| |
| Not regulated |
| TRANSPORT HAZARD CLASS (ES): |
| |
| Not regulated |
| PACKING GROUP (if applicable): |
| |
| Not regulated |
| |

SUMMARY: Product is not regulated under DOT/TDG and other transportation regulations.

14.1. ENVIRONMENTAL HAZARDS

Not available

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE Not available

14.3. SPECIAL PRECAUTIONS FOR USER Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

15.2. US FEDERAL INFORMATION:

SARA TITLE III: Section 302, Extremely Hazardous Substances, 40 CFR 355:

SARA TITLE III: Section 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) Health Hazard; Chronic Health Hazard; Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.



SARA TITLE III: Section 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements if it contains Toxic Chemical Constituents above their de minimus concentrations.

Clean Air Act – Not available

| SARA TITLE III | | | | |
|-----------------------------|-----------------|--------------|------------|-------------|
| CHEMICAL NAME | SECTION 302 | SECTION 304 | CERCLA RQ | SECTION 313 |
| | (EHS) TPQ (LBS) | EHS RQ (LBS) | (LBS) | (TRI) |
| Cement, Alumina, Chemicals | Not Listed | Not Listed | Not Listed | Not Listed |
| Glass, oxide | Not Listed | Not Listed | Not Listed | Not Listed |
| Portland cement | Not Listed | Not Listed | Not Listed | Not Listed |
| Calcium carbonate | Not Listed | Not Listed | Not Listed | Not Listed |
| Calcium sulfate (Anhydrite) | Not Listed | Not Listed | Not Listed | Not Listed |
| Mullite | Not Listed | Not Listed | Not Listed | Not Listed |
| Crystalline Silica, Quartz | Not Listed | Not Listed | Not Listed | Not Listed |
| Lithium carbonate | Not Listed | Not Listed | Not Listed | Listed |


15.3. US STATE RIGHT TO KNOW LAWS:

| California Proposition 65: | WARNING! This product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm (Crystalline Silica, Glass oxide, Lithium carbonate) |
|--|---|
| Other U.S. States "Right to Know" Lists: | |
| New Jersey: | CEMENT, ALUMINA, CHEMICALS: CAS#65997-16-2 SILICATE, PORTLAND CEMENT: CAS#65997-15-1 GLASS, OXIDE: CAS#65997-17-3 CALCIUM CARBONATE: CAS#1317-65-3 GYPSUM (CALCIUM SULFATE): VARIOUS (CAS#10101-41-4/7778-18-9/14978-04-0) |
| Pennsylvania: | CEMENT, ALUMINA, CHEMICALS: CAS#65997-16-2 CEMENT, PORTLAND, CHEMICALS: CAS#65997-15-1 GLASS, OXIDE: CAS#65997-17-3 LIMESTONE: CAS#1317-65-3 GYPSUM (CALCIUM SULFATE): VARIOUS (CAS#10101-41-4/7778-18-9/14978-04-0) |
| Massachusetts: | PORTLAND CEMENT: CAS#65997-15-1 CALCIUM CARBONATE: CAS#1317-65-3 GLASS, OXIDE: CAS#65997-17-3 GYPSUM (CALCIUM SULFATE): VARIOUS (CAS#10101-41-4/7778-18-9/14978-04-0) |
| Minnesota: | PORTLAND CEMENT: CAS#65997-15-1 CALCIUM CARBONATE: CAS#1317-65-3 GLASS, OXIDE: CAS#65997-17-3 GYPSUM (CALCIUM SULFATE): VARIOUS (CAS#10101-41-4/7778-18-9/14978-04-0) |
| Florida: | Not Available |
| Michigan: | Not Available |



15.4. GLOBAL INVENTORIES

| Chemical Name | USA TSCA | Canada DSL/NDSL |
|------------------------------|----------|--------------------|
| Cement, Alumina, Chemicals | Yes | DSL |
| Glass, oxide | Yes | DSL |
| Portland cement | Yes | DSL |
| Calcium carbonate | Yes | DSL |
| Calcium sulfate (Anhydrite)* | Yes | DSL |
| Mullite | Yes | DSL |
| Crystalline Silica, Quartz | Yes | DSL |
| Lithium carbonate | Yes | DSL |





15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

| CP65 | California Proposition 65 | |
|-----------|--|--|
| OSHA (O) | Occupational Safety and Health Administration | |
| ACGIH (G) | American Conference of Governmental Industrial Hygienists | |
| | A1 – Confirmed human carcinogen | |
| | A2 – Suspected human carcinogen | |
| | A3 – Animal carcinogen | |
| | A4 – Not classifiable as a human carcinogen | |
| | A5 – Not suspected a human carcinogen | |
| IARC (I) | International Agency for Research on Cancer | |
| | 1 – The agent (mixture) is carcinogenic to humans | |
| | 2A – The agent (mixture) is probably carcinogenic to humans; there | |
| | is limited evidence of carcinogenicity in humans and sufficient | |
| | evidence of carcinogenicity in experimental animals. | |
| | 2B – The agent (mixture) is possibly carcinogenic to humans; there | |
| | is limited evidence of carcinogenicity in humans in the absence of | |
| | sufficient evidence of carcinogenicity in experimental animals. | |
| | • 3 – The agent (mixture, exposure circumstance) is not classifiable | |
| | as to its carcinogenicity to humans. | |
| | 4 – The agent (mixture, exposure circumstance) is probably not | |
| | carcinogenic to humans. | |
| NTP (N) | National Toxicology Program | |
| | 1 – Known to be carcinogens | |
| | 2 – Reasonably anticipated to be carcinogens | |

Section 16: OTHER INFORMATION

| Date of Preparation: | March 7, 2014 |
|----------------------|---------------|
| Version: | 1.0 |
| Revision Date: | N/A |

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by:

Custom Building Products Phone: (562)-968-2980 www.custombuildingproducts.com

End of Safety Data Sheet