

FLUSH FLOOR VENT

## DO NOT TRY TO INSTALL YOUR NEW FLUSH VENT WITHOUT FIRST READING THESE STEPS.

We highly recommend your contractor install your vent while they are installing your flooring. It is best to let them know that you want to use our product before they begin.

For a standard vent opening (duct opening) of 4" x 10", you have received a vent 1" larger – finishing at 5" x 11". For a standard vent opening (duct opening) of 3" x 10", you have received a vent 1" larger – finishing at 4" x 11". This is because our flush vent sit a ½" on the subfloor on all 4 sides for support. This is what allows it to lay flush.

For standard size vents, you have received: a flush vent with a coated steel backer bonded to it making it safe to walk on after proper installation; a coated diffuser plate, which is also your template and allows you to level your vent.


2. Once you have marked your duct area (4x10),

find the centre of the hole.


1. Figure out exactly where your vent will land and mark your tiles accordingly, with a pencil.



4. You now have your new vent dimensions marked on your tile. 1" longer than your duct work, and 1" wider.




5. Use a saw to carefully cut your tiles as required. (You want to avoid any chips as these edges will show with the final product.)




3. Use the template provided, place it over your

marked centre and trace the template. Giving you

6. Install the tiles as usual with mortar, using the same size grout line.



7. Place the template/diffuser into your opening with the counter sunk holes facing up. Lay the vent on top



8. Adjust the height of the diffuser plate to allow the vent to lay perfectly flush and screw in place. (Full details are in the video link below.)



9. Place your new flush floor vent into the opening

for a look that was Made2Match.



## Watch a quick video with full detailed instructions:

**URL**: https://youtu.be/V-NRBrCx2Bw



YouTube Seach: Made2Match Vent Installation

