TRANSPARENT LOG HOME GLOSS FINISH

NO. 15 CLEAR

PRODUCT INFORMATION

BEHR PREMIUM® Transparent Log Home Gloss Finish is a durable and flexible formula that moves with the natural expansion and contraction of natural wood surfaces and will also protect from the sun's harmful UV rays. It's available in both clear and cedar finishes, and is also great for fences and siding.

RECOMMENDED USES:

Ideal for use on exterior surfaces such as:
• Wood
Do not use on horizontal surfaces subject to foot traffic.

PRODUCT SPECIFICATIONS:

Pre-Mixed Colors:
No. 15 Clear
No. 16 Cedar

Gloss: 80 – 100 @ 60°

Resin Type: Alkyd/Acrylic Dispersion

Weight per Gallon: 8.5 lb

% Solids by Volume: 30% ± 2%

% Solids by Weight: 31% ± 2%

VOC: < 275 g/L

Flash Point: N/A

Viscosity: 20 – 35 sec #2 Zahn Cup

Recommended Film Thickness:
Wet: 8.2 / Dry: 2.4 mils @ 200 sq ft/gal
Wet: 4.1 / Dry: 1.2 mils @ 400 sq ft/gal

Coverage: 200 – 400 sq ft/gal, depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

- Clean and recoat surface when finish no longer has gloss or luster of if the film is broken. Thoroughly seal the ends of the boards and all porous areas such as knots with several thin coats.
- Maintain wet edge when applying. Back-brushing during all apoplication methods. Apply product end-end or to board lengths to prevent lap marks.

Brush: Nylon/polyester

Roller: 3/8" – 3/4" nap roller cover, depending on surface texture

Airless Spray:

Tip: .015" – .019"
Filter: 60 mesh

Thinning: DO NOT THIN. Product is formulated for use at package consistency only.

Dry Time: 77°F & 50% RH
To Touch: 8 – 12 hours
To Recoat: 24 hours
Dry times are temperature, humidity, and film thickness dependent.

SURFACE PREPARATION:

The following steps and products are recommended for best results: If you use a product such as BEHR PREMIUM® Wood Stain & Finish Stripper No. 64 to remove loose wood fibers, latex, oil-based and 100% acrylic coating on new or weathered wood, then you must use BEHR PREMIUM® All-In-One Wood Cleaner No. 63 to brighten & neutralize wood. If you do not use BEHR PREMIUM Wood Stain & Finish Stripper No. 64, use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to clean and brighten the wood sruface and to remove light to medium stains caused by mold, mildew, algae & fungus. On new wood, use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to remove mill glaze and open the pores of the wood. Rinse thoroughly and allow to dry before coating. Lightly sand any remaining wood fibers/fuzz..

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers unused product and soiled rags, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 6/1/2020			
SCAQMD	YES	OTC	YES
CARB SCM 2007	YES	LADCO	YES
OTC PHASE II	YES	AIM	YES

CAUTIONS/LIMITATIONS:

- For best results, apply when air, material and surface temperatures are between 40°F and 90°F. Do not apply in direct sunlight. Temperatures above 90°F can cause the coating to dry too fast, whereas temperatures below 40°F can inhibit proper film formation.
- Do not use if rain is expected within 24 hours.
- Test product for color on a small hidden area before proceeding.
- Avoid applying finish too heavily. Over application of stain will lead to surface failure including peeling & cracking.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:

WARNING IRRITANT HARMFUL IF SWALLOWED. CONTAINS ALKYD RESIN. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows an doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a Behr Paint Company representative, call 1-800-854-0133 Ext. 2 (U.S.A. only). ©2020 Behr Process Corporation, Santa Ana, CA 92705 U.S.A.

Revised 6/2020