

BEHR PREMIUM® Color Enhancing Sealer

No. 982 Natural

- Deepens & Enriches Colors Found in Porous Substrates
- Water Resistant
- Penetrating Formula
- Interior/Exterior & Horizontal/Vertical Surfaces
- Ideal for Porous Natural Stones, Bricks, and Pavers

Coverage:
175-400 Sq. Ft.
Depending On Porosity

Dry Time:
24-72 Hrs. To Cure

Apply
Until Saturated

Protect
From Freezing

CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

WHERE TO USE:

Horizontal and vertical uncoated porous natural stones and masonry surfaces such as: concrete pavers, flagstone, slate, limestone, sandstone, brick, cobblestone, stacked stone, and more. Do not use on smooth, glazed, or polished surfaces. Not recommended for use on areas subject to hydrostatic pressure such as basement walls or floors. NOTE: SURFACE MAY APPEAR SLIGHTLY DARKER. IT IS ADVISABLE TO TEST THE PRODUCT ON AN INCONSPICUOUS AREA BEFORE GENERAL APPLICATION TO ENSURE THE DESIRED APPEARANCE IS ACHIEVED.

PREPARATION (Proper surface preparation is required)

- All surfaces must be clean, sound, dry, and free of any dirt, oil, and grease.
- Remove all dirt, oil, or grease using a cleaner/degreasing product or detergent. Follow all manufacturer's label instructions.
- Use a paint stripper to remove any previous coatings or sealers. Follow all manufacturer's label instructions.
- Test: Sprinkle a few drops of water onto the surface.
- If water is quickly absorbed and the surface feels like 150 grit sandpaper, the surface is ready.
- If water beads or rolls off the surface, additional cleaning may be necessary.

APPLICATION

- DO NOT THIN.
- Stir or mix product thoroughly before and occasionally during application.
- Use product when air and surface temperature is between 50–90° F (10-32° C).
- Apply using a high quality pump sprayer, 1/4" – 3/8" nap roller, synthetic brush, or a sponge pad applicator until saturated. Multiple coats may be necessary on very porous surfaces. Apply within 24 hours of initial application.
- DO NOT ALLOW PRODUCT TO POOL. Remove any puddles by back rolling using a nap roller or by wiping up excess with a clean cloth before it cures.
- On vertical surfaces, apply from the bottom up and saturate well. Avoid dripping and clean up any excess with a clean cloth before it cures.

DRY TIME

- Longer dry time required in cooler temperatures and in higher humidity.
- Water and stain repellency starts to develop within 24 hours.
- Allow 24-72 hours before subjecting surface to automotive tires, heavy foot traffic, or repositioning furniture.
- Wait at least 30 days before rinsing or cleaning.

DISPOSAL

- Properly dispose of all soiled applicators and rags after use and protect unused product from freezing.
- For disposal of empty containers and unused product, contact your household refuse collection service.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY For three years from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within three years from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. To obtain warranty service, call 1-800-854-0133. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

WARNING: This product can expose you to chemicals including ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

WARNING! IRRITANT. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING VAPORS, SPRAY MIST AND SANDING DUST. SANDING, GRINDING OR ABRADING MAY RELEASE SANDING DUST, WHICH MAY BE HARMFUL IF INHALED AND HAS BEEN SHOWN TO CAUSE LUNG DAMAGE OR CANCER WITH LONG TERM EXPOSURE. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY

©2022 Behr Process Corp.
Santa Ana, CA 92705 U.S.A.
behr.com
V.O.C. <120 g/L (Low Solids)
REV 7/22