EASY TO USE DIRECTIONS:

①Using a soft bristle brush, simply "mush" or "stipple" into crevice areas.②Roll all possible areas (an all-purpose fabric roller is preferred).③Avoid traditional brush strokes when using BEYOND PAINT™ Countertop.④Two **light** coats of BEYOND PAINT™ Multi-Purpose SEALER are recommended; allow 2-4 hour drying time between coats.⑤Clean up with soap and water.

RECOMMENDED TOOLS:

① Paint Tray. ②Fabric or woven roller nap and handle.

EASY CARE DIRECTIONS:

① After initial 3 days curing time, maintain by washing with mild soap and water as needed. ②Keep your BEYOND PAINT™ Countertop from extreme heat and direct cutting as you would on any countertop surface.

TO USE IN COMBINATION WITH OUR MULTI-PURPOSE SEALER AND FOR CUSTOM FINISHES, USE IN COMBINATION WITH OUR COUNTERTOP FLECKS.

1 COLOR APPLICATION: Apply 2+ coats as directed above.

1 COLOR GRANITE FINISH: Roll on your final coat of BEYOND PAINT™ Countertop in small (approx. 1 ft x 2 ft) sections. Immediately shake the BEYOND PAINT™ Countertop FLECKS onto wet BEYOND PAINT™ Countertop as desired.

2 COLOR GRANITE FINISH: Roll on two coats of one color. When dry, sponge on another color of BEYOND PAINT™ Countertop. Work in small sections and shake the BEYOND PAINT™ Countertop Flecks onto wet sponged BEYOND PAINT™ Countertop.