

CLEAR

CLEAR

CLEAR

CLEAR

CLEAR



FLASHING

WINDOWS

DOORS

SIDING

TRIM

Contiene: Destilados de petróleo, trimetil (etil metil cetoxima) silano. Puede causar irritación en los ojos, la piel, la nariz y la garganta. Puede causar somnolencia. La exposición repetida o prolongada puede ocasionar efectos adversos en la piel, la sangre y el hígado. Nocivo si se traga o se absorbe a través de la piel. No lo ingiere. No inhale las emanaciones. Utilice solamente con ventilación adecuada. Proporcione entrada de aire fresco. Evite el contacto con los ojos, piel y ropa. Use guantes y gafas de seguridad. Lávese bien después de manipular. **PRIMEROS AUXILIOS: OJOS:** Enjuague inmediatamente los ojos con agua. **PIEL:** Lávese meticulosamente. **INHALACIÓN:** Trasládese al aire fresco. **INGESTION: NO INDUZCA EL VOMITO.** Obtenga atención médica si surgen complicaciones debido a la exposición. **En caso de emergencia,** llame al centro de control de envenenamiento al 1-800-222-1222. Consulte la Hoja de datos de seguridad (SDS, por sus siglas en inglés) para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**
⚠ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov
 Para obtener las instrucciones y garantía en español, llame al 1-888-327-8477 o visite dap.com.
QUESTIONS? ¿PREGUNTAS? Call/Llame al 1-888-DAP-TIPS or visit/o visite dap.com & click on/y pulse en "Ask the Expert."

DAP Products Inc.,
Baltimore, MD
21224

Made in the USA
for DAP Products
Inc. with U.S. and
globally sourced
materials.

dap.com

Silicone Max™

Meets ASTM C920, Class 50

**PREMIUM
ALL PURPOSE
100%
SILICONE**

**MAXIMUM
FLEXIBILITY
For Extreme
Joint Movement**

**Water Resistant in
30 Minutes**

**100%
WATERPROOF &
WEATHERPROOF**

- Shrink & Crack Proof
- Low Odor
- Interior/Exterior
- Lifetime Guarantee

WARNING! MAY CAUSE EYE & SKIN IRRITACION.
Read back panel carefully for other cautions.

¡ADVERTENCIA! PUEDE IRRITAR LOS OJOS Y LA PIEL.
Lea atentamente el panel posterior para conocer otras precauciones.

10.1 fl oz (300 mL)

DAP® SILICONE MAX™ is a premium performance 100% silicone sealant that provides maximum flexibility & adhesion to withstand extreme expansion & contraction. Meets ASTM C920 Specification for Class 50, Uses G, A & M. **FOR BEST RESULTS:** Apply in temps. above 40°F. Not recommended for filling butt joints, surface defects, tuck-pointing, high-temp applications or continuous underwater use. Joint width should not exceed 1/2". If joint depth exceeds 1/2" use backer rod. Not paintable. Store below 120°F in a dry place.
INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk. 2. Cut nozzle at 45° angle. 3. Puncture inner foil seal. 4. Load into caulk gun. 5. Fill gap w/ sealant. 6. Smooth bead. 7. At 73°F & 50% relative humidity, sealant is water resistant at 30 minutes & reaches full cure at 24 hours. Low humidity may slow cure. 8. Clean uncured sealant w/ mineral spirits. Scrape away cured sealant. Do not use mineral spirits to clean skin.

Contains: Petroleum distillates, methyl tri(ethylmethylketoxima) silane. May cause eye, skin, nose & throat irritation. May cause drowsiness. Repeated or prolonged exposure may cause adverse skin, blood & liver effects. Harmful if swallowed or absorbed through the skin. Do not ingest. Do not breathe vapor. Use only w/ adequate ventilation. Ensure fresh air entry during application & drying. Avoid contact w/ eye, skin & clothing. Wear gloves & safety glasses. Wash thoroughly after handling. **FIRST AID: EYE:** Immediately flush eyes w/ plenty of water. Get medical attention. **SKIN:** Wash thoroughly. Immediately flush skin w/ soap & plenty of water. **INHALATION:** Remove to fresh air. If irritation persists, get medical attention. **INGESTION: DO NOT INDUCE VOMITING.** Get medical attention if complications arise from any exposure. **For emergencies,** call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

CCCS Calif. ARB VOC <3 wt/wt% (VOC 38 g/L)
LIFETIME GUARANTEE: DAP warrants this product for sealant purposes during the lifetime of your home. If product fails to perform when used as directed, return container & sales receipt to DAP Products Inc., TCS, 2400 Boston St., Baltimore., MD 21224 for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.