

18V X2 LXT® (36V) BRUSHLESS CORDLESS 1-1/8" AVT® ROTARY HAMMER KIT, ACCEPTS SDS-PLUS BITS W/ EXTRACTOR, AFT®, AWS™ CAPABLE (5.0AH)



**NEW TOOL OVERVIEW
XRH10PTW**

**OSHA
COMPLIANT**



**5.0Ah
BATTERY**

**3
YEAR
WARRANTY
LITHIUM-ION
TOOL &
BATTERY**

ALSO AVAILABLE AS A BARE TOOL: XRH10ZW

**LXT X2 18V + 18V 36V
BRUSHLESS**

FEATURES

- Powerful BL™ Brushless motor delivers 0-980 RPM, 0-5,000 BPM and 2.3 ft.lbs. of impact energy to handle the most demanding applications
- Auto-Start Wireless System (AWS™) which utilizes Bluetooth® technology for wireless power-on/off communication between tool and dust extractor
- AWS™ capable with Auto-Start Wireless Transmitter (part no. 198901-5) sold separately
- Vibration-absorbing back handle and side handle further reduce vibration and increase comfort on the job
- Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears if the bit binds
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs

SPECIFICATIONS


Max. Capacity (concrete drilling)	1-1/8"
Optimum Range (concrete drilling)	3/16" - 5/8"
Max. Capacity (concrete drilling w/ core bit)	2-1/8"
Impact Energy (ft.lbs.)	2.3
Impact Energy (Joules)	3.2 J
Blows Per Minute (variable speed)	0 - 5,000 BPM
No Load Speed (variable speed)	0 - 980 RPM
Vibration Control	Yes
Vibration (m/s²)9
Battery	2X 18V LXT® Lithium-Ion
Overall Length	14-3/4"
Net Weight (with battery)	11 lbs.
Bit Type	Accepts SDS-PLUS
UPC Code (XRH10PTW)	088381-865159
UPC Code (XRH10ZW)	088381-857789

PRODUCT HIGHLIGHTS



PERFORMANCE

X2 LXT® technology delivers up to 140 1/2"x2-3/8" holes per charge using two 18VLXT® 5.0Ah batteries



COMFORT

AVT® is an active internal counterbalance system engineered to reduce vibration



DUST MANAGEMENT

OSHA Table 1 compliant on-board dust extractor has a filter cleaning mechanism for optimum suction



CONTROL

AFT® electronically turns off the motor if rotation of bit is suddenly forced to stop

STANDARD EQUIPMENT

- XRH10ZW - Tool Only
- (2) 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850B)
- 18V LXT® Lithium-Ion Dual Port Charger (DC18RD)
- Side Handle
- Depth Gauge
- Tool Bag

RELATED PRODUCTS

1. Dust Extraction Cup (195173-3)
2. Auto-Start Wireless Transmitter (198901-5)
3. 18V X2 LXT® (36V) Brushless 2.1 Gal. HEPA Filter Dry Dust Extractor/Vacuum, AWS™ (XCV08Z)
4. 3/8" x 6" SDS-PLUS Bit, 3-Cutter, 10/pk (B-61254)
5. 1/2" x 6" SDS-PLUS Bit, 3-Cutter, 10/pk (B-61276)

