

## Focal Point Products

### Louver Installation Instructions

Focal Point Products offers two types of louvers – decorative and functional. Decorative louvers have closed, non-ventilating slats that do not allow air flow. Functional louvers offer the same decorative appeal, but include open slats that allow air flow for ventilation.

**SAFETY FIRST:** When sawing, sanding, nailing or screwing Focal Point polyurethane products wear safety glasses and a dust mask

#### INSTALL A FUNCTIONAL LOUVER

1. Position the louver against the siding in the desired location
2. Make sure the louver is level and trace the outline of the louver with a pencil
3. Once you're sure the cut you're about to make will not go through studs or electrical lines, cut the hole into the wall 2" inside the traced outline
4. Apply polyurethane construction adhesive to the inside of the louver's brickmould, and position the louver in the hole
5. Using non-corrosive screws or nails through the brickmould face, attach the louver to the wall. Countersink the fasteners approximately 1/8"
6. Wipe off any excess adhesive, fill the nail or screw holes with an appropriate filler material and paint the louver with a high-quality, exterior latex or oil based paint

#### INSTALL A DECORATIVE LOUVER

1. Apply polyurethane construction adhesive to the perimeter inside edge of the louver
2. Position the louver in the desired place and make sure it's level
3. Using non-corrosive screws or nails through the brickmould face, attach the louver to the wall. Countersink the fasteners approximately 1/8"
4. Wipe off any excess adhesive, fill the nail or screw holes with an appropriate filler material and paint the louver with a high-quality, exterior latex or oil based paint