

RAIN BIRD®

42SA

Heavy Duty "Simple Adjust" Rotor

*Professional Gear Drive
with added durability and
high performance
Rain Curtain™ nozzle*

*Replacement for:
Rain Bird® 5000™
Orbit® Voyager II™
KRain® K2™
Hunter® PGP™*

SPRAYS 26 TO 38 FEET

ADJUST FROM 40-360°

READY FOR INSTALLATION

3/4" INLET

42SA Superior Gear Drive Rotor Simple To Use:

Find your fixed LEFT edge.

Using the palm of your hand, turn the center cap to the right until it stops. Then turn it to the left until it stops. This is your fixed left edge, which is the starting point from which rotation begins. Arc is preset to rotate 180 degrees (half-circle).

Adjusting the Pattern.

Using a flat bladed screwdriver, turn the arc adjustment screw clockwise (+) to increase the arc or counterclockwise (-) to decrease the arc. Pattern is adjustable from 40 to 360 degrees. Always adjust in the direction of rotation.

Adjusting the Spray Distance.

Using a flat bladed screwdriver, turn the radius reduction screw to reduce the distance of throw up to 25%.

NOTE: To manually pull up the stem, insert a flat bladed screwdriver into the slot located on the side of the stem under the rubber cover.


3.0 GPM Pre installed Nozzle Performance Chart

Pressure PSI	25	35	45	55	65
Radius ft.	35	37	37	37	38
Flow GPM	2.58	3.11	3.59	3.95	4.37

GPM = Gallons Per Minute.

For technical or design service assistance,
please call 1-800-Rain Bird
or visit us at www.rainbird.com

© 2002 Rain Bird Corporation



Rain Bird. The Intelligent use of water™

Made in Mexico

P/N: 173500