

BLACK

BLACK

BLACK

BLACK

BLACK


**EXTREME
STRETCH**

CAUTION! Contains ethylene glycol. May cause mild skin irritation. Do not get in eyes, on skin or clothing. Use gloves and safety glasses. Use in well-ventilated area. Do not ingest. **In an emergency,** call poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

¡PRECAUCIÓN! Contiene etilenglicol. Puede causar irritación leve de la piel. Evite el contacto c/los ojos, la piel y la ropa. Use guantes y gafas de seguridad. Use en un área bien ventilada. No lo ingiera. **En caso de emergencia,** llame a un centro de control de envenenamiento al 800-222-1222. Para más información, consulte la Hoja de datos de seguridad (SDS). Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ WARNING Cancer & Reproductive Harm / **ADVERTENCIA** Cáncer y daños al sistema reproductor—
www.P65warnings.ca.gov

NCCS Calif. ARB VOC < 1.5 wt/wt%
(VOC 27 g/L)

QUESTIONS?/¿PREGUNTAS?

Call/Llame al **888-DAP-TIPS** or visit/o
visite dap.com & click on/ y pulse
en "Ask the Expert."

DAP Products Inc.

Baltimore, MD

Made in the
USA with U.S.

and globally
sourced
materials.

dap.com

600%
TOTAL STRETCH

**EXTREME
STRETCH**
SEALS 3" JOINTS UP TO

**HIGH PERFORMANCE ACRYLIC URETHANE
ELASTOMERIC SEALANT**

- Crackproof & Waterproof
- Adheres to Virtually Any Substrate
- Paintable in 2 Hours
- Easy Water Clean-up & Low Odor
- Interior/Exterior
- Lifetime Guarantee

Read back panel
carefully for cautions!
¡Lea cuidadosamente
el panel posterior!

10.1 fl oz (300 mL)

**EXTREME
STRETCH**

DAP® EXTREME STRETCH is a high performance acrylic urethane elastomeric sealant ideal for sealing a wide variety of interior & exterior surfaces such as windows, doors, siding, trim, molding, sinks, countertops & more. It stretches over 600% & provides superior adhesion & long-lasting durability. **EXTREME STRETCH** forms a flexible, 100% waterproof & weatherproof seal to withstand environmental conditions. It is easy to apply & tool, paintable, low in odor & cleans up with water. Cured sealant is mold & mildew resistant. VOC compliant.

FOR BEST RESULTS: Apply in temperatures above 40°F. Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temps & higher humidity will slow down dry time. Not for continuous underwater use, filling butt joints, surface defects or tuck-pointing. Joint size should not exceed 3" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material. Store away from extreme heat or cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Cut nozzle at a 45° angle to desired bead size. 3. Load cartridge into caulk gun. 4. Fill gap with sealant. 5. Smooth/tool bead. 6. Clean excess wet sealant with damp sponge before it skins over. Dried sealant must be cut or scraped away. 7. Paintable after 2 hours (longer in cool/humid conditions) with latex or oil-based paints. 8. Reseal cartridge for storage & reuse.

COVERAGE: 55 linear ft at 3/16" diameter bead.

LIFETIME GUARANTEE: DAP warrants this product for sealant purposes during the lifetime of your home, when used as directed, within one year of purchase. Call **888-DAP-TIPS**, with your sales receipt and product container available for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.

Para obtener las instrucciones y garantía en español, llame al 888-DAP-TIPS o visite dap.com.