

****IMPORTANT: Read all instructions before beginning application process****



InvisiTread Detailed Application Instructions

Tools Required:

Spreader/Squeegee or Acid Resistant Hudson Sprayer (recommended for larger areas)
2x 5 gallon pails/buckets – clean
Sponge Mop or Wet-Dry Vacuum/Extraction Tool (recommended)
Deck Brush

****PRE-APPLICATION TESTING****

Utilize steps 6 - 9 on a small hidden area or extra tile to determine dwell time for desired traction. Longer dwell time equals higher traction. Start with 6 minutes of dwell time and work up to no more than 15 minutes per application. Occasionally, 2 applications are needed to increase COF to desired levels, extract 1st application and repeat steps 6-9.

Application Process

Step 1: In 1st 5 gallon bucket, mix 6oz Traction Wash per gallon of water, a 1:20 dilution. Use a higher concentration (up to 12 oz/gal) if very dirty or greasy.

Step 2: CLEAN. Clean the floor very well with the Traction Wash solution from step 1. Use the deck brush for the grout and tile.

Step 3: Rinse the floor with clean water and dry. Use a wet dry vacuum or extraction tool, if available. It is ok to leave the grout joints wet or damp.

Step 4: Fill Hudson sprayer (or 2nd bucket, if spreading instead of spraying) with 1 gallon of InvisiTread per 400 sq ft. *Do not dilute. Do not mix chemicals.*

Step 5: Re-fill 1st bucket with 10 oz of Traction Wash per 1 gallon of water for every 1,000 sqft. Set aside. This will be used to neutralize and rinse the InvisiTread after dwell time is completed.

Step 6: APPLY. Spray or spread the InvisiTread onto the area to be treated. Use a liberal amount of product. Coverage should not be more than 500 sq. ft per gallon.

Step 7: DWELL. Allow InvisiTread to dwell for 6 - 15min (exact time determined by your pre-application testing). Keep surface saturated, do not allow to dry out, puddle or run off.

Step 8: RINSE. After dwell time has elapsed pour 1:20 Traction Wash dilution onto the tile and scrub grout joints with brush to break up residue. Extract surface.

Step 9: *Test traction by wetting the surface with clean water and trying to slide foot. If more traction is desired repeat step 6 - 9 for a 2nd application.*****

Step 10: Rinse a 2nd time with clean water and then extract surface. Surface is ready for immediate use.

Clean regularly with Traction Wash™ @ 1:32 dilution, to maintain your enhanced Coefficient Of Friction (COF).

Grout Troubleshooting - if necessary

After grout has completely dried out you might notice some white residue form in a few spots over the next few days. This is simply a salt residue left over after application, scrub with 1:4 dilution of vinegar to water to remove. This does not occur on every application or every type of grout.

Contact customer service at 888-842-3356 with any questions.



Company Profile:

Surface Solutions, LLC

Industry:

Surface Engineering
Consulting
Slip Resistant Treatments
Anti-Graffiti Treatments

Website:

www.InvisiTread.com
www.TotalSurfaceSolution.com

Corporate Address:

356 Millburn Ave.
Suite 7
Millburn, NJ 07041

Contact:

support@totalsurfacesolution.com
888-842-3356