

PRODUCT SHEET

## Non-metallic push-in fittings Carlon®



## Superior pull-out performance and cost efficiency.

Better than ever, Carlon® non-metallic fittings now available in 1/2" and 3/4" sizes.

## Features and benefits

- Easy push-in installation in knockouts—no tools required
- · Certified for one or two cables
- Insertion from inside or outside of enclosures increases installation flexibility
- Snug fit eliminates movement within knockout
- Exceeds pull-out requirements for better cable security
- Distinctive colors to differentiate sizes: 1/2" gray, 3/4" blue
- · UL® Listed, CSA Certified



## Installation:







 $\overline{\phantom{a}}$  02 Installation without cables: Insert the fitting into the knockout from the inside or outside of the enclosure.



03 For two-cable installation: Cables may be inserted individually or together.



Please see product instruction sheet for complete installation instructions and warnings.





Cat. no.	Description	Trade size (in.)	Clamping range (in.)		Suggested application (non-metallic sheathed cable)	Packaging
			min.	max.		
SNM12-6R	Non-metallic fitting ½ in.	1/2	0.21	0.42	14/2 - 12/2 - 10/2 - 14/3 - 12/3 - 10/3 2 cables: 2 x 14/2 - 2 x 12/2 - 1 x 14/2 - 1 x 12/2	Jar of 50 pcs
SNM12-100CP	Non-metallic fitting ½ in.	1/2	0.21	0.42	14/2 - 12/2 - 10/2 - 14/3 - 12/3 - 10/3 2 cables: 2 x 14/2 - 2 x 12/2 - 1 x 14/2 - 1 x 12/2	Bag of 100 pcs
SNM34-6R	Non-metallic fitting ¾ in.	3/4	0.22	0.65	12/2 - 10/2 - 8/2 - 6/2 - 14/3 - 12/3 - 10/3 - 8/3 - 6/3 2 cables: 2 x 12/2 - 2 x 10/2 - 1 x 12/2 - 1 x 10/2	Jar of 40 pcs
SNM34-100CP	Non-metallic fitting ¾ in.	3/4	0.22	0.65	12/2 - 10/2 - 8/2 - 6/2 - 14/3 - 12/3 - 10/3 - 8/3 - 6/3 2 cables: 2 x 12/2 - 2 x 10/2 - 1 x 12/2 - 1 x 10/2	Bag of 100 pcs

Please ask your Thomas & Betts sales representative for a complete catalog of quality Thomas & Betts electrical products or visit us at www.tnb.com. For customer service, call 1-800-816-7809. For technical questions, call 1-888-862-3289.

Thomas Betts

A Member of the ABB Group