



**CELLOFOAM®**  
North America Inc.

## **PERMAFLOAT®** *Performance Dock Flotation*

- Easy to install
- EPS Foam filled for positive buoyancy if breached
- Extra wide ribbing provides easier tool access
- Available in a variety of sizes to meet your specific needs
- Seamless rotationally molded polyethylene shell
- 15 Year Warranty
- FLASH DOT reflector takes the guesswork out of night docking
- Meets Army Core of Engineers Requirements
- Tank Tested Buoyancy Ratings +0/-5%



***Setting the standard for Quality & Service  
in the Marine Industry for over 25 years!***

PERMAFLOAT® Dock Floats offer durable flotation that can be easily attached to any new or existing wood, steel or aluminum dock system. Surprisingly some communities still allow the use of unencapsulated foam insulation to be used as floats when weathering and debris impact can cause bits of EPS foam to be released into the environment. PERMAFLOAT Dock Floats encapsulate the foam with rugged hard plastic walls to ensure our waters remain beautiful and unmarred.

PERMAFLOAT Dock Floats are rotationally molded, eliminating seams that can result in separation and leakage. The nominal .150" thick shell is made of prime virgin polyethylene with ultraviolet inhibitors. This tough shell withstands damage from the sun, saltwater, fresh water, debris, gas and marine organisms. Suitable for Residential and Commercial applications.



*Please contact your Cellofoam  
PERMAFLOAT Dock Flotation Specialist  
for the most accurate assessment of your  
Dock Flotation needs. (800) 531-4734*



## 12" Depth SERIES

Part #	Dimensions	Weight (lb)	Buoyancy* (lb)
RP1412	12" x 48" x 12"	16	207
RP2312	24" x 36" x 12"	21	332
RP2412	24" x 48" x 12"	27	454
RP3412	36" x 48" x 12"	38	700
RP3612	36" x 72" x 12"	55	1061
RP3812	36" x 96" x 12"	73	1412
RP4412	48" x 48" x 12"	49	940
RP4512	48" x 60" x 12"	60	1186
RP4612	48" x 72" x 12"	71	1420
RP4812	48" x 96" x 12"	94	1900



## 16" Depth SERIES

Part #	Dimensions	Weight (lb)	Buoyancy* (lb)
RP2316	24" x 36" x 16"	25	446
RP2416	24" x 48" x 16"	32	598
RP3416	36" x 48" x 16"	44	925
RP3616	36" x 72" x 16"	64	1402
RP3816	36" x 96" x 16"	85	1870
RP3.5616	42" x 72" x 16"	74	1636
RP4416	48" x 48" x 16"	57	1242
RP4516	48" x 60" x 16"	69	1568
RP4616	48" x 72" x 16"	82	1880
RP4816	48" x 96" x 16"	108	2518



### Dimensions are Width x Length x Depth

All weights, buoyancies, and dimensions are nominal and subject to manufacturing tolerances. \* Buoyancy numbers provided are maximum assuming complete submersion. Lower buoyancies will be achieved with less than complete submersion. Purchasers of our floats and lift tanks should engage with professional design experts to incorporate these products into their marine systems.





## 20" Depth SERIES

Part #	Dimensions	Weight (lb)	Buoyancy* (lb)
RP1420	12" x 48" x 20"	22	334
RP2320	24" x 36" x 20"	28	537
RP2420	24" x 48" x 20"	36	731
RP3420	36" x 48" x 20"	50	1132
RP3620	36" x 72" x 20"	72	1718
RP3820	36" x 96" x 20"	95	2295
RP4420	48" x 48" x 20"	64	1522
RP4520	48" x 60" x 20"	78	1923
RP4620	48" x 72" x 20"	93	2307
RP4820	48" x 96" x 20"	122	3092



## 24" Depth SERIES

Part #	Dimensions	Weight (lb)	Buoyancy* (lb)
RP2424	24" x 48" x 24"	41	882
RP3424	36" x 48" x 24"	57	1364
RP3624	36" x 72" x 24"	82	2072
RP3824	36" x 96" x 24"	108	2771
RP4424	48" x 48" x 24"	73	1836
RP4524	48" x 60" x 24"	88	2320
RP4624	48" x 72" x 24"	105	2786
RP4824	48" x 96" x 24"	137	3737



## Additional Sizes & Styles

Part #	Dimensions	Weight (lb)	Buoyancy* (lb)
*RP20728	20" x 72" x 8"	26	356
*RP207210	20" x 72" x 10"	29	443
RP2810	20" x 96" x 10"	39	598
RP2408	24" x 48" x 8"	22	288
RP2418	24" x 48" x 18"	34	652
RP3408	36" x 48" x 8"	32	472

\*Rowing Dock Floats

## 32" Depth SERIES

Part #	Dimensions	Weight (lb)	Buoyancy* (lb)
RP3632	36" x 72" x 32"	105	2678
RP4632	48" x 72" x 32"	131	3648
RP4832	48" x 96" x 32"	167	4920

Dimensions are Width x Length x Depth

Our full line of float specifications and drawings are available online at [www.cellofoam.com](http://www.cellofoam.com)



## 3 YEAR WARRANTY



### Permaport® 3 YEAR WARRANTY

EFFECTIVE 3/6/2008  
LEGACY PERMAPORT ONLY

This warranty applies only to the original purchaser of Cellofoam permaport™. Cellofoam warrants this product to be free from materials and manufacturing defects for a period of 3 years in private use or 1 year in commercial use. The polyethylene shell is warranted against, peeling, cracking, sloughing or excessive fading from UV exposure. This product is filled with positive flotation in the form of expanded polystyrene and should the shell be perforated, the unit will remain afloat. The warranty period begins on the purchase date of the permaport from an authorized permaport dealer, distributor or Cellofoam facility. Warranty claims must be received in writing at the corporate offices of Cellofoam by mail or fax (770-860-1725) within the above specified time periods. All claims must include the dated original bill of sale, and the problem you are experiencing with your permaport along with your contact information.

Upon inspection by a Cellofoam representative to determine if the warranty claim meets the above criteria and that it is deemed defective, we will repair or replace the product or refund your purchase price within a reasonable period of time. Warranty repairs, replacement or refunds will be solely the decision of Cellofoam. If we decide to replace your product we may replace with either a new or reconditioned permaport. Cellofoam will not warrant this product if there is damage from improper installation or abuse, if used for any purpose other than the docking of jet skis, damage by forces of nature including but not limited to ice, wind, fire or flood nor if damaged in shipment or by vandalism.

CELLOFOAM WILL NOT BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES. This warranty is the only warranty for the permaport, and it sets forth all our responsibilities for the permaport. There are no other warranties either expressed or implied regarding this product. Purchaser agrees that any legal action for breach of this warranty shall only be brought in the court of Rockdale, County in Conyers, GA. Regardless of where the permaport was purchased or used.

**CONYERS, GA**  
1961 Rockdale Industrial Blvd. 30012

*For orders and customer  
service requests, contact us at*  
**800-531-4734**  
*floats@cellofoamna.com*

**SALLISAW, OK**  
400 E. Houser Ave. 74955

[www.cellofoam.com](http://www.cellofoam.com)