

A black and white photograph of a room. On the left, there are heavy, dark curtains hanging from a window. In the upper right corner, a chandelier with many crystals is visible. In the lower right corner, a portion of a sofa with cushions is shown. The floor appears to be polished wood. A semi-transparent dark rectangle is overlaid in the center of the image, containing text.

HOW TO DRESS YOUR WINDOW CURTAINS *and* VALANCES

Curtains

| | |
|-----------------|---|
| Grommet..... | 1 |
| Rod Pocket..... | 2 |
| Back Tab..... | 3 |

Valances

| | |
|----------------|---|
| Straight..... | 4 |
| Ascot..... | 5 |
| Waterfall..... | 6 |

GROMMET PANEL



HARDWARE

Traditional or decorative curtain rod.
Curtain rods usually include brackets
and screws.

HANGING INSTRUCTIONS

1. Install curtain hardware on window trim or wall depending on your desired result.
2. Insert curtain rod through each grommet.

TIPS

1. Group the grommets all together in your hand first, then slip them through the rod with ease.
2. Check grommet opening measurement to ensure you purchase a rod size that will fit through the opening.

BACK TAB PANEL



HARDWARE

Traditional or decorative curtain rod. Curtain rods usually include brackets and screws.

HANGING INSTRUCTIONS

1. Install curtain hardware on window trim or wall depending on your desired result.
2. Fabric loops are on the reverse of the curtain. Insert the curtain rod through each fabric loop and adjust curtain panel to create an evenly spaced header.

ROD POCKET PANEL



HARDWARE

Traditional or decorative curtain rod.
Curtain rods usually include brackets
and screws.

HANGING INSTRUCTIONS

1. Install curtain hardware on window trim or wall depending on your desired result.
2. Glide the rod through the rod pocket ensuring the front of the panel is facing forward and pull all the way through.
3. Adjust the header to be spaced evenly and standing up straight for a finished look.

STRAIGHT VALANCE



HARDWARE

Traditional curtain rod brackets and screws.

HANGING INSTRUCTIONS

1. Measure the spots for the curtain rod brackets first.
2. Thread the valance onto the rod and then hang the rod on the brackets. Adjust the valance so it is distributed evenly across the rod.

TIPS

A valance should traditionally cover the top 2-6 inches of your window frame, so brackets should be placed about 4 inches above the top of the window.

ASCOT VALANCE



HARDWARE

Traditional rod and
curtain rod brackets.

HANGING INSTRUCTIONS

1. Measure the spots for the curtain rod brackets first.
2. Thread 3 ascot valances onto the rod and then hang the rod in the brackets. Adjust the curtain so it is distributed evenly across the rod.
3. Put the rod onto the brackets and hang the valance.

TIPS

A valance should traditionally cover the top 2-6 inches of your window frame, so brackets should be placed about 4 inches above the top of the window.

WATERFALL VALANCE



HARDWARE

Detachable curtain rod and
curtain rod brackets.

HANGING INSTRUCTIONS

1. Separate the curtain rod. Hold your first valance with the pattern facing you. Each valance contains a header and a rod pocket on both the left, and right side. Insert the left curtain rod into the bottom of the left rod pocket and thread the valance through.
2. Repeat Step 1 with the second valance.
3. Using the same rod, insert into the rod pocket located on the right side of valance 1, entering through the top. Thread completely through. Valance 1 should now be positioned behind valance 2.
4. Hold the third valance with the pattern facing you. Using the right curtain rod, insert the rod into the right rod pocket of the valance, entering through the bottom.
5. Returning to valance 2, take the side left hanging, and thread onto the right curtain rod from the bottom of the right rod pocket.
6. Set valance and rod onto window. Once the rod is set, expand the headers to connect each valance and eliminate the empty spaces. From here, evenly adjust all valances, and fix any uneven pleats.