

# ROMAN™

THE NO.1 CONTRACTOR BRAND

Technical Data: PRO-732

Updated: 2/8/16



## PRO-732

### Extra-Strength™ Adhesive

#### Clay Wallcovering Adhesive

**Product Number(s):** 10005, 10002, 10001

**Base:** Clay and Modified starches

### Product Information

**General Properties:** Commercial grade clay-based wallcovering adhesive designed to spread easily with a roller. Specifically formulated for wallcovering applications requiring low moisture.

- Recommended for roller application
- High solids/low moisture
- Excellent adhesion
- Maximum wet tack
- Smooth, thick consistency
- LEED compliant

**Recommended Uses:** Medium to heavyweight (Type II and Type III) wallcoverings

**Compatible Coatings:** All ROMAN® primers

**Mildew-Resistant:** All Roman products contain biocides for in-can preservation

### Specification Data

**Percent Solids:** Approximately 48-51%

**Coverage:** Up to approx. 200 square feet per gallon

**Viscosity:** Approximately 105,000 cps

**VOC (actual):** 0.18% ( $\leq 5$  g/L)

**VOC (regulatory):**  $\leq 25$  g/L

**Storage:** Avoid freezing; keep in cool, dry place.

**Drying Time:** Varies, depending on the temperature, ventilation and humidity of the room.

Roman Decorating Products – Calumet City, Illinois

For Technical Help: Call 1-800-488-6117 or Email: [technicalhelp@romandec.com](mailto:technicalhelp@romandec.com)

[www.romandecoratingproducts.com](http://www.romandecoratingproducts.com)

---

## Application Instructions

**Surface Preparation:** Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, loose wallcoverings, damaged wallboard, or plaster. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

**Dilution:** Do not dilute.

**Application Method:** Use only when the room temperature is above 50°F. PRO-732 is recommended for roller application. Avoid contact with the surface of embossed, textured, or delicate wallcoverings.

**Clean-Up:** Before the adhesive dries, remove the excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls.

---

## Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Roman Decorating Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

---

## Limited Warranty

Roman Decorating Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

---

## Caution

**Store in a cool, dry place. DO NOT FREEZE!** Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.