



BEHR ULTRA® Exterior Semi-Gloss Enamel

- Stain-Blocking Paint & Primer[◇]
- Excellent Durability & Hide in Fewer Coats
- Resists Rain Shortly After Application
- Guards Against Damage from Sunlight & Moisture

- Stain & Dirt Resistant
- Low Temperature Application
- Enhanced Mildew Resistant Finish
- Lifetime Limited Warranty*
- Low VOC, 100% Acrylic

No. 5850 ULTRA PURE WHITE®
No. 5853 Deep Base
No. 5854 Medium Base

[◇]A PRIMER COAT MAY BE NEEDED ON SOME SURFACES. SEE PREPARATION AND PRIME FOR DETAILS.



1 Hr Dry Time
2 Hr Recoat Time



250-400 Sq. Ft.
Coverage Per Gallon



Soap & Water
Clean-Up



Protect
from Freezing

FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.

BEHR ULTRA®

Paint, Prime, and Protect with BEHR ULTRA® Exterior Paint. A versatile stain-blocking paint & primer that delivers all weather protection with excellent durability and hide in fewer coats. Paint with confidence knowing ULTRA Exterior resists rain shortly after application and can be applied in low temperatures. The paint film guards against damage from sunlight and moisture, resists stains & dirt, and provides enhanced mildew resistance, ensuring a STAYS LOOKING NEW LONGER® finish.

WHERE TO USE

Ideal for properly prepared, coated or uncoated, exterior surfaces such as: Stucco, Concrete, Masonry, Concrete Masonry Units, Brick, Fiber Cements, Wood, Engineered Wood, Steel, Galvanized Steel, Aluminum, Other Ferrous Metals, Other Non-Ferrous Metals, Architectural Plastics.

PREPARATION & PRIME

Use on properly prepared and cleaned coated and uncoated exterior surfaces. Countersink nailheads, fill and sand smooth. Remove rust, loose or peeling paint. Repair imperfections and sand smooth. Wash off dirt, grease and chalk with detergent and/or powerwash. Remove mildew stains with a mildew stain removing product. Clean and sand new or weathered wood. Scuff sand or degloss smooth or glossy surfaces. Scuff sand or etch metals. Rinse and allow to dry. Caulk windows, doors and other openings. Allow new stucco, plaster and masonry to cure for 30 days before painting. Use BEHR ULTRA® Paint as a primer for repaired or uncoated surfaces, including woods that contain tannins (two primer coats required for redwood and cedar) and heavily stained areas. Lock in stains with the first primer coat; if necessary, apply a second primer coat of BEHR ULTRA Paint. For drastic color changes or when applying deep colors denoted with a dagger (†) on the color chip, apply a tinted primer coat of BEHR ULTRA Paint if needed.

*LIFETIME LIMITED WARRANTY

Behr Process LLC warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified on the label during the warranty period, Behr Process LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **To obtain warranty service, call 1-800-854-0133.** Behr Process LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company representative, call 1-800-854-0133.

APPLICATION

Apply product on dry substrates when air and surface temperatures are between 35-90°F (2-32°C) and will remain between 35-90°F (2-32°C) for at least 4 hours after applying. Allow paint film to dry for at least 60 minutes prior to rain showers when temperatures are between 60-70°F (15-21°C) and 60-70% relative humidity. Lower temperatures, higher humidity or deep colors may increase dry time and/or rain resistance time. Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity. On semi-smooth surfaces, use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or airless sprayer (.015-.021" spray tip, 60 mesh filter). On rough surfaces, use a high quality 3/4-1" nap roller cover. Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon. Certain colors may require additional coats for complete hide. On heavy stains and woods that contain tannins, allow 12-16 hours of dry time between coats. Cooler temperatures or higher humidity may prolong drying time. After 4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant. When applying to vinyl, color choice must be the same color or lighter than the existing color. Do not use on floors.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit Behr.com for painting tips, expert project advice and the perfect color coordination with the ColorSmart by BEHR® Tool.

WARNING If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

⚠ WARNING: This product can expose you to chemicals including ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

WARNING! IRRITANT. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CONTAIN: CRYSTALLINE SILICA and TITANIUM DIOXIDE. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**



©2024 BEHR PROCESS LLC
Santa Ana, CA 92705 U.S.A. • behr.com
VOC <50 g/L • REV. 08/24