

D6000-2 Series Fiberglass Multi Section Extension Ladders



The D6000-2 series fiberglass extension ladders have non-conductive side rails and a duty rating of 250 lbs. The TRACTION-TRED® D rungs are slip resistant and the side rails are interlocking. The rail shields protect the bottom of the rail and the SHU-LOK® shoe pivots easily for use on hard or penetrable surfaces. The exclusive ALFLO® rung joint guarantees TWIST-PROOF® performance.

Features

- Alflo rung joint for Twist-Proof performance
- Base section may be used as a single ladder
- Direct rung to rail connections
- Electrically non-conductive side rails
- Guides at top of base section
- Guides on bottom of fly section
- Interlocking side rails
- Mar-resistant molded end caps
- Rail shield and shoe bracket protects rail
- Rope and pulley system
- Rope clamp ties rope to rung
- Rugged gravity spring locks
- Shoe with slip-resistant pad and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

Specifications

Model No.	Size	Reach Height	Max Working Length	Max. Open Extended Length	Approx. Closed Length	Approx. Shipping Weight Lbs.
D6016-2	 16 ft	16 ft	13 ft	13 ft	8 ft	32.5
D6020-2	20 ft	19 ft	17 ft	17 ft	10 ft	39
D6024-2	24 ft	23 ft	21 ft	21 ft	12 ft	46
D6028-2	28 ft	27 ft	25 ft	25 ft	14 ft	59