

SPREADROCK® PROJECT BUYING GUIDE



SpreadRock® is a real stone coating that can deliver years of solid performance and timeless beauty to all kinds of surfaces, both indoors and out.

It's a simple **THREE-STEP** system that requires the following **specific products and quantities** for desired results...

PRIME IT

1



Textured Primer

Locks into the concrete. Creates an optimal installation surface for SpreadRock.

Coverage: **160 - 200 sq.ft. per gallon**, depending on smoothness of surface and application thickness.

****Use only DAICH primer. Do not substitute.**

SPREADROCK IT

2



SpreadRock® Granite Coating

Coverage: **40 - 60 sq.ft. per gallon, per coat** (two coats required) depending on smoothness of surface and application thickness. **Apply very thin coats for best coverage and results.**

SEAL IT

3



DAICH TracSafe Anti-Slip Sealer

SpreadRock must be sealed for final hardness, water and dirt protection. Seal with TracSafe Anti-Slip Sealer for an optimal combination of surface protection and slip-resistance.

Coverage: **400 sq.ft. per gallon, per coat.**

****Use only DAICH sealers. Do not substitute.**

SPREADROCK® PURCHASE GUIDE FOR COMMON PROJECT SIZES

	Project Size	Textured Primer (Gallons)	SpreadRock (Gallons)	TracSafe (Gallons)
<p>Surface roughness/texture and application thickness can impact SpreadRock coverage. Apply SpreadRock in two very thin coats, pressing firmly with the trowel or squeegee.</p> <p>The purchase quantity suggestions here are calculated using conservative coverage rates to help ensure adequate supply for most projects and user skill levels.</p>	150 Sq.Ft.	1	8	1
	200 sq.ft.	2	10	1
	250 sq.ft.	2	12	2
	300 sq.ft.	2	15	2
	350 sq.ft.	3	18	2
	400 sq.ft.	3	20	2