

## **Flex Seal MINI**

FLEX SEAL® MINI is a rubberized sealant spray coating that sprays out as a liquid, seeps into cracks and holes and dries to a watertight, flexible coating. It's the easy way to coat, seal, and stop leaks fast.

### **Product Features**

- It's an easy-to-use, portable, aerosol spray.
- Sprays out as a liquid and dries as a strong, rubberized coating
- Stays flexible and pliable
- It will last for years.
- It will not sag or drip in summer heat.
- It will not crack or peel in winter cold.
- Stops vibrations and deadens noise
- Protects surface from corrosion
- Can be used on wet or dry surfaces
- Once completely dry, it can be painted any color.
- Available in three (3) colors

### **Sizes:**

MINI 2 oz.

### **Colors:**

Black, Clear and White

### **Recommended Uses**

FLEX SEAL® MINI has many advantageous applications and uses, that when applied correctly, can last for many years. The most common uses for Flex Seal are listed below:

### **Common Flex Seal Applications:**

- Fix leaky roofs, gutters, and downspouts
- Repair RV'S, campers, and mobile homes
- Repair skylights
- Vent Pipes
- For roof drip edges and flashings
- Leaky or broken hose and PVC pipe repairs
- To seal or repair windowsills
- For A/C drip pans, portable A/C units, duct work, and chimneys
- On boats and other personal watercrafts
- For bird baths, ponds, and fountains
- Flat, metal, rubberized and granulated roof repairs and leaks
- Foundations, gravel stops, asphalt shingles, and overlapped seams
- And, much more!

### Recommended surfaces:

- Wood
- Metal
- Tile
- Concrete
- Masonry
- Fabric
- Glass
- Plastic
- Aluminum
- Porcelain
- Dry wall
- Rubber
- Cement
- Some vinyls and so much more!

\*Flex Seal MINI may not be compatible with *all* plastics, vinyls, or rubbers.

### Directions

1. Read entire can. Wear face and eye protection, protective gloves, and clothing.
2. Make sure the surface is clean, dry, and free of grease, oil, and dirt.
3. Shake well.
4. Spray 8" to 12" from surface, using an even, sweeping motion.
5. Apply multiple, even coats until ALL cracks and holes have been filled.
6. **IMPORTANT:** Allow 24 to 48 hours to dry before applying another coat.
7. Let it dry completely. (It usually takes up to 24 to 48 hours to fully cure.)

\*Use Flex Seal MINI ONLY in a well-ventilated area. When using inside, prevent vapor build-up by opening doors and windows.

\*\*Ensure fresh air entry during application and drying.

\*\*\*Do not use near heat, sparks, pilot lights or other sources of ignition.

### FLEX TIPS:

1. Spray a larger area than area where the leak is and feather the edges.
2. For best results, apply multiple coats rather than one thick coat and use at can temperatures above 60°F.
3. Make sure Flex Seal MINI has filled ALL cracks and holes and is FULLY CURED before testing product.
4. If light can pass through, apply additional coats.