



## Technical Data Sheet

Ryobi Lithium-Ion Battery Pack

Battery Voltage: 40V

Battery Capacity: 6Ah / 216Wh

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Lithium-Ion Battery – Rechargeable

**Model Number:**

GP40602

**Issue Date:**

August 2019

Techtronic Industries Power Equipment

P.O. Box 1288

Anderson, SC 29622

**Company Phone Number:**

1-800-860-4050

**Emergency Contact Number:**

**Chemtrec (United States only):** 1-800-424-9300

**(International):** +1-703-741-5970

### SECTION 2: HAZARDS IDENTIFICATION

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

#### ▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.

### SECTION 3: COMPOSITION/INFORMATION OF INGREDIENTS

Refer to battery cell SDS for more information.

## SECTION 4: FIRST AID MEASURES

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

### ▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.
- No exposure during routine handling of product. Risk of exposure occurs only if the battery is mechanically or electrically abused.
- No effect under routine handling and use to eyes, skin, or if inhaled. Ingestion is not likely, given the physical size and state of the cell. If swallowed, seek medical attention immediately.
- If exposure to internal materials within cell due to damaged outer casing, the following actions are recommended:

#### EYE CONTACT:

Flush with water for 10 minutes without rubbing and immediately seek medical attention.

#### SKIN CONTACT:

Wash area immediately with soap and water. If irritation continues, seek medical attention.

#### INHALATION:

Leave area immediately, move to fresh air, and seek medical attention.

#### INGESTION:

If swallowed, contact POISON CONTROL CENTER immediately.

## SECTION 5: FIRE FIGHTING MEASURES

Refer to battery cell SDS for more information.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **PERSONAL PRECAUTIONS:**

- Use standard industrial clothing in normal use.
- If handling large containers of cells, wear steel-toed footwear.

### **ENVIRONMENTAL PRECAUTIONS:**

No special precautions necessary.

### **METHODS FOR CONTAINMENT:**

- Transport container outdoors.
- Always consult and obey all international, federal, and local environmental laws.

### **METHODS FOR CLEANUP:**

No data available

### **OTHER INFORMATION:**

No data available

## **SECTION 7: HANDLING AND STORAGE**

### **HANDLING:**

- Use only approved charging equipment.
- Do not disassemble battery or battery pack.
- Do not puncture, crush, or dispose of in fire.

### **STORAGE:**

To obtain the longest possible battery life, we suggest the following:

- Remove the battery pack from the charger once it is fully charged and ready for use.

For battery pack storage longer than 30 days:

- Store the battery pack where the temperature is below 80°F and away from moisture.
- Store battery packs in a 30%-50% charged condition.
- Every six months of storage, charge the pack as normal.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Refer to battery cell SDS for more information.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Battery pack consists of battery cells assembled in resin enclosure and is a solid odorless product that will burn if incinerated.

## SECTION 10: STABILITY AND REACTIVITY

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

### ▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.

## SECTION 11: TOXICOLOGY INFORMATION

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

### ▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.

## **SECTION 12: ECOLOGICAL INFORMATION**

### **ECOTOXICOLOGICAL INFORMATION:**

None in routine handling of product.

### **TOXICITY:**

No data available

### **PERSISTENCE AND DEGRADABILITY (BIOPERSISTENCY & BIODEGRADABILITY):**

None in routine handling of product.

### **POTENTIAL OF BIOACCUMULATION:**

None in routine handling of product.

### **MOBILITY IN SOIL:**

None in routine handling of product.

### **OTHER ADVERSE EFFECTS:**

No data available

### **DISPOSAL:**

Follow guidelines in Section 13.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

This product contains Lithium-ion batteries. Local, state or federal laws may prohibit disposal of batteries in ordinary trash. Consult your local waste authority for information regarding available recycling and/or disposal options.

### **DISPOSAL:**

- Dispose in accordance with appropriate regulations.
- Always consult and obey all international, federal, provincial/state, and local hazardous waste disposal laws. Some jurisdictions require recycling of this spent product. Battery recycling is encouraged.
- Lithium-ion batteries are safe for disposal in the normal municipal waste stream since they are not defined by the federal government as hazardous waste. However, Lithium-ion batteries are recyclable.
- To preserve natural resources, please recycle or dispose of batteries properly.

### **▲ WARNING:**

- Upon removal, cover the battery pack's terminals with heavy-duty adhesive tape.
- Do not attempt to destroy or disassemble battery pack or remove any of its components.
- Batteries must be recycled or disposed of properly.
- Also, never touch both terminals with metal objects and/or body parts as short circuit may result.
- Keep away from children. Failure to comply with these warnings could result in fire and/or serious injury.
- This product does not contain mercury, cadmium or Lithium (metal).
- DO NOT INCINERATE battery cells.

## SECTION 14: TRANSPORTATION INFORMATION

### U.S. DOT Hazardous Material Regulations (Re: Ground Transport)

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries packed with equipment over 101 watt hours when packaged correctly can travel under 49 CFR 173.185 when travelling by ground in the continental U.S. Must have the IACO label (UN3480 for batteries only, UN3481 for batteries packed with equipment).

### Canada Transport Dangerous Goods (Re: Ground Transport)

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries packed with equipment over 101 watt hours when traveling by ground in Canada must be declared as Dangerous Goods. The batteries must be packaged according to Packing Instruction 965. The following labels must be on the package: DG9 diamond, Red Bordered Lithium-ion warning label (ICAO). The package must also include a UN3480 Lithium-ion batteries label with the net weight of the batteries in kgs. The BOL must also state UN3480, Lithium-ion batteries,9,PGII or UN3481 Lithium-ion batteries packed with equipment,9,PGII.

### International Dangerous Goods Regulations (Re: Air, Sea, Ground Transport)

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries over 101 watt hours packed with equipment when shipped by sea will be considered Class 9 Dangerous Goods must be packaged according to Packing Instruction 965, and contain the following labels: DG9 diamond, Red Bordered Lithium-ion warning label (ICAO), and UN3480/3481 label with the kg of lithium label.

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries over 101 watt hours packed with equipment when shipped by air will be considered Class 9 Dangerous Goods must be packaged according to Packing Instruction 965, and contain the following labels: DG9 diamond, Red Bordered Lithium-ion warning label (ICAO), Cargo Aircraft Only, and a label stating the amount of kgs of lithium in the box.

This rechargeable Lithium-ion battery has passed the relevant transportation test requirements as described in the UN Manual of Tests and Criteria, Part III, section 38.3. UN 38.3 Test Reports are maintained by the company.

## SECTION 15: REGULATORY INFORMATION

Compliant with relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub section 38.3.

### CALIFORNIA PROPOSITION 65

⚠ **WARNING: Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

## SECTION 16: OTHER INFORMATION

The information contained within this document is provided for your information only. In case of any discrepancy, the information provided in the battery cell Safety Data Sheet takes precedence over the information provided in the battery pack Technical Data Sheet.

Prepared by: Techtronic Industries Power Equipment

The batteries referenced herein are considered exempt articles and are not subject to the OSHA Hazard Communication Standard; therefore an SDS is not required. This sheet is being provided as a service to our customers.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. TECHTRONIC INDUSTRIES POWER EQUIPMENT makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereto.

**PONY**

Pony Testing International Group

Report No.: MDIKXCJN51541716

# MSDS Report

Sample  
Description & Model  
Lithium-ion Cell ICR18650/20P

---

Applicant  
EVE Energy Co., Ltd

---

Address  
NO.36,HuiFeng7thRoad,ZhongkaiHi-TechZone,HuiZhou,  
Guangdong,China

---

No.: MDIKXCJN51541716  
Code: mt92f0z



**PONY** 博尼测试  
Pony Testing International Group

www.ponytest.com

☎Hotline: 400-819-5688

北京分公司: 0100-8878-8116

上海分公司: 02122-1870-8866

天津分公司: 0222-2720-0000

广州分公司: 020-3117-5170/5170/5170/5170

深圳分公司: 0755-2666-0000

杭州分公司: 0571-220-5555

成都分公司: 028-6482-2999

武汉分公司: 027-87526-100

重庆分公司: 023-8721-0000

西安分公司: 029-2620-0000

济南分公司: 0531-8721-0000

南京分公司: 025-8129-1122



Pony Testing International Group

Report No.: MDIKXCJN51541716 Date: 03.28.2016 Page 1 of 13

# Material Safety Data Sheet

Reference to GHS/AC.10/30/Rev.6 (GHS)

## Section 1 - Chemical Product and Company Identification

**Chemical product identification**

**Sample Description:** Lithium-Ion Cell

**Sample Model:** ICR18650/ZOP

**Recommended Uses:** N/A

**Restrictions on Use:** N/A

**Supplier name:** EVE Energy Co., Ltd

**Address:** NO.36, HuiFeng 7th Road, Zhongkai Hi-Tech Zone, HuiZhou, Guangdong, China

**Phone number:** 0752-5751932

**FAX:** 0752-2608033

**E-mail:** 018138@evebattery.com

**Emergency phone number:** 0752-5751932

## Section 2 - Hazards Identification

**Emergency overview:** This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture, the below hazards exist.

**CAS#** 1333-86-4

**Classification according to GHS**

Carcinogenicity (2)

Specific target organ toxicity, repeated exposure (1) (lung)

**Label elements**

**Hazard pictogram(s):**



**Signal word:**

Danger

**Hazard statement(s):**

H351 Suspected of causing cancer

H372 Causes damage to organs through prolonged or repeated exposure (lung)



www.ponytest.com

☎MutiLine 400-819-5688

北京总部: 010-82119116	天津分公司: 022-59510000	上海分公司: 021-6631099	深圳分公司: 0755-2662900
青岛分公司: 0532-86706466	重庆分公司: 023-78810850	广州分公司: 020-8220430	广州分公司: 020-8220430
天津分公司: 022-27160710	武汉分公司: 027-86600020	昆明分公司: 0871-87245056	其他办事处: 027-87997127
新疆分公司: 0991-6651156	拉萨分公司: 0891-6950000	成都分公司: 028-16390000	厦门分公司: 0592-5566300





# PONY

Report No. : MDKXCJN51541716 Date:03.28.2016 Page 2 of 13

Pony Testing International Group

### Precautionary statement(s):

#### Prevention:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P280 Wear protective gloves, protective clothing, eye protection and face protection.
- P260 Do not breathe dust.
- P264 Wash skin and clothing thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.

#### Response:

- P308 + P313 IF exposed or concerned: Get medical advice.
- P314 Get medical advice if you feel unwell.

#### Storage

- P405 Store locked up.

#### Disposal:

- P501 Contents handling to approved waste treatment plants.

CAS# 616-38-6

### Classification according to GHS

Flammable liquids (2)

Specific target organ toxicity, single exposure; Narcotic effects (3)

Reproductive toxicity (2)

### Label elements

#### Hazard pictogram(s):



#### Signal word:

Danger

#### Hazard statement(s):

- H225 Highly flammable liquid and vapour
- H336 May cause drowsiness or dizziness
- H361 Suspected of damaging fertility or the unborn child

#### Precautionary statement(s):

#### Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof equipment.

**PONY 尼测试**  
Pony Testing International Group

www.ponytest.com

Hotline 400-819-5688

北京分公司: 010-80111110	天津分公司: 022-57120001	上海分公司: 021-68810000	深圳分公司: 0755-26000000
广州分公司: 020-83210000	武汉分公司: 027-87111111	成都分公司: 028-87710000	重庆分公司: 023-89221111
西安分公司: 029-81110000	南京分公司: 025-11110000	杭州分公司: 0571-87210000	青岛分公司: 0532-20001111
烟台分公司: 0535-11110000	郑州分公司: 0371-55550000	济南分公司: 0531-81110000	海口分公司: 0898-11110000



Pony Testing International Group

- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P280 Wear protective gloves, protective clothing, eye protection and face protection.
- P261 Avoid breathing gas, mist, vapours and spray.
- P271 Use only outdoors or in a well-ventilated area.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.

**Response:**

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P370 + P378 In case of fire: Use the appropriate media put out the fire.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER or doctor, if you feel unwell.
- P308 + P313 IF exposed or concerned: Get medical advice.

**Storage**

- P403 + P235 Store in a well-ventilated place. Keep cool.
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.

**Disposal:**

- P501 Contents handling to approved waste treatment plants.

CAS# 7440-60-8

**Classification according to GHS**

- Specific target organ toxicity, single exposure; Respiratory tract irritation (3)
- Specific target organ toxicity, repeated exposure (1) (liver)
- Hazardous to the aquatic environment, long-term hazard (3)

**Label elements**

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s):

- H335 May cause respiratory irritation
- H372 Causes damage to organs through prolonged or repeated exposure (liver)
- H412 Harmful to aquatic life with long lasting effects

Precautionary statement(s):



www.ponytest.com	☎Hotline 400-819-8688
北京实验室: (010) 84994116	西安实验室: (029) 85590028
天津实验室: (022) 88705800	烟台实验室: (0535) 38101561
长沙实验室: (0731) 77667580	大连实验室: (0411) 86308020
杭州实验室: (0571) 66884200	郑州实验室: (0371) 66105070
上海实验室: (021) 64581029	福州实验室: (0591) 85319029
深圳实验室: (0755) 83756450	广州实验室: (020) 87219096
武汉实验室: (027) 83097127	海口实验室: (0898) 3168218



Pony Testing International Group

**Prevention:**

- P271 Use only outdoors or in a well-ventilated area.
- P260 Do not breathe dust.
- P264 Wash skin and clothing thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.

**Response:**

- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER or doctor, if you feel unwell.

**Storage**

- P403 + P233 Store in a well-ventilated place, Keep container tightly closed.

**Disposal:**

- P501 Contents or container handling to approved waste treatment plants.

CAS# 7429-90-6

Classification according to GHS

- Specific target organ toxicity, repeated exposure (1) (Lung)
- Hazardous to the aquatic environment, long-term hazard (4)

**Label elements**

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

- H372 Causes damage to organs through prolonged or repeated exposure (Lung)
- H413 May cause long-lasting harmful effects to aquatic life

Precautionary statement(s):

**Prevention:**

- P260 Do not breathe dust.
- P264 Wash skin and clothing thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.

**Response:**

- P314 Get medical advice if you feel unwell.

**Storage**

None.

**Disposal:**

www.ponytest.com

Hotline 400-819-8688



北京办事处 (010) 80181116	成都办事处 (028) 87150918	广州办事处 (020) 61052909	深圳办事处 (0755) 26052000
天津办事处 (022) 84700566	杭州办事处 (0571) 81104000	武汉办事处 (027) 87726600	佛山办事处 (0757) 83274210
郑州办事处 (0371) 27100730	长沙办事处 (0731) 84050020	昆明办事处 (0871) 67211400	贵阳办事处 (0851) 81997127
南京办事处 (025) 83301166	重庆办事处 (023) 68300670	西安办事处 (029) 63997900	银川办事处 (0951) 8500018



Pony Testing International Group

P501 Contents handling to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12

**Section 3 - Composition/Information on Ingredients**

Chemical characterization: Mixture.

Chemical Composition	CAS No.	EC#	Weight (%)
Lithium Manganese Nickel And Cobalt	---	---	<35
Carbon black	1333-86-4	215-609-9	<5
Sodium carboxy methyl cellulose	9004-32-4	618-378-6	<2
Polyvinylidene fluoride resin	24937-78-9	607-458-6	<2
Graphite	7782-42-5	231-955-3	<20
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	<5
1,3-Dioxolan-2-one	96-49-1	202-510-0	<5
Carbonic acid, dimethyl ester	616-35-6	210-478-4	<5
Copper	7440-50-8	231-169-6	<15
Aluminium	7429-90-5	231-072-3	<10

**Section 4 - First Aid Measures**

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.



# PONY

Pony Testing International Group

Report No.: MDIKXCJN51541716 Date:03.28.2016 Page 6 of 13

### After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

### After swallowing

Do not induce vomiting. Get medical attention.

**Personal protective equipment for first-aid responders:** No data available.

**Most important symptoms/effects, acute and delayed:** No data available.

**Indication of immediate medical attention and special treatment needed:** No data available.

## Section 5 - Fire Fighting Measures

### Suitable extinguishing media:

Use extinguishing agent suitable for local conditions and the surrounding environment. Such as dry powder, CO<sub>2</sub>.

### Unsuitable extinguishing media:

No data available.

### Specific Hazards arising from the chemical:

#### Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature (>150°C (302°F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

### Specific protective actions for fire-fighters:

Protective equipment: Wear self-contained respirator. Wear fully protective impervious suit.

## Section 6 - Accidental Release Measures

### Personal precautions:

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

### Protective equipment:

No data available.

### Emergency procedures:

Remove ignition sources, evacuate area. Sweep up using a method that does not generate dust. Collect as much of the spilled material as possible, placed the spilled material into a suitable disposal container. Keep spilled material out of sewers, ditches and bodies of water.

**PONY 谱尼测试**  
Pony Testing International Group

www.ponytest.com

Hotline 400-819-5688

北京分公司: 010-83511116	天津分公司: (022) 83100088	上海分公司: 021-60819999	深圳分公司: 0755-26050809
青岛分公司: 0532-88750866	烟台分公司: 0535-380-0150	宁波分公司: 0574-87704499	广州分公司: 020-39026830
大连分公司: 0411-23509730	武汉分公司: 027-83460829	杭州分公司: 0571-82219090	武汉分公司: 027-83460829
济南分公司: 0531-6881180	郑州分公司: 0371-59350050	苏州分公司: 0512-69997002	厦门分公司: 0592-5834000



Pony Testing International Group

**Environmental precautions:**

Do not allow material to be released to the environment without proper governmental permits.

**Methods and materials for containment and cleaning up:**

All waste must refer to the United Nations, the national and local regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## Section 7 - Handling and Storage

**Precautions for safe handling:**

Consumption of food and beverage should be avoided in work areas.

Wash hands with soap and water before eating, drinking.

Ground containers when transferring liquid to prevent static accumulation and discharge.

**Information about fire and explosion protection:**

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

**Conditions for safe storage, including any incompatibilities:****Requirements to be met by storerooms and receptacles**

Store in a cool, dry, well-ventilated place.

**Information about storage in one common storage facility**

Keep away from heat, avoiding the long time of sunlight.

**Further information about storage conditions**

Keep container tightly sealed.

**Specific and use**

No data available.

## Section 8 - Exposure Controls/Personal Protection

**Control parameters**

CAS No.	ACGIH	NIOSH	OSHA
1333-86-4	TLV-TWA 3.5mg/m <sup>3</sup>	REL-TWA 3.5mg/m <sup>3</sup>	PEL-TWA 3.5mg/m <sup>3</sup>
9004-32-4	N/A	N/A	N/A
24937-79-9	N/A	N/A	N/A



Pony Testing International Group

7782-42-6	TLV-TWA 2mg/m <sup>3</sup>	REL-TWA 2.5mg/m <sup>3</sup>	PEL-TWA 15mppcf PEL-TWA 20mppcf
21324-40-3	N/A	N/A	N/A
96-49-1	N/A	N/A	N/A
616-38-6	N/A	N/A	N/A
7440-50-8	TLV-TWA 0.2mg/m <sup>3</sup> TLV-TWA 1mg/m <sup>3</sup>	REL-TWA 1mg/m <sup>3</sup> REL-TWA 0.1mg/m <sup>3</sup>	PEL-TWA 0.1mg/m <sup>3</sup> PEL-TWA 1mg/m <sup>3</sup>
7429-90-5	TLV-TWA 10mg/m <sup>3</sup> TLV-TWA 5mg/m <sup>3</sup>	REL-TWA 2mg/m <sup>3</sup> REL-TWA 5mg/m <sup>3</sup> REL-TWA 10mg/m <sup>3</sup>	PEL-TWA 5mg/m <sup>3</sup> PEL-TWA 15mg/m <sup>3</sup>

**Appropriate engineering controls:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and food.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

**Personal Protective Equipment**

**Respiratory protection:** Wear suitable protective mask in order to reduce the respiratory system. A large number of leakage, wear chemical protective clothing, including self-contained breathing apparatus.

**Hand Protection:** Wear appropriate protective gloves to reduce skin contact.

**Eyes Protection:** Wear safety goggles or eye protection combined with respiratory protection.

**Skin and Body Protection:** Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

**Section 9 - Physical and Chemical Properties**

**Information on basic physical and chemical properties**

- Colour: Green.
- Physical State: Cylindrical.
- Odour: Not available.
- Odour threshold: Not available.
- pH: Not available.