

Tri-Ply® #75 Base Sheet Data Sheet

Updated: 5/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



® TRI-PLY®

#75 Base Sheet



Description

Tri-Ply® #75 Base Sheet is a premium roofing base sheet constructed with a strong glass mat that is coated on both sides to ensure a closed-sheet design to prevent asphalt bleed-through. The sealed sheet also serves as an effective flame retarder for the application of torch-applied modified bitumen membranes.

Uses

Tri-Ply® #75 Base Sheet is engineered for use in the construction of Tri-Ply® built-up and modified bitumen roofs. It is suitable for nailable specifications, such as plywood, where bleed-through is a concern.

Advantages

- Extra strength for excellent nail-holding ability. Superb tensile strength and resilience to bleed-through, thereby reducing risks of splitting and cracking of membrane.

Advantages (Continued)

- Dimensionally stable for improved membrane performance.
- Rolls out flat for easy installation.

Applicable Standards

Meets ASTM D4601, Type II

FM Approved

UL Listed

Miami-Dade County Product Control Approved

Nominal Specifications

Roll Size	3 square roll 320 gross sq. ft. (29.7m ²)
Roll Length	97.5' (29.7 m)
Roll Width	39.4" (1.0 m)
Roll Weight	68 lb. (30.8 kg)