

ALMOND

ALMOND

ALMOND

ALMOND

ALMOND



Kwik Seal®



CAUTION! Contains ethylene glycol. May cause mild skin irritation. Do not get in eye, on skin, or on clothing. Use gloves and safety glasses. Use in well-ventilated area. Do not ingest. In an emergency, call your poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

¡PRECAUCIÓN! Contiene etilenglicol. Puede causar una ligera irritación en la piel. Evite el contacto con los ojos, la piel y la ropa. Use guantes y gafas de seguridad. Utilice en un área con buena ventilación. No lo ingiere. En caso de emergencia, llame a un centro de control de envenenamiento al 800-222-1222. Refiérase a la Ficha de Datos sobre Seguridad (SDS, por sus siglas en inglés) para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ WARNING Cancer and Reproductive Harm / **ADVERTENCIA** Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov

NCCS Calif. ARB <1.5 wt% (VOC 45 g/L)

QUESTIONS?/¿PREGUNTAS?
Call/Llame al 888-DAP-TIPS
or visit/o visite
dap.com & click
on/y pulse en
"Ask the Expert."



DAP Products Inc.
Baltimore, MD 21224

Made in the USA
with U.S. and
globally sourced
materials.
dap.com

Kwik Seal®

Kitchen & Bath Adhesive Caulk



Cured Caulk is Mold & Mildew Resistant

- Bonds Like a Glue, Seals Like a Caulk
- Paintable
- Easy Water Clean-up & Low Odor

Kitchen, Bath & Plumbing



Read back panel for cautions!
¡Lea las precauciones en el panel posterior!

10.1 fl oz (300 mL)

Kwik Seal®



DAP® KWIK SEAL® Kitchen & Bath Adhesive Caulk is an easy-to-use acrylic latex that bonds like a glue & seals like a caulk. Once cured, caulk is mold & mildew resistant & 100% waterproof. Easy to apply, paintable, low in odor & cleans up with water.

FOR BEST RESULTS: Apply in temperatures above 40°F. Not for continuous underwater use. Joint width should not exceed 3/8". If joint depth exceeds 3/8", use foam backer rod. Store away from extreme heat/cold. **Caulk applies white & dries clear in 7-14 days (depending on joint depth, temperatures, & humidity)**

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Cut nozzle at 45° angle to desired bead size. 3. Puncture inner foil seal. 4. Load cartridge into caulk gun. 5. Fill gap or joint with caulk. 6. Smooth bead. 7. Clean up excess wet caulk with a damp sponge before it skins over. Clean hands & tools with warm water. Excess dried caulk must be cut or scraped away. 8. **PAINTABLE.** Allow caulk to dry clear before painting with latex or oil-based paints. 9. Wait at least 36 hours before exposing to water or moisture. 10. Reseal cartridge for storage & reuse.

COVERAGE: 55 linear ft at 3/16" diameter bead

WARRANTY: If product fails to perform when used as directed, within one year of date of purchase, call **888-DAP-TIPS**, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

Para obtener las instrucciones y garantía en español, llame al 888-327-8477 o visite dap.com.