

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.03.2020

Rev. 2

Revision: 03.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name: Comp B**
 - **1.2 Relevant identified uses of the substance or mixture and uses advised against**

Catalyst for EpoxyElite Evo (comp A), EpoxyElite EVO (FR) (comp A), LITOELASTIC EVO (comp A), LITOELASTIC EVO (FR) (comp A), Starlike EVO (comp A), Starlike Crystal EVO (comp A), Starlike ColorCrystal (comp A)

 - **Application of the substance / the mixture** Hardener
 - **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
LITOKOL S.p.A.
Via G.Falcone, 13/1
42048 Rubiera (RE) - ITALY
Tel. +39 0522 626391 - Fax. +39 0522 620150
 - **Further information obtainable from:** LITOKOL S.p.A. - Email: laboratorio@litokol.it
 - **1.4 Emergency telephone number:**
UNITED KINGDOM
 - **National Poisons Information Service (NPIS)** - Tel: +44 844 8920111
 - ITALY - POISON CONTROL CENTERS (24h / 365d) :
 - Milano - Ospedale Niguarda Ca' Granda - Tel. +39 02 66101029
 - Pavia - Centro Nazionale di Informazione Tossicologica - IRCCS Fondazione S. Maugeri - Tel. +39 0382 24444
 - Firenze - Azienda Ospedaliero-Universitaria "Careggi" U.O. Tossicologia Medica - Tel. +39 055 7947819
 - Bergamo - Azienda Ospedaliera Papa Giovanni XXIII - Tel. +39 800 883300
 - Roma - CAV Policlinico "Umberto I" - Tel. 06 49978000
 - Roma - CAV Policlinico "A. Gemelli" - Tel. 06 3054343
 - Roma - CAV "Ospedale Pediatrico Bambino Gesù" - Tel. +39 06 68593726
 - Foggia - Azienda Ospedaliero-Universitaria Foggia - Tel. +39 0881 732326
 - Napoli - Azienda Ospedaliera "A. Cardarelli" - Tel. +39 081 7472870
- LITOKOL S.p.A.
Technical support: Tel. +39 0522 622852 (Monday - Friday: 8.30-12.30 AM , 2.00-6.00 PM)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
 - **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
 - **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
TEPA polymer adduct
3-aminomethyl-3,5,5-trimethylcyclohexylamine
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
- **Precautionary statements**
P102 Keep out of reach of children.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2020

Rev. 2

Revision: 03.03.2020

Trade name: Comp B

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

2.3 Other hazards

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 117317-22-3	TEPA polymer adduct ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1A, H317; STOT SE 3, H335	≥94-<98%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<1.5%
CAS: 9046-10-0 EC number: 618-561-0 Reg.nr.: 01-2119557899-12-XXXX	Polyetheramine ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 3, H412	≥1-<1.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
Protect unharmed eye.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

- No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Wear fully protective suit.
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2020

Rev. 2

Revision: 03.03.2020

Trade name: **Comp B**

(Contd. of page 2)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Pick up mechanically.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Store only in the original receptacle.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Store receptacle in a well ventilated area.
Keep container tightly sealed.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
 - **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

CAS: 9046-10-0 Polyetheramine

Dermal	DNEL / Long term exposure - Systemic effects	2.5 mg/Kg bw/d (workers)
Inhalative	DNEL / Long term exposure - Systemic effects	1.36 mg/m ³ (workers)

· PNECs

CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

PNEC / aqua	0.06 mg/l (freshwater) 0.006 mg/l (marine water)
PNEC / sediment	5.784 mg/Kg dw (freshwater) 0.578 mg/Kg dw (marine water)
PNEC / soil	1.121 mg/Kg dw (sewage treatment plant)

CAS: 9046-10-0 Polyetheramine

PNEC / aqua	0.015 mg/l (freshwater) 150 mg/l (intermittent releases) 0.018 mg/l (marine water)
PNEC / sediment	0.132 mg/Kg dw (freshwater)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2020

Rev. 2

Revision: 03.03.2020

Trade name: Comp B

(Contd. of page 3)

PNEC / soil	0.125 mg/Kg dw (marine water) 0.0176 mg/Kg dw
-------------	--

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Do not eat or drink while working.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Ensure that washing facilities are available at the work place.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.
Short term filter device:
Filter A

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Rubber gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level > 2

· **Eye protection:**



Tightly sealed goggles

Goggles recommended during refilling

· **Body protection:** Light weight protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· **General Information**

· **Appearance:**

· **Form:** Liquid
· **Colour:** Amber coloured
· **Odour:** Amine-like
· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/freezing point:** Undetermined.
· **Initial boiling point and boiling range:** 200 °C

· **Flash point:** 130 °C

· **Flammability (solid, gas):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2020

Rev. 2

Revision: 03.03.2020

Trade name: **Comp B**

(Contd. of page 4)

· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapour pressure:	Not applicable.
· Density at 20 °C:	0.98 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not determined. Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
· Dynamic at 25 °C:	1000 mPas
· Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1,030 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

CAS: 9046-10-0 Polyetheramine

Oral	LD50	2,885 mg/kg (rat)
Dermal	LD50	2,979 mg/kg (rabbit)
Inhalative	LC50 / 4h	>0.74 mg/l (rat)

- **Primary irritant effect:**
 - **Skin corrosion/irritation**
 - Test OECD 439 - Skin irritation tested
 - Causes skin irritation.
 - **Serious eye damage/irritation**
 - Causes serious eye irritation.
 - **Respiratory or skin sensitisation**
 - May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
 - **Carcinogenicity** Based on available data, the classification criteria are not met.
 - **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
 - May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2020

Rev. 2

Revision: 03.03.2020

Trade name: **Comp B**

· **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. of page 5)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

No further relevant information available.

CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC50 / 48h	23 mg/l (daphnia)
EC50 / 72h	>50 mg/l (algae - <i>Scenedesmus capricornutum</i>)
EC50 / 96h	110 mg/l (fish)

CAS: 9046-10-0 Polyetheramine

EC50 / 72h	2.1-15 mg/l (algae)
EC50 / 96h	15 mg/l (fish)
NOEC / 96h	15-600 mg/l (fish)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· Additional ecological information:

· General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Also poisonous for fish and plankton in water bodies.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user

Not applicable.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2020

Rev. 2

Revision: 03.03.2020

Trade name: Comp B

(Contd. of page 6)

· UN "Model Regulation":	Void
---------------------------------	------

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 Regulation (EC) No 1907/2006 (REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals)
 Regulation (EC) No 1272/2008 (CLP - Classification, Labelling and Packaging of substances and mixtures)
 Compilation of Safety Data Sheet: Reg.UE n. 830/2015 (amending Reg.EC n.1907/2006, Annex II)

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **REACH**

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

· **Classification according to Regulation (EC) No 1272/2008**

Skin corrosion/irritation

Serious eye damage/eye irritation

Skin sensitisation

Specific target organ toxicity (single exposure)

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Contact:** LITOKOL S.p.A.

· **Abbreviations and acronyms:**

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

CLP: Classification, Labelling and Packaging

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· *** Data compared to the previous version altered.**

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.03.2019

Rev. 1

Revision: 18.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** EpoxyElite EVO (comp A)**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Application of the substance / the mixture Epoxy mortar**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

LITOKOL S.p.A.
Via G.Falcone, 13/1
42048 Rubiera (RE) - ITALY
Tel. +39 0522 626391 - Fax. +39 0522 620150

Further information obtainable from: LITOKOL S.p.A. - Email: laboratorio@litokol.it**1.4 Emergency telephone number:**

UNITED KINGDOM

• National Poisons Information Service (NPIS) - Tel: +44 844 8920111

ITALY - POISON CONTROL CENTERS (24h / 365d) :

- Milano - Ospedale Niguarda Ca' Granda - Tel. +39 02 66101029
- Pavia - Centro Nazionale di Informazione Tossicologica - IRCCS Fondazione S. Maugeri - Tel. +39 0382 24444
- Firenze - Azienda Ospedaliero-Universitaria "Careggi" U.O. Tossicologia Medica - Tel. +39 055 7947819
- Bergamo - Azienda Ospedaliera Papa Giovanni XXIII - Tel. +39 800 883300
- Roma - CAV Policlinico "Umberto I" - Tel. 06 49978000
- Roma - CAV Policlinico "A. Gemelli" - Tel. 06 3054343
- Roma - CAV "Ospedale Pediatrico Bambino Gesù" - Tel. +39 06 68593726
- Foggia - Azienda Ospedaliero-Universitaria Foggia - Tel. +39 0881 732326
- Napoli - Azienda Ospedaliera "A. Cardarelli" - Tel. +39 081 7472870

LITOKOL S.p.A.

Technical support: Tel. +39 0522 622852 (Monday - Friday: 8.30-12.30 AM , 2.00-6.00 PM)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS07

Signal word Warning**Hazard-determining components of labelling:**

Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight ≤ 700)
formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.03.2019

Rev. 1

Revision: 18.03.2019

Trade name: EpoxyÉlite EVO (comp A)

(Contd. of page 1)

- P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-15%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40-XXXX	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-5%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22-XXXX	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
 - **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
 - **After skin contact:**
If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
 - **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
 - **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
 - **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
 - **Protective equipment:** Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.03.2019

Rev. 1

Revision: 18.03.2019

Trade name: EpoxyÉlite EVO (comp A)

(Contd. of page 2)

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**· 7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.**· 7.2 Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:** No special requirements.**· Information about storage in one common storage facility:** Not required.**· Further information about storage conditions:**

Store in a cool place.

Store in dry conditions.

Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****· Additional information about design of technical facilities:** No further data; see item 7.**· 8.1 Control parameters****· Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Regulatory information WEL (Great Britain): EH40/2018**· DNELs****CAS: 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)**

Oral	DNEL / Long term exposure - Systemic effects	0.75 mg/Kg bw/d (general population)
	DNEL / Short term exposure - Systemic effects	0.75 mg/Kg (general population)
Dermal	DNEL / Long term exposure - Systemic effects	3.6 mg/Kg bw/d (general population)
		8.33 mg/Kg bw/d (workers)
	DNEL / Short term exposure - Systemic effects	3.6 mg/Kg (general population)
		8.33 mg/Kg (workers)
Inhalative	DNEL / Long term exposure - Systemic effects	12.25 mg/m ³ (workers)
	DNEL / Short term exposure - Systemic effects	12.25 mg/m ³ (workers)

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Dermal	DNEL / Long term exposure - Systemic effects	2.35 mg/Kg bw/d (general population)
		3.9 mg/Kg bw/d (workers)
	DNEL / Long term exposure - Local effects	1 mg/Kg (general population)
		1.7 mg/Kg (workers)
	DNEL / Short term exposure - Systemic effects	10 mg/Kg (general population)
		17 mg/Kg (workers)
Inhalative	DNEL / Short term exposure - Local effects	40 mg/Kg (general population)
		68 mg/Kg (workers)
	DNEL / Long term exposure - Systemic effects	4.1 mg/m ³ (general population)
		13.8 mg/m ³ (workers)
	DNEL / Long term exposure - Local effects	1.46 mg/m ³ (general population)
		0.98 mg/m ³ (workers)
	DNEL / Short term exposure - Systemic effects	7.6 mg/m ³ (general population)
		29 mg/m ³ (workers)
	DNEL / Short term exposure - Local effects	2.9 mg/m ³ (general population)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.03.2019

Rev. 1

Revision: 18.03.2019

Trade name: EpoxyÉlite EVO (comp A)

(Contd. of page 3)

	9.8 mg/m ³ (workers)
· PNECs	
CAS: 25068-38-6 Reaction product: bisphenol-A(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	
PNEC / aqua	6 mg/l (freshwater) 0.0006 mg/l (marine water)
PNEC / sediment	0.996 mg/Kg dw (freshwater) 0.0996 mg/Kg dw (marine water)
PNEC / soil	0.196 mg/Kg dw
PNEC / STP	10 mg/l (sewage treatment plant)
CAS: 9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	
PNEC / aqua	0.003 mg/l (freshwater) 0.0254 mg/l (intermittent releases) 0.0003 mg/l (marine water)
PNEC / sediment	0.249 mg/Kg dw (freshwater) 0.0294 mg/Kg dw (marine water)
PNEC / soil	237 mg/Kg dw
PNEC / STP	10 mg/l (sewage treatment plant)
CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivs	
PNEC / aqua	0.0072 mg/l (freshwater) 0.00072 mg/l (marine water)
PNEC / sediment	66.77 mg/Kg dw (freshwater) 6.677 mg/Kg dw (marine water)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Do not eat or drink while working.
 Keep away from tobacco products.
 Avoid close or long term contact with the skin.
 Ensure that washing facilities are available at the work place.
 The usual precautionary measures are to be adhered to when handling chemicals.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.

· **Respiratory protection:**

Filter A/P2



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Butyl rubber, BR
 Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.03.2019

Rev. 1

Revision: 18.03.2019

Trade name: EpoxyÉlite EVO (comp A)

(Contd. of page 4)

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

· Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Appearance:**

· Form:	Pasty
· Colour:	White
· Odour:	Odourless
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· Change in condition

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	Undetermined.

· **Flash point:** Not applicable.

· **Flammability (solid, gas):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

· Explosion limits:

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapour pressure:** Not determined.

· Density at 20 °C:	>1 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

· Solubility in / Miscibility with

· **water:** Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· Viscosity:

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· Solvent content:

· Organic solvents:	0.0 %
· VOC (EC)	0.00 %

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** Reacts with strong acids and oxidising agents.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.03.2019

Rev. 1

Revision: 18.03.2019

Trade name: EpoxyÉlite EVO (comp A)

(Contd. of page 5)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

CAS: 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

CAS: 9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Oral LD50 26,800 mg/kg (rat)

Dermal LD50 4,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

EC50 / 48h 1.8 mg/l (crustacea - Daphnia magna)

LC50 / 96h 2 mg/l (fish - Oncorhynchus mykiss)

ErC50 / 72h 11 mg/l (algae - Scenedesmus capricornutum)

CAS: 9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

EC50 / 48h 1.6 mg/l

LC50 / 96h 0.55 mg/l (fish)

EC50 / 72h 1.8 mg/l (algae)

NOEC / 21d 0.3 mg/l

LC50 / 48h 0.73 mg/l (fish)

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

EC50 / 48h 6.07 mg/l (crustacea - Daphnia magna)

LC50 / 96h >500 mg/l (fish)

EC50 / 72h 843 mg/l (algae)

- **12.2 Persistence and degradability**

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Ready Biodegradability / 28d 87 %

- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.03.2019

Rev. 1

Revision: 18.03.2019

Trade name: EpoxyÉlite EVO (comp A)

(Contd. of page 6)

- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
 - **Remark:** Harmful to fish
- **Additional ecological information:**
 - **General notes:**
 - Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation**
 - Disposal must be made according to official regulations.
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
 - **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name	
· ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA	
· Class	Void
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - Regulation (EC) No 1907/2006 (REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals)
 - Regulation (EC) No 1272/2008 (CLP - Classification, Labelling and Packaging of substances and mixtures)
 - Compilation of Safety Data Sheet: Reg.UE n. 830/2015 (amending Reg.EC n.1907/2006, Annex II)
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category E2** Hazardous to the Aquatic Environment
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
 - **REACH**
 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.03.2019

Rev. 1

Revision: 18.03.2019

Trade name: EpoxyÉlite EVO (comp A)

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

· **Classification according to Regulation (EC) No 1272/2008**

Skin corrosion/irritation

Serious eye damage/eye irritation

Skin sensitization

Hazardous to the aquatic environment - chronic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Contact: LITOKOL S.p.A.**

· **Abbreviations and acronyms:**

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

CLP: Classification, Labelling and Packaging

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3