



**IF YOU HAVE ANY QUESTIONS OR CONCERNS, OR ARE MISSING PARTS
DO NOT RETURN TO THE STORE!**

PLEASE CALL OUR CONSUMER HOTLINE AT 1-800-253-4642

INSTRUCTION MANUAL FOR 65HR8

LIMITED WARRANTY

Root-Lowell Manufacturing Company warrants to the original purchaser only that this product will continue to function as intended if used in accordance with the operating instructions (under NORMAL CONSUMER USE) for one year. If the product fails to function as intended--DO NOT RETURN IT TO THE STORE--call our CONSUMER SERVICE HOTLINE at 1-800-253-4642 (toll free) for fast service. We will, at our option, repair or replace any non-functioning parts without charge (*shipping and handling charges will apply*). Root-Lowell Manufacturing Company shall have the option of requiring the return of the non-functioning product together with the proof of purchase to establish a claim under this warranty. This warranty does not apply to damage resulting from accident, misuse, neglect, alterations, operation not in accordance with instructions, commercial use or normal wear.

ANY IMPLIED WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR CONSUMER USE, ARE LIMITED TO THE DURATION SPECIFIED ABOVE. ROOT-LOWELL MANUFACTURING COMPANY'S LIABILITY IS LIMITED SOLELY TO THE REPAIR OR REPLACEMENT OF THE NON-FUNCTIONING PRODUCT OR PART. ROOT-LOWELL MANUFACTURING COMPANY EXCLUDES LIABILITY UNDER THIS WARRANTY FOR ANY AND ALL INCIDENTAL AND CONSEQUENTIAL LOSS OR DAMAGE.

Some states do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of incidental consequential damages, so these limitations or exclusions may not apply to you. This warranty gives you specific legal rights and you may have other rights which vary from state to state.

INTRODUCTION

This hose reel has been manufactured from high quality materials and the most suitable components. The system winds the hose in automatically, using a spring drive. An automatic gripping mechanism allows the automatic winding system to be locked so that the length of unwound hose can be adjusted. An automatic alignment device ensures that the hose winds onto the reel correctly. The wall mounting bracket allows the hose reel to pivot 180 degrees for ease of use. The high-quality hose is capable of a high rate of flow at high pressure.

ATTENTION: BEFORE USE

PLEASE NOTE:

- The hose is NOT suited for drinkable water.
- Only factory trained professionals should attempt to open the cover on the hose reel.
- Please CAREFULLY read the instructions before use.

PARTS LIST

HOSE and REEL (1 each)

SPRAY NOZZLE (1 each)

MOUNTING BRACKET (1 each)

METAL BRACKET PIVOT TUBE (1 each)

EXPANSIVE BOLTS (set of 4)

TOOLS NEEDED FOR INSTALLATION

1. POWER DRILL

2. 1/2" MASONRY DRILL BIT

3. 1/2" SOCKET WRENCH